



# CAMBRIDGE ISOTOPE LABORATORIES

## PRODUCT AND COMPANY IDENTIFICATION

Product Name: EN-1948-4 WHO (DIOXIN-LIKE) PCB "STARTER KIT"  
Catalog No: EC-1948-4W-KIT  
Company: Cambridge Isotope Laboratories Inc.  
50 Frontage Road  
Andover, MA. 01810  
USA  
Telephone: 1-800-322-1174 International information 1-978-749-8000  
Emergency: 1-800-424-9300 International Emergency 1-703-741-5970

## HAZARDS IDENTIFICATION

### Emergency Overview

### OSHA Hazards

Irritant/Harmful

### GHS Classification(s)

Flammable liquids -Cat 1  
Acute toxicity, Inhalation -Cat 4  
Skin irritation -Cat 2  
Eye irritation -Cat 2A  
Specific target organ toxicity - single exposure -Cat 3, Central nervous system  
Aspiration hazard -Cat 1  
Chronic aquatic toxicity -Cat 2

### GHS Label elements, including precautionary statements



Pictograms

Signal word Danger

Hazard statement(s)

See individual Safety Data Sheets

## COMPOSITION

Each kit contains:

EC-5380	EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOCTANE:NONANE
EC-5370	EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE
EC-5372	EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE
EC-5371	EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE



# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/<sup>13</sup>C<sub>12</sub>, 99%) IN ISOCTANE:NONANE

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 19/08/2014

Revision date: 05/02/2016

Supersedes: 19/08/2014

Version: 2.0

**EC-5380**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixtures  
Product name. : EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/<sup>13</sup>C<sub>12</sub>, 99%) IN ISOCTANE:NONANE  
Product code : EC-5380

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : For professional use only.  
Industrial.

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-703-741-5970 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 1 H224  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
STOT SE 3 H336  
Asp. Tox. 1 H304  
Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

#### Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11  
Xn; R20  
Xn; R65  
N; R51/53

Full text of R-phrases: see section 16

#### Classification (GHS-US)

Flam. Liq. 1 H224  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
STOT SE 3 H336  
Asp. Tox. 1 H304  
Aquatic Acute 2 H401

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Chronic 2

H411

### Adverse physicochemical, human health and environmental effects

Central Nervous System.

## 2.2. Label elements

### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: N-NONANE UNLABELED

Hazard statements (CLP)

: H224 - Extremely flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors  
P264 - Wash Both hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment

### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H224 - Extremely flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness  
H401 - Toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors  
P264 - Wash Both hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear protective clothing, protective gloves  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER/doctor/physician if you feel unwell  
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)  
P331 - If swallowed, do NOT induce vomiting  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362 - Take off contaminated clothing and wash before reuse  
P370+P378 - In case of fire: Use Alcohol resistant foam., Carbon dioxide., Dry chemical., Water spray for extinction  
P391 - Collect spillage  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to Comply with applicable regulations.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	34.151168094 - 95.172647705	R10 Xn; R20 Xn; R65 R67 Xi; R38
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC no) 208-759-1 (EC index no) 601-009-00-8	4.827326943 - 65.846865187	Xi; R38 N; R50/53 R67 F; R11
2,3',4,4',5-PENTACB UNLABELED	(CAS No) 31508-00-6 (EC no) 215-648-1 (EC index no) 602-039-00-4	0.000000084 - 0.000685069	Xn; R22
3,3',4,4'-TETRACB UNLABELED	(CAS No) 32598-13-3 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	R33 N; R50/53
3,4,4',5-TETRACB UNLABELED	(CAS No) 70362-50-4 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	N; R50/53 R33
2,3,3',4,4'-PENTACB UNLABELED	(CAS No) 32598-14-4 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	Xn; R22 R33 N; R50/53
2,3,4,4',5-PENTACB UNLABELED	(CAS No) 74472-37-0 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	Xn; R22 N; R50/53
2',3,4,4',5-PENTACB UNLABELED	(CAS No) 65510-44-3 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	R33
3,3',4,4',5,5'-HEXACB UNLABELED	(CAS No) 32774-16-6 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	N; R50/53 Xn; R22
3,3',4,4',5-PENTACB UNLABELED	(CAS No) 57465-28-8 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	R33
2,3,3',4,4',5,5'-HEPTACB UNLABELED	(CAS No) 39635-31-9 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	R33
2,3,3',4,4',5-HEXACB UNLABELED	(CAS No) 38380-08-4 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	R33
2,3',4,4',5,5'-HEXACB UNLABELED	(CAS No) 52663-72-6 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	R33
2,3,3',4,4',5'-HEXACB UNLABELED	(CAS No) 69782-90-7 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	R33
3,3',4,4'-TETRACB (PCB-77) (13C12, 99%)	(CAS No) 105600-23-5 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20 N; R50/53
3,4,4',5-TETRACB (PCB-81) (13C12, 99%)	(CAS No) 208461-24-9 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Directive 67/548/EEC
2,3',4,4',5-PENTACB (PCB-118) (13C12, 98%)	(CAS No) 104130-40-7 (EC no) 215-648-1 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33
2',3,4,4',5-PENTACB (PCB-123) (13C12, 99%)	(CAS No) 208263-64-3 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33
2,3,3',4,4'-PENTACB (PCB-105) (13C12, 99%)	(CAS No) 208263-62-1 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 Xi; R41 N; R50/53 R33
2,3,4,4',5-PENTACB (PCB-114) (13C12, 99%)	(CAS No) 208263-63-2 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33
2,3,3',4,4',5-HEXACB (PCB-156) (13C12, 99%)	(CAS No) 208263-68-7 (EC index no) 602-039-00-4	0.0000014	N; R50/53 Xn; R48/21/22 R33
3,3',4,4',5-PENTACB (PCB-126) (13C12, 99%)	(CAS No) 208263-65-4 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20 N; R50/53 R33
3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%)	(CAS No) 32774-16-6 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 Xn; R48/20/21/22
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%)	(CAS No) 33025-41-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%)	(CAS No) 39635-33-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
2,3',4',5-TETRACB (PCB-70) (13C12, 99%)	(CAS No) 208263-81-4 (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
2,3,3',5,5'-PENTACB (PCB-111) (13C12, 99%)	(CAS No) 235416-29-2 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%)	(CAS No) 39635-35-3 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%)	(CAS No) 35065-30-6 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33
2,3,3',4,4',5,5'-HEPTACB (PCB-189) (13C12, 99%)	(CAS No) 208263-73-4 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33
2,3,3',4,4',5'-HEXACB (PCB-157) (13C12, 99%)	(CAS No) 235416-30-5 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33
2,3',4,4',5,5'-HEXACB (PCB-167) (13C12, 99%)	(CAS No) 208263-69-8 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	34.151168094 - 95.172647705	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC no) 208-759-1 (EC index no) 601-009-00-8	4.827326943 - 65.846865187	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4,4',5-PENTACB UNLABELED	(CAS No) 31508-00-6 (EC no) 215-648-1 (EC index no) 602-039-00-4	0.000000084 - 0.000685069	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4'-TETRACB UNLABELED	(CAS No) 32598-13-3 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,4,4',5-TETRACB UNLABELED	(CAS No) 70362-50-4 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4'-PENTACB UNLABELED	(CAS No) 32598-14-4 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	Eye Dam. 1, H318 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4,4',5-PENTACB UNLABELED	(CAS No) 74472-37-0 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2',3,4,4',5-PENTACB UNLABELED	(CAS No) 65510-44-3 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5,5'-HEXACB UNLABELED	(CAS No) 32774-16-6 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5-PENTACB UNLABELED	(CAS No) 57465-28-8 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5,5'-HEPTACB UNLABELED	(CAS No) 39635-31-9 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5-HEXACB UNLABELED	(CAS No) 38380-08-4 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4,4',5,5'-HEXACB UNLABELED	(CAS No) 52663-72-6 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5'-HEXACB UNLABELED	(CAS No) 69782-90-7 (EC index no) 602-039-00-4	0.000000014 - 0.000114178	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4'-TETRACB (PCB-77) (13C12, 99%)	(CAS No) 105600-23-5 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,4,4',5-TETRACB (PCB-81) (13C12, 99%)	(CAS No) 208461-24-9 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4,4',5-PENTACB (PCB-118) (13C12, 98%)	(CAS No) 104130-40-7 (EC no) 215-648-1 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2',3,4,4',5-PENTACB (PCB-123) (13C12, 99%)	(CAS No) 208263-64-3 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4'-PENTACB (PCB-105) (13C12, 99%)	(CAS No) 208263-62-1 (EC index no) 602-039-00-4	0.0000014	Eye Dam. 1, H318 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4,4',5-PENTACB (PCB-114) (13C12, 99%)	(CAS No) 208263-63-2 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5-HEXACB (PCB-156) (13C12, 99%)	(CAS No) 208263-68-7 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5-PENTACB (PCB-126) (13C12, 99%)	(CAS No) 208263-65-4 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%)	(CAS No) 32774-16-6 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%)	(CAS No) 33025-41-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%)	(CAS No) 39635-33-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4',5-TETRACB (PCB-70) (13C12, 99%)	(CAS No) 208263-81-4 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',5,5'-PENTACB (PCB-111) (13C12, 99%)	(CAS No) 235416-29-2 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%)	(CAS No) 39635-35-3 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%)	(CAS No) 35065-30-6 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5,5'-HEPTACB (PCB-189) (13C12, 99%)	(CAS No) 208263-73-4 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5'-HEXACB (PCB-157) (13C12, 99%)	(CAS No) 235416-30-5 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4,4',5,5'-HEXACB (PCB-167) (13C12, 99%)	(CAS No) 208263-69-8 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	Classification (GHS-US)
N-NONANE UNLABELED	(CAS No) 111-84-2	34.151168094 - 95.172647705	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304
ISOOCTANE UNLABELED	(CAS No) 540-84-1	4.827326943 - 65.846865187	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R-, H- and EUH-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
unsuitable extinguishing media	: Do not use a heavy water stream.



# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapor.  
Explosion hazard : May form flammable/explosive vapor-air mixture.  
Reactivity : Vapors may form explosive mixture with air.

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Avoid breathing dust, mist or spray. Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust, mist or spray. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Provide good ventilation in process area to prevent formation of vapor.  
Hygiene measures : Wash Both hands thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.  
Storage conditions : Store at room temperature away from light and moisture.  
Incompatible products : Strong bases. strong acids.  
Incompatible materials : Heat sources. Sources of ignition. Direct sunlight.

### 7.3. Specific end use(s)

No additional information available


## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.000000000 ppm Central Nervous System impairment.

### 8.2. Exposure controls

- Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



- Hand protection : Wear protective gloves.



# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information	: When using, do not eat, drink or smoke.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

*The properties listed below are for the solvent, the main component of this mixture.*

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 128.3 g/mol
Color	: Colorless.
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31.0 °C (87.8 °F) - closed cup
Self ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.718 g/ml
Solubility	: Water: 0 %
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 0.87 - 2.9 % (V)

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapors may form explosive mixture with air.

### 10.2. Chemical stability

See storage and expiration date on CoA.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Sparks. Heat. Direct sunlight. Overheating. Open flame. Extremely high or low temperatures.

### 10.5. Incompatible materials

strong acids. Strong bases.

### 10.6. Hazardous decomposition products

May release flammable gases. fume. Carbon monoxide. Carbon dioxide.

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE	
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
LC50 inhalation rat (ppm)	3200 ppm/4h
ATE (gases)	3200.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
ATE (dust, mist)	1.500 mg/l/4h

3,4,4',5-TETRACB UNLABELED (70362-50-4)	
	LD50 - Oral - guinea pig - 1 mg/kg

N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
LC50 inhalation rat (ppm)	3200 ppm/4h
ATE (gases)	3200.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
ATE (dust, mist)	23.760 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. Skin - rat - Skin irritation - Draize test
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: May be fatal if swallowed and enters airways. Based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Harmful if inhaled.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

3,3',4,4'-TETRACB UNLABELED (32598-13-3)	
LC50 fish 1	> 0.002 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	> 0.002 mg/l Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

3,4,4',5-TETRACB UNLABELED (70362-50-4)	
LC50 fish 1	Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

3,3',4,4'-TETRACB (PCB-77) (13C12, 99%) (105600-23-5)	
LC50 fish 1	Pimephales promelas (fathead minnow) - 96 h

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>3,3',4,4'-TETRACB (PCB-77) (13C12, 99%) (105600-23-5)</b>	
EC50 Daphnia 1	Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

<b>2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%) (35065-30-6 (Unlabeled))</b>	
LC50 fish 1	0.034 mg/l Pimephales promelas (fathead minnow) - 96 h

### 12.2. Persistence and degradability

<b>EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

<b>EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE</b>	
Log Pow	5.65
Bioaccumulative potential	Not established.

<b>3,3',4,4'-TETRACB UNLABELED (32598-13-3)</b>	
Bioconcentration factor (BCF REACH)	81.5
Bioaccumulative potential	Bioaccumulation: Oryzias latipes - 20 d      Bioconcentration factor (BCF): 81.5.

<b>2,3',4,4',5-PENTACB UNLABELED (31508-00-6)</b>	
Log Pow	7.12

<b>3,3',4,4'-TETRACB (PCB-77) (13C12, 99%) (105600-23-5)</b>	
Bioaccumulative potential	Bioaccumulation: Oryzias latipes - 20 d      Bioconcentration factor (BCF): 81.5.

<b>2,3',4,4',5-PENTACB (PCB-118) (13C12, 98%) (104130-40-7)</b>	
Log Pow	7.12

<b>N-NONANE UNLABELED (111-84-2)</b>	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

<b>3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%) (32774-16-6 (Unlabeled))</b>	
Log Pow	6.7

<b>2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%) (35065-30-6 (Unlabeled))</b>	
Log Pow	8.27

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.

Waste disposal recommendations : Dispose of contents/container to Comply with applicable regulations. Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

### 14.1. UN number

UN-No.(DOT) : 1920

DOT NA no. UN1920

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.2. UN proper shipping name

DOT Proper Shipping Name : Nonanes  
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger  
DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
Marine pollutant : No



### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

Packing group (ADR) : III  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 30  
Classification code (ADR) : F1  
Danger labels (ADR) : 3 - Flammable liquids



Orange plates : An orange rectangular plate with a black border. The number '30' is in the top half and '1920' is in the bottom half, both in black.

Tunnel restriction code : D/E  
Limited quantities (ADR) : 5L  
EAC : 3Y  
Excepted quantities (ADR) : E1

#### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

MFAG-No : 128

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

### 14.4. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

### 14.5. Special precautions for user

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
-------------------------------------	--

#### N-NONANE UNLABELED (111-84-2)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
-------------------------------------	--

#### ISOOCTANE UNLABELED (540-84-1)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

### 15.2. International regulations

#### CANADA

#### EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### 15.2.1. National regulations

No additional information available

### 15.3. US State regulations

#### EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE()

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.
----------------------------	---

#### N-NONANE UNLABELED (111-84-2)

U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### ISOOCTANE UNLABELED (540-84-1)

U.S. - Massachusetts - Right To Know List  
 U.S. - Pennsylvania - RTK (Right to Know) List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
R10	Flammable
R11	Highly flammable
R20	Harmful by inhalation
R22	Harmful if swallowed
R33	Danger of cumulative effects
R38	Irritating to skin
R41	Risk of serious damage to eyes
R48	Danger of serious damage to health by prolonged exposure
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed
R48/21/22	Harmful: danger of serious damage to health by prolonged exposure in contact with skin and if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness


# EN-1948-4 WHO PCB CALIBRATION SERIES (CS1-CS6) (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5380

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 3 Serious Hazard
- Physical : 0 Minimal Hazard

### CIL Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*





# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 15/08/2014

Revision date: 24/09/2019

Supersedes: 15/08/2014

Version: 2.0

EC-5370

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixtures  
Product name : EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE  
Product code : EC-5370

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000

[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)

International: 1-703-741-5970 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R10  
Xn; R20  
Xn; R65  
Xi; R36/38  
R67

Full text of R-phrases: see section 16

#### GHS-US classification

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Central Nervous System. Flammable liquid and vapor. May cause drowsiness or dizziness. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. Label elements

#### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Hazardous ingredients

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : N-NONANE UNLABELED
- : H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.  
P264 - Wash Both hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective clothing, protective gloves.

#### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

Hazard statements (GHS-US)

Precautionary statements (GHS-US)

- : Danger
- : H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness
- : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.  
P264 - Wash Both hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective clothing, protective gloves.  
P301+P310 - If swallowed: Immediately call a poison center or doctor  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a poison center or doctor if you feel unwell  
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)  
P331 - Do NOT induce vomiting.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 - Store in a well-ventilated place. Keep cool.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container to Comply with applicable regulations

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.99996	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%)	(CAS-No.) 39635-33-1 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000014	N; R50/53 R33 R48
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%)	(CAS-No.) 33025-41-1 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000013	N; R50/53 R33 R48
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%)	(CAS-No.) 39635-35-3 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000013	N; R50/53 R33 R48

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.99996	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%)	(CAS-No.) 39635-33-1 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%)	(CAS-No.) 33025-41-1 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000013	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%)	(CAS-No.) 39635-35-3 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000013	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS-No.) 111-84-2	99.99996	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%)	(CAS-No.) 39635-33-1 (Unlabeled)	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%)	(CAS-No.) 33025-41-1 (Unlabeled)	0.000013	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%)	(CAS-No.) 39635-35-3 (Unlabeled)	0.000013	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H- phrases: see section 16

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Alcohol resistant foam.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Reactivity	: Flammable liquid and vapor. Vapors may form flammable mixture with air.

#### 5.3. Advice for firefighters

Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Avoid all contact with skin, eyes, or clothing. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). Take precautionary measures against static discharges.

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store in a well-ventilated place. Keep container tightly closed. Keep dry. Ground/bond container and receiving equipment.
- Storage conditions : Store at room temperature away from light and moisture.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.

### N-NONANE UNLABELED (111-84-2)

Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment : Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.



Materials for protective clothing : Wear suitable protective clothing and gloves.  
Hand protection : protective gloves.  
Eye protection : Chemical goggles or face shield. Chemical goggles or safety glasses.  
Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.  
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator.  
Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

*The properties listed below are for the solvent, the main component of this mixture.*

Physical state : Liquid  
Appearance : Liquid  
Molecular mass : 128.3 g/mol  
Color : Colorless  
Odor : No data available  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : Not applicable  
Freezing point : -53 °C (- 63 °F) - lit  
Boiling point : 151 °C (304 °F) - lit  
Flash point : 31 °C (87.8 °F) - closed cup  
Auto-ignition temperature : 205 °C (401 °F)  
Decomposition temperature : No data available  
Flammability (solid, gas) : Not applicable  
Vapor pressure : 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Specific gravity / density : 0.718 g/ml at 25 °C (77 °F)  
Solubility : Water: 0.0002 % at 25 °C (77 °F) - slightly soluble  
Log Pow : 5.65  
Log Kow : No data available  
Viscosity, kinematic : <= 1.008 mm<sup>2</sup>/s at 20 °C (68 °F)  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : 0.87 - 2.9 % (V)

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor. Vapors may form flammable mixture with air.

### 10.2. Chemical stability

See storage and expiration date on CoA.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available



# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.6. Other adverse effects

Other adverse effects : Disposal must be done according to official regulations. Very toxic to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.

Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No.(DOT) : 1920  
DOT NA no. UN1920

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Nonanes  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 242

### 14.3. Additional information

Emergency Response Guide (ERG) Number : 128  
Other information : No supplementary information available.

### Overland transport

Packing group (ADR) : III  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 30  
Classification code (ADR) : F1  
Hazard labels (ADR) : 3 - Flammable liquids



# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Orange plates : 

30
1920

Tunnel restriction code (ADR) : D/E  
Limited quantities (ADR) : 5l  
EAC : 3Y  
Excepted quantities (ADR) : E1

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
MFAG-No : 128

### Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L  
Civil Aeronautics Law : Flammable liquids

### 14.4. Environmental hazards

Other information : No supplementary information available.

### 14.5. Special precautions for user

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%) (33025-41-1 (Unlabeled))	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%) (39635-33-1 (Unlabeled))	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%) (39635-35-3 (Unlabeled))	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313
N-NONANE UNLABELED (111-84-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

##### EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

Listed on the Canadian DSL (Domestic Substances List)

##### N-NONANE UNLABELED (111-84-2)

Listed on the Canadian DSL (Domestic Substances List)

#### 15.2.1. National regulations

No additional information available

### 15.3. US State regulations

##### EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

##### 2,3,4,4'-TETRACB (PCB-60) (13C12, 99%) (33025-41-1 (Unlabeled))

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	No	Yes	

##### 3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%) (39635-33-1 (Unlabeled))

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	

##### 2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%) (39635-35-3 (Unlabeled))

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	

##### N-NONANE UNLABELED (111-84-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

##### 2,3,4,4'-TETRACB (PCB-60) (13C12, 99%) (33025-41-1 (Unlabeled))

###### State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List

##### 3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%) (39635-33-1 (Unlabeled))

###### State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) List

# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%) (39635-33-1 (Unlabeled))</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
<b>2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%) (39635-35-3 (Unlabeled))</b>
<b>State or local regulations</b>
U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List
<b>N-NONANE UNLABELED (111-84-2)</b>
<b>State or local regulations</b>
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

## SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R10	Flammable
R20	Harmful by inhalation
R33	Danger of cumulative effects
R36/38	Irritating to eyes and skin
R48	Danger of serious damage to health by prolonged exposure
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



# EN-1948-4 PCB SAMPLING STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5370

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### Hazard Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

### CIL Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*



# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 15/08/2014

Revision date: 25/09/2019

Supersedes: 15/08/2014

Version: 2.0

EC-5372

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixtures  
Product name : EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE  
Product code : EC-5372

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-703-741-5970 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Acute Tox. 4 (Inhalation:vapour) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
STOT SE 3 H336  
Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R10  
Xn; R20  
Xn; R65  
Xi; R36/38  
R67

Full text of R-phrases: see section 16

#### GHS-US classification

Flam. Liq. 3 H226  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
STOT SE 3 H336  
Asp. Tox. 1 H304

Full text of H statements : see section 16

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Adverse physicochemical, human health and environmental effects

Central Nervous System. Flammable liquid and vapor. May cause drowsiness or dizziness. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

## 2.2. Label elements

### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: N-NONANE UNLABELED

Hazard statements (CLP)

: H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, face protection, protective clothing, protective gloves.

### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.  
P264 - Wash Both hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective clothing, protective gloves.  
P301+P310 - If swallowed: Immediately call a poison center or doctor  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a poison center or doctor if you feel unwell  
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)  
P331 - Do NOT induce vomiting.



# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to Comply with applicable regulations

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.999827	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
3,3',4,4'-TETRACB (PCB-77) (13C12, 99%)	(CAS-No.) 105600-23-5 (EC Index-No.) 602-039-00-4 (Unlabeled)	0.000015	Xn; R48/20 N; R50/53
2',3,4,4',5-PENTACB (PCB-123) (13C12, 99%)	(CAS-No.) 208263-64-3 (EC Index-No.) 602-039-00-4	0.000015	Xn; R48/20/21/22 N; R50/53 R33
2,3,3',4,4'-PENTACB (PCB-105) (13C12, 99%)	(CAS-No.) 208263-62-1 (EC Index-No.) 602-039-00-4	0.000015	Xn; R48/20/21/22 Xi; R41 N; R50/53 R33
2,3,3',4,4',5,5'-HEPTACB (PCB-189) (13C12, 99%)	(CAS-No.) 208263-73-4 (EC Index-No.) 602-039-00-4	0.000015	Xn; R48/20/21/22 N; R50/53 R33
2,3',4,4',5,5'-HEXACB (PCB-167) (13C12, 99%)	(CAS-No.) 208263-69-8 (EC Index-No.) 602-039-00-4	0.000015	Xn; R48/20/21/22 N; R50/53 R33
3,4,4',5-TETRACB (PCB-81) (13C12, 99%)	(CAS-No.) 208461-24-9 (EC Index-No.) 602-039-00-4	0.000014	Xn; R48/20/21/22 N; R50/53 R33
2,3',4,4',5-PENTACB (PCB-118) (13C12, 98%)	(CAS-No.) 104130-40-7 (EC-No.) 215-648-1 (EC Index-No.) 602-039-00-4	0.000014	Xn; R48/20/21/22 N; R50/53 R33
2,3,4,4',5-PENTACB (PCB-114) (13C12, 99%)	(CAS-No.) 208263-63-2 (EC Index-No.) 602-039-00-4	0.000014	Xn; R48/20/21/22 N; R50/53 R33
2,3,3',4,4',5-HEXACB (PCB-156) (13C12, 99%)	(CAS-No.) 208263-68-7 (EC Index-No.) 602-039-00-4	0.000014	N; R50/53 Xn; R48/21/22 R33
3,3',4,4',5-PENTACB (PCB-126) (13C12, 99%)	(CAS-No.) 208263-65-4 (EC Index-No.) 602-039-00-4	0.000014	Xn; R48/20 N; R50/53 R33
3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%)	(CAS-No.) 32774-16-6 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000014	N; R50/53 Xn; R48/20/21/22
2,3,3',4,4',5'-HEXACB (PCB-157) (13C12, 99%)	(CAS-No.) 235416-30-5 (EC Index-No.) 602-039-00-4	0.000014	Xn; R48/20/21/22 N; R50/53 R33

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.999827	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
3,3',4,4'-TETRACB (PCB-77) (13C12, 99%)	(CAS-No.) 105600-23-5 (EC Index-No.) 602-039-00-4 (Unlabeled)	0.000015	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2',3,4,4',5-PENTACB (PCB-123) (13C12, 99%)	(CAS-No.) 208263-64-3 (EC Index-No.) 602-039-00-4	0.000015	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4'-PENTACB (PCB-105) (13C12, 99%)	(CAS-No.) 208263-62-1 (EC Index-No.) 602-039-00-4	0.000015	Eye Dam. 1, H318 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5,5'-HEPTACB (PCB-189) (13C12, 99%)	(CAS-No.) 208263-73-4 (EC Index-No.) 602-039-00-4	0.000015	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4,4',5,5'-HEXACB (PCB-167) (13C12, 99%)	(CAS-No.) 208263-69-8 (EC Index-No.) 602-039-00-4	0.000015	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,4,4',5-TETRACB (PCB-81) (13C12, 99%)	(CAS-No.) 208461-24-9 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4,4',5-PENTACB (PCB-118) (13C12, 98%)	(CAS-No.) 104130-40-7 (EC-No.) 215-648-1 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4,4',5-PENTACB (PCB-114) (13C12, 99%)	(CAS-No.) 208263-63-2 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5-HEXACB (PCB-156) (13C12, 99%)	(CAS-No.) 208263-68-7 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5-PENTACB (PCB-126) (13C12, 99%)	(CAS-No.) 208263-65-4 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%)	(CAS-No.) 32774-16-6 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,4',5'-HEXACB (PCB-157) (13C12, 99%)	(CAS-No.) 235416-30-5 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS-No.) 111-84-2	99.999827	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304

Full text of R- and H- phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Alcohol resistant foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.  
Reactivity : Flammable liquid and vapor. Vapors may form flammable mixture with air.

### 5.3. Advice for firefighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Avoid all contact with skin, eyes, or clothing. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). Take precautionary measures against static discharges.  
Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed. Keep dry. Ground/bond container and receiving equipment.  
Storage conditions : Store at room temperature away from light and moisture.

### 7.3. Specific end use(s)

No additional information available

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.

#### 8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Personal protective equipment

: Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.



Materials for protective clothing

: Wear suitable protective clothing and gloves.

Hand protection

: protective gloves.

Eye protection

: Chemical goggles or face shield. Chemical goggles or safety glasses.

Skin and body protection

: Wear suitable protective clothing, gloves and eye/face protection.

Respiratory protection

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator.

Environmental exposure controls

: Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state : Liquid

Appearance : Liquid

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Molecular mass	: 128.3 g/mol
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31 °C (87.8 °F) - closed cup
Auto-ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.718 g/ml at 25 °C (77 °F)
Solubility	: Water: 0.0002 % at 25 °C (77 °F) - slightly soluble
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: <= 1.008 mm <sup>2</sup> /s at 20 °C (68 °F)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 0.87 - 2.9 % (V)

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor. Vapors may form flammable mixture with air.

### 10.2. Chemical stability

See storage and expiration date on CoA.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:vapour: Harmful if inhaled.

EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative
N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>N-NONANE UNLABELED (111-84-2)</b>	
Additional information	: S. Typhimurium Result: negative
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>3,3',4,4'-TETRACB (PCB-77) (13C12, 99%) (105600-23-5)</b>	
LC50 fish 1	> 0.002 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	> 0.002 mg/l Daphnia magna (Water flea) - 48 h
LOEC (chronic)	0.5 mg/l mortality: Pimephales promelas (fathead minnow) - 7 d
NOEC (chronic)	0.1 mg/l mortality: Oncorhynchus mykiss (rainbow trout) - 7 d

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE</b>	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
<b>3,3',4,4'-TETRACB (PCB-77) (13C12, 99%) (105600-23-5)</b>	
Log Pow	6.63
Bioaccumulative potential	Bioaccumulation: Oryzias latipes - 20 d Bioconcentration factor (BCF): 81.5.
<b>2,3',4,4',5-PENTACB (PCB-118) (13C12, 98%) (104130-40-7)</b>	
Log Pow	7.12
<b>N-NONANE UNLABELED (111-84-2)</b>	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
<b>3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%) (32774-16-6 (Unlabeled))</b>	
Log Pow	6.7

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : Disposal must be done according to official regulations. Very toxic to aquatic life with long lasting effects.

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
- Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
- Ecology - waste materials : Dispose of as unused product.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

- UN-No.(DOT) : 1920
- DOT NA no. : UN1920

#### 14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Nonanes
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
- DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 242

#### 14.3. Additional information

- Other information : No supplementary information available.

#### Overland transport

- Packing group (ADR) : III
- Class (ADR) : 3 - Flammable liquid
- Hazard identification number (Kemler No.) : 30
- Classification code (ADR) : F1
- Hazard labels (ADR) : 3 - Flammable liquids



- Orange plates : An orange rectangular plate with a black border. The number "30" is printed in black in the upper half, and the number "1920" is printed in black in the lower half.

- Tunnel restriction code (ADR) : D/E



# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Limited quantities (ADR) : 5l  
EAC : 3Y  
Excepted quantities (ADR) : E1

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
MFAG-No : 128

### Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L  
Civil Aeronautics Law : Flammable liquids

### 14.4. Environmental hazards

Other information : No supplementary information available.

### 14.5. Special precautions for user

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
N-NONANE UNLABELED (111-84-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

### 15.2. International regulations

#### CANADA

EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
Listed on the Canadian DSL (Domestic Substances List)	
N-NONANE UNLABELED (111-84-2)	
Listed on the Canadian DSL (Domestic Substances List)	

#### 15.2.1. National regulations

No additional information available

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE()	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

N-NONANE UNLABELED (111-84-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

N-NONANE UNLABELED (111-84-2)
State or local regulations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

### SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R10	Flammable
R20	Harmful by inhalation
R33	Danger of cumulative effects
R36/38	Irritating to eyes and skin
R41	Risk of serious damage to eyes

# EN-1948-4 WHO PCB EXTRACTION STANDARD (13C12, 99%) 100 NG/ML IN NONANE


EC-5372

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed
R48/21/22	Harmful: danger of serious damage to health by prolonged exposure in contact with skin and if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



### Hazard Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 3 Serious Hazard
- Physical : 0 Minimal Hazard

### CIL Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*



# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 15/08/2014

Revision date: 24/09/2019

Supersedes: 15/08/2014

Version: 2.0

EC-5371

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixtures  
Product name : EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE  
Product code : EC-5371

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-703-741-5970 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R10  
Xn; R20  
Xn; R65  
Xi; R36/38  
R67

Full text of R-phrases: see section 16

#### GHS-US classification

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of H statements : see section 16

# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Adverse physicochemical, human health and environmental effects

Central Nervous System. Flammable liquid and vapor. May cause drowsiness or dizziness. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

## 2.2. Label elements

### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: N-NONANE UNLABELED

Hazard statements (CLP)

: H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, face protection, protective clothing, protective gloves.

### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, face protection, protective clothing, protective gloves.  
P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a doctor, a POISON CENTER if you feel unwell  
P321 - Specific treatment (see Hazardous component(s) for labeling on this label)  
P331 - Do NOT induce vomiting.

# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), dry extinguishing powder to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.999958	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
2,3',4',5-TETRACB (PCB-70) (13C12, 99%)	(CAS-No.) 208263-81-4 (EC Index-No.) 602-039-00-4	0.000014	N; R50/53 R33 R48
2,3,3',5,5'-PENTACB (PCB-111) (13C12, 99%)	(CAS-No.) 235416-29-2 (EC Index-No.) 602-039-00-4	0.000014	Xn; R48/20/21/22 N; R50/53 R33
2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%)	(CAS-No.) 35065-30-6 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000014	N; R50/53 R33

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.999958	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
2,3',4',5-TETRACB (PCB-70) (13C12, 99%)	(CAS-No.) 208263-81-4 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',5,5'-PENTACB (PCB-111) (13C12, 99%)	(CAS-No.) 235416-29-2 (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%)	(CAS-No.) 35065-30-6 (Unlabeled) (EC Index-No.) 602-039-00-4	0.000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS-No.) 111-84-2	99.999958	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304

Full text of R- and H- phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Alcohol resistant foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.  
Reactivity : Flammable liquid and vapor. Vapors may form flammable mixture with air.

### 5.3. Advice for firefighters

Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Wear personal protective equipment. Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill. Dispose as hazardous waste. Comply with local regulations for disposal.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Avoid all contact with skin, eyes, or clothing. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). Take precautionary measures against static discharges.  
Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing fume, gas, mist, spray, vapors. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.



# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store in a well-ventilated place. Keep container tightly closed. Keep dry. Ground/bond container and receiving equipment.
- Storage conditions : Store at room temperature away from light and moisture.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup> USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Personal protective equipment : Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.



- Materials for protective clothing : Wear suitable protective clothing and gloves.
- Hand protection : protective gloves.
- Eye protection : Chemical goggles or face shield. Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator.



# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls : Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

*The properties listed below are for the solvent, the main component of this mixture.*

Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 128.3 g/mol
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31 °C (87.8 °F) - closed cup
Auto-ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 5.69 hPa (4.27 mmHg) at 25 °C (77 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.718 g/ml at 25 °C (77 °F)
Solubility	: Water: 0.0002 % at 25 °C (77 °F) - slightly soluble
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: <= 1.008 mm <sup>2</sup> /s at 20 °C (68 °F)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 0.87 - 2.9 % (V)

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapor. Vapors may form flammable mixture with air.

#### 10.2. Chemical stability

See storage and expiration date on CoA.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:vapour: Harmful if inhaled.

#### EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
----------------------------	------------------------------------

# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m <sup>3</sup> male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

#### 2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%) (35065-30-6 (Unlabeled))

LC50 fish 1	0.034 mg/l Pimephales promelas (fathead minnow) - 96 h
-------------	--

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

#### EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

#### 2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%) (35065-30-6 (Unlabeled))

Log Pow	8.27
---------	------

#### N-NONANE UNLABELED (111-84-2)

Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : Disposal must be done according to official regulations. Very toxic to aquatic life with long lasting effects.

# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
- Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
- Ecology - waste materials : Dispose of as unused product.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

- UN-No.(DOT) : 1920
- DOT NA no. UN1920

#### 14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Nonanes
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : III - Minor Danger
- DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 242

#### 14.3. Additional information

- Other information : No supplementary information available.

#### Overland transport

- Packing group (ADR) : III
- Class (ADR) : 3 - Flammable liquid
- Hazard identification number (Kemler No.) : 30
- Classification code (ADR) : F1
- Hazard labels (ADR) : 3 - Flammable liquids



- Orange plates : 

- Tunnel restriction code (ADR) : D/E

# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Limited quantities (ADR)	: 5l
EAC	: 3Y
Excepted quantities (ADR)	: E1

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

MFAG-No : 128

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

Civil Aeronautics Law : Flammable liquids

### 14.4. Environmental hazards

Other information : No supplementary information available.

### 14.5. Special precautions for user

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313
N-NONANE UNLABELED (111-84-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

### 15.2. International regulations

#### CANADA

EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE	
Listed on the Canadian DSL (Domestic Substances List)	
N-NONANE UNLABELED (111-84-2)	
Listed on the Canadian DSL (Domestic Substances List)	

#### 15.2.1. National regulations

No additional information available

### 15.3. US State regulations

EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE()	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive	No

# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE()	
Toxicity - Female	
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

N-NONANE UNLABELED (111-84-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

N-NONANE UNLABELED (111-84-2)
State or local regulations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

## SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R10	Flammable
R20	Harmful by inhalation
R33	Danger of cumulative effects
R36/38	Irritating to eyes and skin
R48	Danger of serious damage to health by prolonged exposure
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful


# EN-1948-4 PCB RECOVERY STANDARD (13C12, 99%) 100 NG/ML IN NONANE

EC-5371

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



### Hazard Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

### CIL Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*