



TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 12/21/2010 Revision date: 12/22/2022 Supersedes: 12/12/2016 Version: 3.2

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : TOLUENE-D8 "100%" (D, 99.94%)
Chemical name : Toluene
CAS-No. : 108-88-3
Product code : DLM-42
Formula : C7H8

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Cambridge Isotope Laboratories, Inc.
50 Frontage Rd
01810
ANDOVER, MA, 01810
USA
T 1-800-322-1174
cilsales@isotope.com - www.isotope.com

1.4. Emergency telephone number

Emergency number : 1-703-741-5970
Chemtrec 1-800-424-9300 24 hours

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Reproductive toxicity Category 2	H361	(Dermal, Inhalation, oral)
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs (kidneys, liver, urinary bladder, brain) through prolonged or repeated exposure (Dermal, Inhalation, oral)
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Hazardous to the aquatic environment – Acute Hazard Category 2	H401	Toxic to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	: H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H361 - (Dermal, Inhalation, oral) H373 - May cause damage to organs (kidneys, liver, urinary bladder, brain) through prolonged or repeated exposure (Dermal, Inhalation, oral) H401 - Toxic to aquatic life P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe fume, mist, spray, vapors. P261 - Avoid breathing dust, fume, gas, mist, spray, vapors. P264 - Wash Both hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear eye protection, face protection, protective clothing, protective gloves. P301+P310 - If swallowed: Immediately call a poison center or doctor. P302+P352 - If on skin: Wash with plenty of water. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P308+P313 - If exposed or concerned: Get medical advice/attention. P312 - Call a poison center or doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see Hazard pictograms (CLP) on this label). P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse. P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to Comply with applicable regulations.
-----------------------------------	---

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%	GHS US classification
TOLUENE-D8 "100%" (D, 99.94%) (Main constituent)	CAS-No.: 108-88-3	100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
First-aid measures after inhalation	: If breathed in, move person to fresh air. If not breathing, give artificial respiration. Consult a physician.
First-aid measures after skin contact	: Wash off with soap and plenty of water. Consult a physician.
First-aid measures after eye contact	: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Lung irritation, chest pain, pulmonay edema, Inhalation studies have shown the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotom in animals. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: May be harmful if absorbed through the skin. Causes skin irritation.
Symptoms/effects after eye contact	: Contact may cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

5.2. Specific hazards arising from the chemical

No additional information available

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray to cool unopened containers.
Protection during firefighting : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Flammable in presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Use personal protective equipment, and ensure adequate ventilation. Avoid breathing vapors, mist, gas. Remove ignition sources, and move personnel to safe area. Vapors accumulate especially in low areas to form explosive concentrations.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

- For containment : Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent build up of electrostatic charge.
Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed in a cool, dry and well-ventilated place.
Storage conditions : Store at room temperature away from light and moisture.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)

USA - ACGIH - Occupational Exposure Limits

Local name	Toluene
ACGIH OEL TWA [ppm]	20 ppm Visual impairment, Female reproductive, Pregnancy loss

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)	
Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2022
USA - ACGIH - Biological Exposure Indices	
Local name	TOLUENE
BEI	0.3 mg/g Kreatinin Parameter: o-Cresol (with hydrolysis) - Medium: urine - Sampling time: End of shift - Notations: B 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [2]	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
OSHA PEL STEL [2]	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.

Hand protection:

Wear suitable protective clothing and gloves

Eye protection:

Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection:

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection:

Wear appropriate NIOSH/MSHA approved respirator.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colorless
Odor	: No data available
Odor threshold	: 2.14 ppm Source: HSDB

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH	: No data available
Melting point	: -94.9 °C Source: HSDB
Freezing point	: No data available
Boiling point	: 110.6 °C Source: HSDB
Flash point	: 4 °C Source: HSDB
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 28.4 mm Hg at 25°C Source: HSDB
Relative vapor density at 20°C	: 3.1 Source: HSDB
Relative density	: 0.8623 Source: HSDB
Density	: 0.865 g/ml at 25 °C (77 °F)
Molecular mass	: 92.14 g/mol Source: HSDB
Solubility	: Water: 0.526 g/100ml
Partition coefficient n-octanol/water (Log Pow)	: 2.73 Source: HSDB
Auto-ignition temperature	: 480 °C Source: HSDB
Decomposition temperature	: No data available
Viscosity, kinematic	: 0.647 mm ² /s
Viscosity, dynamic	: 0.56 cP Source: HSDB
Explosion limits	: 1.2 – 7 % (V) Upper explosion limit: 1 – 7.8 % Source: GESTIS
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Avoid Heat, Flames and Sparks. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Formed under fire conditions. - Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)	
LD50 oral rat	5580 mg/kg Source: ECHA
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LC50 Inhalation - Rat	12500 – 28800 mg/m ³ 4 h
ATE US (dermal)	12196 mg/kg body weight
ATE US (vapors)	12.5 mg/l/4h
ATE US (dust, mist)	12.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: (Dermal, Inhalation, oral).
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (kidneys, liver, urinary bladder, brain) through prolonged or repeated exposure (Dermal, Inhalation, oral).
Aspiration hazard	: May be fatal if swallowed and enters airways.
Viscosity, kinematic	: 0.647 mm ² /s
Potential Adverse human health effects and symptoms	: Lung irritation, chest pain, pulmonay edema, Inhalation studies have shown the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotom in animals. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Symptoms/effects after inhalation	: May be harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Symptoms/effects after skin contact	: May be harmful if absorbed through the skin. Causes skin irritation.
Symptoms/effects after eye contact	: Contact may cause eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

SECTION 12: Ecological information

12.1. Toxicity

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Source: ECHA
LC50 - Other aquatic organisms [1]	10 mg/l <i>Pseudokirchneriella subcapitata</i> (Green algae) - 24 h
EC50 - Crustacea [1]	3.78 mg/l Source: ECHA
LC50 - Fish [2]	7.63 mg/l <i>Oncorhynchus mykiss</i> (Rainbow trout) - 96 h
EC50 - Crustacea [2]	6 mg/l <i>Daphnia magna</i> (Water flea) - Immobilization - 48 h
ErC50 algae	245 mg/l <i>Chlorella vulgaris</i> (Fresh water algae) - 24 h
LOEC (chronic)	8.04 mg/l <i>Pimephales promelas</i> (Fathead minnow) - 7 d
NOEC (chronic)	5.44 mg/l <i>Pimephales promelas</i> (fathead minnow) - 7 d
NOEC chronic crustacea	0.74 mg/l

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)

Partition coefficient n-octanol/water (Log Pow)	2.73 Source: HSDB
---	-------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.

Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No : UN1294
UN-No. (TDG) : UN1294
UN-No. (IMDG) : 1294
UN-No. (IATA) : 1294

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Toluene
Proper Shipping Name (TDG) : TOLUENE
Proper Shipping Name (IMDG) : TOLUENE
Proper Shipping Name (IATA) : Toluene

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : 3

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (TDG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3

Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : II

Packing group (IMDG) : II

Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1294

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG

UN-No. (TDG) : UN1294
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L
Emergency Response Guide (ERG) Number : 130

IMDG

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B
Flash point (IMDG) : 7°C c.c.
Properties and observations (IMDG) : Colourless liquid with a benzene-like odour. Flashpoint: 7°C c.c. Explosive limits: 1.27% to 7% Immiscible with water.
MFAG-No : 130

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)

SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
TOLUENE-D8 "100%" (D, 99.94%)	108-88-3	Present	Active	

TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

TOLUENE-D8 "100%" (D, 99.94%) (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
No significant risk level (NSRL)	7000 µg/day
Maximum allowable dose level (MADL)	7000 µg/day
State or local regulations	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 12/22/2022

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of H-phrases

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.


TOLUENE-D8 "100%" (D, 99.94%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.