



DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 20/10/2015

Revision date: 27/08/2018

Supersedes: 20/10/2015

Version: 1.1

EDF-5525

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name : DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE
Product code : EDF-5525

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000

cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)

International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapour)	H331
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 1	H370

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11

T; R39/23/24/25

Xi; R36/38

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2	H225
Acute Tox. 3 (Oral)	H301
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapour)	H331
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 1	H370

Full text of H statements : see section 16

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Eyes, Kidney, Liver, Heart, Central nervous system. Highly flammable liquid and vapour. Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (if inhaled, if swallowed, in contact with skin). Toxic in contact with skin. Toxic if inhaled. Toxic if swallowed. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: N-NONANE UNLABELED; TOLUENE UNLABELED; 1,2,3,7,8-PENTACHLORODIBENZO-P-DIOXIN (13C12, 99%); 1,2,3,4,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%); 1,2,3,7,8,9-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%); 2,3,7,8-TCDD UNLABELED; 1,2,3,4,6,7,8-HEPTACHLORODIBENZO-P-DIOXIN (13C12, 99%); OCTACHLORODIBENZO-P-DIOXIN (13C12, 99%); 1,2,3,6,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%)

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour
H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H370 - Causes damage to organs (eyes, heart, kidneys, liver, central nervous system) (in contact with skin, if inhaled, if swallowed)

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P260 - Do not breathe dust, mist, vapors, fume, gas, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapour
H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H370 - Causes damage to organs (eyes, kidneys, liver, heart, central nervous system) (Dermal, Inhalation, oral)

Precautionary statements (GHS-US)

: P210 - Keep away from heat, open flames, sparks. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe dust, fume, mist, gas, spray, vapors.
P261 - Avoid breathing dust, fume, gas, spray, vapors, mist.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective clothing, protective gloves.
P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P307+P311 - If exposed: Call a poison center/doctor
P311 - Call a doctor, a POISON CENTER
P312 - Call a doctor, a POISON CENTER if you feel unwell
P321 - Specific treatment (see Hazardous component(s) for labeling on this label)
P322 - Specific treatment (see Hazard pictograms (CLP) on this label)
P330 - Rinse mouth.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO₂), dry extinguishing powder to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

PBT: not relevant – no registration required

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.545934596 8747	F; R11 T; R39/23/24/25 Xi; R36/38
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	0.453874	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
TOLUENE UNLABELED	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	0.000189	F; R11 Xi; R38 Xn; R65 Repr.Cat.3; R62 Repr.Cat.3; R63 R67 N; R51/53 Xn; R48/20
OCTACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 3268-87-9 (Unlabeled)	0.00000063	Xn; R22 Xn; R65 R53
1,2,3,4,6,7,8-HEPTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 67562-39-4 (Unlabeled)	0.00000019	Xn; R22 Xi; R36 R53
3,3',4,4'-TETRACB (PCB-77) (13C12, 99%)	(CAS-No.) 105600-23-5 (EC Index-No.) 602-039-00-4 (Unlabeled)	0.00000019	Xn; R48/20 N; R50/53
3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%)	(CAS-No.) 32774-16-6 (Unlabeled) (EC Index-No.) 602-039-00-4	0.00000019	N; R50/53 Xn; R48/20/21/22
3,4,4',5-TETRACB (PCB-81) (13C12, 99%)	(CAS-No.) 208461-24-9 (EC Index-No.) 602-039-00-4	0.00000019	Xn; R48/20/21/22 N; R50/53 R33
3,3',4,4',5-PENTACB (PCB-126) (13C12, 99%)	(CAS-No.) 208263-65-4 (EC Index-No.) 602-039-00-4	0.00000019	Xn; R48/20 N; R50/53 R33

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Directive 67/548/EEC
1,2,3,4,6,7,8-HEPTACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 35822-46-9 (Unlabeled)	0.00000019	Xn; R22 Xn; R65 R53
1,2,3,6,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 57652-85-7 (Unlabeled)	0.00000019	Xn; R22 Xn; R65 R53
2,3,4,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 60851-34-5 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
1,2,3,4,7,8,9-HEPTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 55673-89-7 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
1,2,3,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 57117-46-6 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
OCTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 39001-02-0 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
2,3,4,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 57117-31-4 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
1,2,3,4,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 70648-26-9 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
1,2,3,7,8,9-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 72918-21-9 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
1,2,3,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 57117-44-9 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
2,3,7,8-TETRACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 51207-31-9 (Unlabeled)	0.00000006	Xn; R22 Xi; R36 R53
1,2,3,7,8-PENTACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 40321-76-4 (Unlabeled)	0.00000006	Xn; R22 Xn; R65 R53
1,2,3,4,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 39227-28-6 (Unlabeled)	0.00000006	Xn; R22 Xn; R65 R53
1,2,3,7,8,9-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 19408-74-3 (Unlabeled)	0.00000006	Xn; R22 Xn; R65 R53
2,3,7,8-TCDD UNLABELED	(CAS-No.) 1746-01-6	0.00000006	N; R50/53 R67 Repr.Cat.3; R62 Repr.Cat.3; R63 Xi; R38 Xn; R65 Xn; R48/20
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% METHANOL UNLABELED	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X (REACH-no) 01-2119433307-44	99.545934596 8747	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	0.453874	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
TOLUENE UNLABELED	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	0.000189	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
OCTACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 3268-87-9 (Unlabeled)	0.00000063	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
1,2,3,4,6,7,8-HEPTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 67562-39-4 (Unlabeled)	0.00000019	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
3,3',4,4'-TETRACB (PCB-77) (13C12, 99%)	(CAS-No.) 105600-23-5 (EC Index-No.) 602-039-00-4 (Unlabeled)	0.00000019	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%)	(CAS-No.) 32774-16-6 (Unlabeled) (EC Index-No.) 602-039-00-4	0.00000019	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,4,4',5-TETRACB (PCB-81) (13C12, 99%)	(CAS-No.) 208461-24-9 (EC Index-No.) 602-039-00-4	0.00000019	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,4',5-PENTACB (PCB-126) (13C12, 99%)	(CAS-No.) 208263-65-4 (EC Index-No.) 602-039-00-4	0.00000019	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2,3,4,6,7,8-HEPTACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 35822-46-9 (Unlabeled)	0.00000019	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
1,2,3,6,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 57652-85-7 (Unlabeled)	0.00000019	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
2,3,4,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 60851-34-5 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
1,2,3,4,7,8,9-HEPTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 55673-89-7 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
1,2,3,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 57117-46-6 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
OCTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 39001-02-0 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
2,3,4,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 57117-31-4 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
1,2,3,4,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 70648-26-9 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
1,2,3,7,8,9-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 72918-21-9 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
1,2,3,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 57117-44-9 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
2,3,7,8-TETRACHLORODIBENZOFURAN (13C12, 99%)	(CAS-No.) 51207-31-9 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413
1,2,3,7,8-PENTACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 40321-76-4 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
1,2,3,4,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 39227-28-6 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Aquatic Chronic 4, H413
1,2,3,7,8,9-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%)	(CAS-No.) 19408-74-3 (Unlabeled)	0.00000006	Acute Tox. 4 (Oral), H302 Asp. Tox. 1, H304 Aquatic Chronic 4, H413

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,3,7,8-TCDD UNLABELED	(CAS-No.) 1746-01-6	0.00000006	Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
100% METHANOL UNLABELED	(CAS-No.) 67-56-1	99.545934596 8747	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 1, H370

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry powder. Dry sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Reactivity	: Flammable liquid and vapour. Vapors may form flammable mixture with air.

5.3. Advice for firefighters

Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.
Other information	: Use water spray to cool exposed surfaces.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Wear respiratory protection. Do not breathe dust, mist, gas, spray, vapors, fume. Avoid contact with skin, eyes and clothing. Ventilate spillage area. Remove all sources of ignition. No open flames, no sparks, and no smoking. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.
----------------------	---

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions : Store at room temperature away from light and moisture.
Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE		
USA OSHA	OSHA PEL (STEL) (mg/m ³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m ³ is approximate. Skin notation.
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1050 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1050 mg/m ³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.
TOLUENE UNLABELED (108-88-3)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Visual impairment. Female reproductive. Pregnancy loss. 2015 Adoption. Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen.; Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0300 mg/l Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0200 mg/l Biological specimen: In blood Remarks: Prior to last shift of workweek Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS-No.: 108-88-3 Parameters: o-Cresol Value: 0.3000 mg/g Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	375 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm USA. NIOSH Recommended Exposure Limits
USA OSHA	OSHA PEL (TWA) (mg/m ³)	375 mg/m ³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)		
USA OSHA	OSHA PEL (STEL) (mg/m ³)	560 mg/m ³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-2
USA OSHA	Remark (OSHA)	OSHA PEL (TWA) - 200 ppm - USA. Occupational Exposure Limits (OSHA) - Table Z-2. Remarks: Z37.12-1967

100% METHANOL UNLABELED (67-56-1)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Headache. Nausea. Dizziness. Eye damage. Substances for which there is a Biological Exposure Index or Indices (see BEI section). Danger of cutaneous absorption.
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³ Basis: NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm Basis: NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Potential for dermal absorption.
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³ Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (mg/m ³)	325 mg/m ³ Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (STEL) (ppm)	250 ppm Basis: USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000. California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	1000 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m ³ is approximate. Skin notation.

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	40 mg/kg bodyweight/day
Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, dermal	260 mg/cm ²
Long-term - systemic effects, dermal	40 mg/kg bodyweight/day
Long-term - local effects, dermal	260 mg/cm ²
Long-term - local effects, inhalation	260 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	8 mg/kg body weight
Acute - systemic effects, inhalation	50 mg/m ³
Acute - systemic effects, oral	8 mg/kg body weight

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
Acute - local effects, inhalation	50 mg/m ³
Long-term - systemic effects, oral	8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	50 mg/m ³
Long-term - systemic effects, dermal	8 mg/kg bodyweight/day
Long-term - local effects, inhalation	50 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	154 mg/l
PNEC aqua (marine water)	15.4 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	570.4 mg/kg dwt
PNEC (Soil)	
PNEC soil	23.5 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/kg

8.2. Exposure controls

Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing : Wear suitable protective clothing and gloves.

Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses.

Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.

Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 32.04 g/mol
Color	: Colorless
Odor	: Pungent
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -98 °C (-144 °F)
Freezing point	: No data available
Boiling point	: 64.7 °C (148.5 °F)
Flash point	: 9.7 °C (49.5 °F) - closed cup
Auto-ignition temperature	: 455 °C (851 °F) at 1,013 hPa (760 mmHg)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 130.3 hPa (97.7 mmHg) at 20 °C (68 °F); 169.27 hPa (126.96 mmHg) at 25 °C (77 °F)
Vapor pressure at 50 °C	: 546.6 hPa (410 mmHg) at 50 °C (122 °F)
Relative vapor density at 20 °C	: 1.11
Relative density	: No data available
Specific gravity / density	: 0.791 g/ml at 25 °C (77 °F)
Solubility	: Water: Completely miscible
Log Pow	: -0.77
Log Kow	: No data available

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidizing properties	: Non oxidizing material according to EC criteria.
Explosion limits	: 6 - 36 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour. Vapors may form flammable mixture with air.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Acid anhydrides. Acid chlorides. Oxidizing agent. Alkali Metal Amides. Reducing agents. Acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	23.760 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative
2,3,4,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (60851-34-5 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,4,7,8,9-HEPTACHLORODIBENZOFURAN (13C12, 99%) (55673-89-7 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-46-6 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
OCTACHLORODIBENZOFURAN (13C12, 99%) (39001-02-0 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,4,6,7,8-HEPTACHLORODIBENZOFURAN (13C12, 99%) (67562-39-4 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
TOLUENE UNLABELED (108-88-3)	
LD50 oral rat	> 5580 mg/kg
LD50 dermal rabbit	12196 mg/kg

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TOLUENE UNLABELED (108-88-3)	
LC50 inhalation rat (mg/l)	12,500 - 28,800 mg/m ³ - 4 h
ATE CLP (dermal)	12196.000 mg/kg body weight
ATE CLP (vapors)	12.500 mg/l/4h
ATE CLP (dust, mist)	12.500 mg/l/4h
2,3,4,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-31-4 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,4,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (70648-26-9 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,7,8,9-HEXACHLORODIBENZOFURAN (13C12, 99%) (72918-21-9 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (57117-44-9 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
2,3,7,8-TETRACHLORODIBENZOFURAN (13C12, 99%) (51207-31-9 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,7,8-PENTACHLORODIBENZO-P-DIOXIN (13C12, 99%) (40321-76-4 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,4,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%) (39227-28-6 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,7,8,9-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%) (19408-74-3 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
2,3,7,8-TCDD UNLABELED (1746-01-6)	
LD50 oral rat	0.02 mg/kg
LD50 dermal rabbit	275 µg/kg
1,2,3,4,6,7,8-HEPTACHLORODIBENZO-P-DIOXIN (13C12, 99%) (35822-46-9 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
OCTACHLORODIBENZO-P-DIOXIN (13C12, 99%) (3268-87-9 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
1,2,3,6,7,8-HEXACHLORODIBENZO-P-DIOXIN (13C12, 99%) (57652-85-7 (Unlabeled))	
ATE CLP (oral)	500.000 mg/kg body weight
100% METHANOL UNLABELED (67-56-1)	
LD50 oral rat	1187 - 2769 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	128.2 mg/l/4h ; 87.6 mg/l - 6 h
ATE CLP (oral)	100.000 mg/kg body weight
ATE CLP (dermal)	300.000 mg/kg body weight
ATE CLP (vapors)	3.000 mg/l/4h
ATE CLP (dust, mist)	128.200 mg/l/4h
LDLO, oral, human	143 mg/kg Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin corrosion/irritation	: Skin. Rabbit. Result: No skin irritation
Serious eye damage/irritation	: Eyes. Rabbit. Result: No eye irritation
Respiratory or skin sensitization	: Maximisation Test . Guinea pig. Did not cause sensitization. (OECD 406 method)
Germ cell mutagenicity	: AMES test : S. typhimurium. Result: negative. fibroblast. Result: Negative. Mutation in mammalian somatic cells. Mutagenicity (in vivo mammalian bone-marrow cystogenetic test, chromosomal analysis) - Mouse - male and female Result: negative. Mouse - male and female. Result: Negative
Carcinogenicity	: Not classified
Reproductive toxicity	: Damage to fetus not classifiable. Fertility classification not possible from current data.
Specific target organ toxicity – single exposure	: Causes damage to organs through prolonged or repeated exposure Causes damage to organs
Specific target organ toxicity – repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure. No data available

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-NONANE UNLABELED (111-84-2)	
NOAEL (oral,rat,90 days)	100 mg/kg bodyweight/day female (OECD Test Guideline 408)
Aspiration hazard	: No aspiration toxicity classification.
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Effects due to Ingestion may include: Headache. Dizziness. Drowsiness. metabolic acidosis. Coma. May be fatal if swallowed and enters airways. If swallowed there is a risk of blindness. Effects on humans. stomach.
Symptoms/effects after inhalation	: Toxic if inhaled.
Symptoms/effects after skin contact	: Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis macrochirus (Bluegill) - 96 h
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h

N-NONANE UNLABELED (111-84-2)	
EC50 Daphnia 1	0.2 mg/l static test EC50 - Daphnia magna (Water flea) - 48 h

TOLUENE UNLABELED (108-88-3)	
EC50 Daphnia 1	8 mg/l Daphnia magna (Water flea) - 24h
LC50 fish 2	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h
EC50 Daphnia 2	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h
ErC50 (algae)	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h
ErC50 (other aquatic plants)	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d

3,3',4,4'-TETRACB (PCB-77) (13C12, 99%) (105600-23-5)	
LC50 fish 1	> 0.002 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	> 0.002 mg/l Daphnia magna (Water flea) - 48 h
LOEC (chronic)	0.5 mg/l mortality: Pimephales promelas (fathead minnow) - 7 d
NOEC (chronic)	0.1 mg/l mortality: Oncorhynchus mykiss (rainbow trout) - 7 d

2,3,7,8-TCDD UNLABELED (1746-01-6)	
LC50 fish 1	0.001 µg/l Oryzias latipes - 72 h

100% METHANOL UNLABELED (67-56-1)	
LC50 fish 1	15400 mg/l mortality LC50 - Lepomis macrochirus (Bluegill) - 96 h
EC50 Daphnia 1	> 10000 mg/l Daphnia magna (Water flea) - 48 h
EC50 Daphnia 2	22000 mg/l Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) - 96 h
NOEC (acute)	7900 mg/l Oryzias latipes - 200 h

12.2. Persistence and degradability

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d

2,3,4,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (60851-34-5 (Unlabeled))	
Persistence and degradability	Not available.

1,2,3,4,7,8,9-HEPTACHLORODIBENZOFURAN (13C12, 99%) (55673-89-7 (Unlabeled))	
Persistence and degradability	Not available.

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,3,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-46-6 (Unlabeled))	
Persistence and degradability	Not available.
OCTACHLORODIBENZOFURAN (13C12, 99%) (39001-02-0 (Unlabeled))	
Persistence and degradability	Not available.
1,2,3,4,6,7,8-HEPTACHLORODIBENZOFURAN (13C12, 99%) (67562-39-4 (Unlabeled))	
Persistence and degradability	Not available.
TOLUENE UNLABELED (108-88-3)	
Persistence and degradability	Readily biodegradable.
2,3,4,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-31-4 (Unlabeled))	
Persistence and degradability	Not available.
1,2,3,4,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (70648-26-9 (Unlabeled))	
Persistence and degradability	Not available.
1,2,3,7,8,9-HEXACHLORODIBENZOFURAN (13C12, 99%) (72918-21-9 (Unlabeled))	
Persistence and degradability	Not available.
1,2,3,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (57117-44-9 (Unlabeled))	
Persistence and degradability	Not available.
2,3,7,8-TETRACHLORODIBENZOFURAN (13C12, 99%) (51207-31-9 (Unlabeled))	
Persistence and degradability	Not available.
2,3,7,8-TCDD UNLABELED (1746-01-6)	
Persistence and degradability	May cause long-term adverse effects in the environment.
100% METHANOL UNLABELED (67-56-1)	
Biochemical oxygen demand (BOD)	600 - 1200 mg/g
Chemical oxygen demand (COD)	1420 mg/g
ThOD	1500 mg/g
Biodegradation	72 % - rapidly biodegradable aerobic - Exposure time 5 d
12.3. Bioaccumulative potential	
DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77
N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.
2,3,4,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (60851-34-5 (Unlabeled))	
Bioaccumulative potential	Not available.
1,2,3,4,7,8,9-HEPTACHLORODIBENZOFURAN (13C12, 99%) (55673-89-7 (Unlabeled))	
Bioaccumulative potential	Not available.
1,2,3,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-46-6 (Unlabeled))	
Bioaccumulative potential	Not available.
OCTACHLORODIBENZOFURAN (13C12, 99%) (39001-02-0 (Unlabeled))	
Bioaccumulative potential	Not available.
1,2,3,4,6,7,8-HEPTACHLORODIBENZOFURAN (13C12, 99%) (67562-39-4 (Unlabeled))	
Bioaccumulative potential	Not available.
TOLUENE UNLABELED (108-88-3)	
BCF fish 1	0.05 mg/l Leuciscus idus (Golden orfe) - 3 d
Bioconcentration factor (BCF REACH)	90
3,3',4,4'-TETRACB (PCB-77) (13C12, 99%) (105600-23-5)	
Log Pow	6.63
Bioaccumulative potential	Bioaccumulation: Oryzias latipes - 20 d Bioconcentration factor (BCF): 81.5.
3,3',4,4',5,5'-HEXACB (PCB-169) (13C12, 99%) (32774-16-6 (Unlabeled))	
Log Pow	6.7
2,3,4,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-31-4 (Unlabeled))	
Bioaccumulative potential	Not available.

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,3,4,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (70648-26-9 (Unlabeled))	
Bioaccumulative potential	Not available.
1,2,3,7,8,9-HEXACHLORODIBENZOFURAN (13C12, 99%) (72918-21-9 (Unlabeled))	
Bioaccumulative potential	Not available.
1,2,3,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (57117-44-9 (Unlabeled))	
Bioaccumulative potential	Not available.
2,3,7,8-TETRACHLORODIBENZOFURAN (13C12, 99%) (51207-31-9 (Unlabeled))	
Bioaccumulative potential	Not available.
2,3,7,8-TCDD UNLABELED (1746-01-6)	
Log Pow	6.64
100% METHANOL UNLABELED (67-56-1)	
BCF fish 1	5 mg/l Cyprinus carpio (Carp) - 72 d at 20 °C
Bioconcentration factor (BCF REACH)	1
Log Pow	-0.77

12.4. Mobility in soil

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
Ecology - soil	Not degradable in the soil.
2,3,4,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (60851-34-5 (Unlabeled))	
Ecology - soil	Not available.
1,2,3,4,7,8,9-HEPTACHLORODIBENZOFURAN (13C12, 99%) (55673-89-7 (Unlabeled))	
Ecology - soil	Not available.
1,2,3,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-46-6 (Unlabeled))	
Ecology - soil	Not available.
OCTACHLORODIBENZOFURAN (13C12, 99%) (39001-02-0 (Unlabeled))	
Ecology - soil	Not available.
1,2,3,4,6,7,8-HEPTACHLORODIBENZOFURAN (13C12, 99%) (67562-39-4 (Unlabeled))	
Ecology - soil	Not available.
2,3,4,7,8-PENTACHLORODIBENZOFURAN (13C12, 99%) (57117-31-4 (Unlabeled))	
Ecology - soil	Not available.
1,2,3,4,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (70648-26-9 (Unlabeled))	
Ecology - soil	Not available.
1,2,3,7,8,9-HEXACHLORODIBENZOFURAN (13C12, 99%) (72918-21-9 (Unlabeled))	
Ecology - soil	Not available.
1,2,3,6,7,8-HEXACHLORODIBENZOFURAN (13C12, 99%) (57117-44-9 (Unlabeled))	
Ecology - soil	Not available.
2,3,7,8-TETRACHLORODIBENZOFURAN (13C12, 99%) (51207-31-9 (Unlabeled))	
Ecology - soil	Not available.
100% METHANOL UNLABELED (67-56-1)	
Ecology - soil	Not degradable in the soil.

12.5. Results of PBT and vPvB assessment

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
PBT: not relevant – no registration required	
TOLUENE UNLABELED (108-88-3)	
PBT: not relevant – no registration required	
100% METHANOL UNLABELED (67-56-1)	
PBT: not relevant – no registration required	

12.6. Other adverse effects

Other adverse effects	: Avoid release to the environment.
Other information	: Stability in water: at 19 °C - (83 - 91%) - 72 h. Remarks: Hydrolyses on contact with water. Hydrolyses readily.

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
- Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
- Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

- UN-No.(DOT) : 1230
- DOT NA no. UN1230

14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Methanol
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid
6.1 - Poison



- DOT Symbols : + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group, I - Proper shipping name appropriate for international and domestic transportation
- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

- Emergency Response Guide (ERG) Number : 131
- Other information : No supplementary information available.

Overland transport

- Hazard identification number (Kemler No.) : 336
- Orange plates :



- Tunnel restriction code (ADR) : D/E
- Limited quantities (ADR) : 1I
- Excepted quantities (ADR) : E2

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 131

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

Civil Aeronautics Law : Flammable liquids

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	5000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313

100% METHANOL UNLABELED (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	5000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313

15.2. International regulations

CANADA

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
Listed on the Canadian DSL (Domestic Substances List)	
100% METHANOL UNLABELED (67-56-1)	
Listed on the Canadian DSL (Domestic Substances List)	

15.2.1. National regulations

No additional information available

15.3. US State regulations

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE

EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE	
State or local regulations	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

100% METHANOL UNLABELED (67-56-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

100% METHANOL UNLABELED (67-56-1)	
State or local regulations	
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances	

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure

DIOXIN/FURAN/CP-PCB INTERNAL STANDARD IN METHANOL/NONANE


EDF-5525

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life
R10	Flammable
R11	Highly flammable
R20	Harmful by inhalation
R22	Harmful if swallowed
R33	Danger of cumulative effects
R36	Irritating to eyes
R36/38	Irritating to eyes and skin
R38	Irritating to skin
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R53	May cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
T	Toxic
Xi	Irritant
Xn	Harmful

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 3 Serious Hazard
- Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product