

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 20/04/2017 Revision date: : Version: 1.0

CLM-10348

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance

Substance name : ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%)

EC No : 207-975-3 (Unlabeled)
CAS No : 503-74-2 (Unlabeled)

Product code : CLM-10348

Formula : (*CH3)2*CH*CH2COOH

Synonyms : 3-Methylbutanoic acid / 3-Methylbutyric acid

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.

50 Frontage Road Andover, MA 01810

USA

USA: 1-800-322-1174 Int: 1-978-749-8000 <u>cilsales@isotope.com</u> www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours) International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Corr. 1A H314

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

C; R35

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 4 H227 Skin Corr. 1C H314

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

20/04/2017 EN (English) 1/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Danger

Hazard statements (CLP) : H314 - Causes severe skin burns and eye damage

Precautionary statements (CLP) P260 - Do not breathe gas, dust, fume, mist, spray, vapours

P264 - Wash Both hands thoroughly after handling

P280 - Wear protective clothing, protective gloves
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor

GHS-US labelling

Hazard pictograms (GHS-US)



GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P210 - Keep away from heat, open flames, hot surfaces, sparks. - No smoking

P260 - Do not breathe dust, fume, gas, mist, vapours, spray

P264 - Wash Both hands thoroughly after handling

P280 - Wear protective clothing, protective gloves

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor

P321 - Specific treatment (see Hazard pictograms (CLP) on this label)

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use Dry powder, Dry chemical, Alcohol resistant foam to

extinguish

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to Comply with applicable regulations

Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Substances

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%)	(CAS No) 503-74-2 (Unlabeled) (EC No) 207-975-3 (Unlabeled)	100	C; R35
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%)	(CAS No) 503-74-2 (Unlabeled) (EC No) 207-975-3 (Unlabeled)	100	Skin Corr. 1A, H314

Full text of R- and H-statements; see section 16

20/04/2017 EN (English) 2/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%) (Main constituent)	(CAS No) 503-74-2 (Unlabeled)	100	Flam. Liq. 4, H227 Skin Corr. 1C, H314

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

First-aid measures after inhalation : If breathed in, move person to fresh air. If not breathing, give artificial respiration. Consult a

physician.

First-aid measures after skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.

Consult a physician.

First-aid measures after eye contact : Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue

rinsing eyes during transport to hospital.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse

mouth with water. Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous

membranes and upper respiratory tract.

Symptoms/injuries after skin contact : May be harmful if absorbed through the skin. Causes skin burns.

Symptoms/injuries after eye contact : Causes eye burns.

Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide.

For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as mist or spray; solid streams of water may be ineffective. Cool all affected containers

with flooding quantities of water.

5.2. Special hazards arising from the substance or mixture

Reactivity : Not available.

5.3. Advice for firefighters

Firefighting instructions : Wear self contained breathing apparatus for fire fighting if necessary.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For containment : Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-

brushing and place in container for disposal according to local regulations.

6.4. Reference to other sections

No additional information available

20/04/2017 EN (English) 3/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed in a cool, dry and well-ventilated place.

: Store at room temperature away from light and moisture. Storage conditions

Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

Control parameters

No additional information available

Exposure controls

Appropriate engineering controls

: Handle in accordance with good industrial hygiene and safety practice. Wash hands before

breaks and at the end of workday.

Personal protective equipment Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.









Materials for protective clothing : Wear suitable protective clothing and gloves. Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.

Choose body protection according to the amount and concentration of the dangerous Skin and body protection

substance at the work place.

: When appropriate, use NIOSH/CEN approved respirator. Respiratory protection

Environmental exposure controls : Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Liquid **Appearance** : Liquid.

Molecular mass : 106.1 g/mol (Labeled)

Colour : Colourless.

Odour : No data available. Odour threshold No data available No data available pΗ Relative evaporation rate (butylacetate=1) : No data available : -29 °C (-20 °F) Melting point Freezing point : No data available

Boiling point : 175 - 177 °C (347 - 351 °F)

Flash point : 74 °C (165 °F) Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : No data available

Vapour pressure : 0.507 hPa (0.380 mmHg) at 20 °C (68 °F)

Relative vapour density at 20 °C : No data available Relative density : No data available

Density : 0.925 g/ml at 20 °C (68 °F)

Solubility : No data available Log Pow : No data available : No data available Log Kow Viscosity, kinematic : No data available

20/04/2017 EN (English) 4/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Not available.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Bases, Oxidizing agents, Reducing agents.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%) (503-74-2 (Unlabeled))		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	3560 mg/kg	
ATE CLP (dermal)	3560.000 mg/kg bodyweight	
Additional information	LD50 Intravenous - mouse - 1,120 mg/kg	

Skin corrosion/irritation : Skin - Rabbit Result: Causes burns. - 24 h. (OECD Test Guideline 404)

Rabbit - Open irritation test - Moderate skin irritation

Serious eye damage/irritation : Serious eye damage, category 1, implicit

Respiratory or skin sensitisation : Not available

No data available
: Not available

Germ cell mutagenicity : Not available
Carcinogenicity : Not classified
Reproductive toxicity : Not available
STOT-single exposure : Not classified
No data available

: Not classified

No data available

Aspiration hazard : Not classified

Potential adverse human health effects and

symptoms

STOT-repeated exposure

: Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin. Inhalation may provoke the following symptoms: Spasm. Inflammation and edema of the bronchi. Inflammation and edema of the larynx. Pneumonitis. Pulmonary edema. Symptoms and signs of poisoning are: Burning sensation. Cough. Wheezing.

Laryngitis. Shortness of breath. Headache. Nausea. Vomiting.

Symptoms/injuries after inhalation : May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous

membranes and upper respiratory tract.

Symptoms/injuries after skin contact : May be harmful if absorbed through the skin. Causes skin burns.

Symptoms/injuries after eye contact : Causes eye burns.

Symptoms/injuries after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

20/04/2017 EN (English) 5/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Persistence and degradability

ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%) (503-74-2 (Unlabeled))

Persistence and degradability Not available.

Bioaccumulative potential

ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%) (503-74-2 (Unlabeled))

Bioaccumulative potential Not available.

Mobility in soil

ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%) (503-74-2 (Unlabeled))

Not available

Results of PBT and vPvB assessment 12.5.

No additional information available

Other adverse effects

Other adverse effects : Not available.

SECTION 13: Disposal considerations

Waste treatment methods

: Waste materials should be disposed of under conditions which meet Federal, State, and Local Regional legislation (waste)

environmental control regulations.

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed Product/Packaging disposal recommendations:

professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

UN number

UN-No.(DOT) : 3265 DOT NA no. UN3265

UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquid, acidic, organic, n.o.s.

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

: 8 - Corrosive Hazard labels (DOT)



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal...... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

20/04/2017 EN (English) 6/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Marine pollutant : No

14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : II

Class (ADR) : 8 - Corrosive substances

Hazard identification number (Kemler No.) : 80
Classification code (ADR) : C3

Danger labels (ADR) : 8 - Corrosive substances



Orange plates

80 3265

Tunnel restriction code (ADR) : E
Limited quantities (ADR) 11
EAC code : 2X
APP code : B
Excepted quantities (ADR) : E2

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 153

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

Civil Aeronautics Law : Corrosive substances(Hazardous materials notice Appended Table 1 Article 194 of the

Enforcement Regulations)

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

SARA Section 311/312 Hazard Classes Fire hazard

Immediate (acute) health hazard

20/04/2017 EN (English) 7/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

No additional information available

National regulations

No additional information available

15.3. US State regulations

ISOVALERIC ACID (2,3,4-13C3, 3-METHYL-13C, 99%)(503-74-2 (Unlabeled))		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	
State or local regulations	U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List	

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-statements:

Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H314	Causes severe skin burns and eye damage
R35	Causes severe burns
С	Corrosive

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause

serious or permanent injury.


2 - Materials that must be moderately heated or exposed to NFPA fire hazard

relatively high ambient temperatures before ignition can

occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even

under fire conditions.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

aiven

Flammability : 2 Moderate Hazard Physical : 0 Minimal Hazard

CIL Multi-Solvent Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

20/04/2017 EN (English) 8/8