



MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 17/11/2016

Revision date:

Version: 1.0

ULM-9957-S

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE
Product code : ULM-9957-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Dermal) H312
Acute Tox. 4 (Inhalation) H332
Eye Irrit. 2 H319

Full text of H-statements: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11
Xn; R20/21/22
Xi; R36

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 2 H225
Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Dermal) H312
Acute Tox. 4 (Inhalation) H332
Eye Irrit. 2A H319

Adverse physicochemical, human health and environmental effects

No additional information available

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
H319 - Causes serious eye irritation

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours
P264 - Wash Both hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P301+P312 - IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)
P330 - If swallowed, rinse mouth
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide., Dry chemical, Water spray for extinction
P403+P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container to Comply with applicable regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ACETONITRILE UNLABELED	(CAS No) 75-05-8 (EC no) 200-835-2 (EC index no) 608-001-00-3 (REACH-no) 01-2119471307-38	99.987	F; R11 Xi; R36 Xn; R20/21/22
MUSK XYLENE UNLABELED substance listed as REACH Candidate (5-tert-butyl-2,4,6-trinitro-m-xylene (musk xylene)) substance listed in REACH Annex XIV (5-tert-butyl-2,4,6- trinitro-m-xylene (Musk xylene))	(CAS No) 81-15-2 (EC no) 201-329-4	0.013	E; R2 E; R3 F; R11 Xn; R20/21/22 Xi; R36/37/38 N; R50/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETONITRILE UNLABELED	(CAS No) 75-05-8 (EC no) 200-835-2 (EC index no) 608-001-00-3 (REACH-no) 01-2119471307-38	99.987	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
MUSK XYLENE UNLABELED substance listed as REACH Candidate (5-tert-butyl-2,4,6-trinitro-m-xylene (musk xylene)) substance listed in REACH Annex XIV (5-tert-butyl-2,4,6- trinitro-m-xylene (Musk xylene))	(CAS No) 81-15-2 (EC no) 201-329-4	0.013	Expl. 1.1, H201 Flam. Sol. 1, H228 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 4, H413

Name	Product identifier	%	GHS-US classification
ACETONITRILE UNLABELED	(CAS No) 75-05-8	99.987	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
First-aid measures after inhalation	: If breathed in, move person to fresh air. If not breathing, give artificial respiration. Consult a physician.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
First-aid measures after ingestion	: Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Harmful if swallowed or if inhaled.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

- Firefighting instructions : Wear self contained breathing apparatus for fire fighting if necessary.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash Both hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed in a dry and well-ventilated place.
Storage conditions : Store at room temperature away from light and moisture.
Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available


SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACETONITRILE UNLABELED (75-05-8)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.0000000000 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	34 mg/m ³ Forms Cyanide in the body.
USA NIOSH	NIOSH REL (TWA) (ppm)	20 ppm Forms Cyanide in the body.
USA OSHA	OSHA PEL (TWA) (mg/m ³)	70 mg/m ³ The value in mg/m ³ is approximate.
USA OSHA	OSHA PEL (TWA) (ppm)	40.0000000000 ppm The value in mg/m ³ is approximate.

8.2. Exposure controls

- Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



- Hand protection : Wear suitable protective clothing and gloves.
Eye protection : Safety glasses with side-shields conforming to EN166. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH or EN 166.

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection	: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Respiratory protection	: Where appropriate, use NIOSH/CEN approved respirators.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid, clear.
Molecular mass	: 41.05 g/mol
Colour	: Colourless.
Odour	: ether-like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -48 °C (-54°F)
Freezing point	: No data available
Boiling point	: 81 - 82 °C (178 - 180 °F)
Flash point	: 2.0 °C (35.6 °F) - closed cup
Auto-ignition temperature	: 523 °C (973 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapour pressure	: 73.18 hPa (54.89 mmHg) at 15°C (59 °F), 119.81 hPa (89.86 mmHg) at 25°C(77 °F)
Relative vapour density at 20 °C	: 1.42 - (Air = 1.0)
Relative density	: No data available
Density	: 0.786 g/ml
Solubility	: Water: 100 %
Log Pow	: -0.34
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 4.4 - 16 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE	
ATE CLP (oral)	500.000 mg/kg bodyweight
ATE CLP (dermal)	1100.000 mg/kg bodyweight
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h

ACETONITRILE UNLABELED (75-05-8)	
LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	≥ 26.8 mg/l
LC50 inhalation rat (ppm)	7551 ppm - 8h
ATE CLP (oral)	500.000 mg/kg bodyweight
ATE CLP (dermal)	2000.000 mg/kg bodyweight
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h

MUSK XYLENE UNLABELED (81-15-2)	
ATE CLP (oral)	500.000 mg/kg bodyweight
ATE CLP (dermal)	1100.000 mg/kg bodyweight
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Symptoms/injuries after inhalation	: Harmful if swallowed or if inhaled.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

ACETONITRILE UNLABELED (75-05-8)	
LC50 fish 1	1640.00 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 Daphnia 1	3600 mg/l Daphnia magna (Water flea) - 48h
NOEC (chronic)	640 mg/l Daphnia magna (Water flea) - 14d

12.2. Persistence and degradability

ACETONITRILE UNLABELED (75-05-8)	
Persistence and degradability	Biodegradability Result: - Readily biodegradable.

12.3. Bioaccumulative potential

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE	
Log Pow	-0.34

ACETONITRILE UNLABELED (75-05-8)	
Log Pow	-0.34

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACETONITRILE UNLABELED (75-05-8)	
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).

12.4. Mobility in soil

ACETONITRILE UNLABELED (75-05-8)	
Ecology - soil	Not expected to absorb on soil.

12.5. Results of PBT and vPvB assessment

MUSK XYLENE UNLABELED (81-15-2)	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture meets the vPvB criteria of REACH regulation, annex XIII	

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
Waste disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Dispose of as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT)	: 1648
DOT NA no.	UN1648

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Acetonitrile
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
Marine pollutant	: No

14.3. Additional information

Other information	: No supplementary information available.
-------------------	---

Overland transport

Packing group (ADR)	: II
Class (ADR)	: 3 - Flammable liquids

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard identification number (Kemler No.) : 33
Classification code (ADR) : F1
Danger labels (ADR) : 3 - Flammable liquids



Orange plates : 

Tunnel restriction code : D/E
Limited quantities (ADR) : 11
EAC code : •2YE
Excepted quantities (ADR) : E2

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"
MFAG-No : 127

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)
Civil Aeronautics Law : Flammable liquids(Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE

Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

ACETONITRILE UNLABELED (75-05-8)

Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

15.2. International regulations

CANADA

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE

Listed on the Canadian DSL (Domestic Substances List)

ACETONITRILE UNLABELED (75-05-8)

Listed on the Canadian DSL (Domestic Substances List)

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2.1. National regulations

No additional information available

15.3. US State regulations

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE()

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.
----------------------------	---

ACETONITRILE UNLABELED (75-05-8)

U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-statements:


Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Expl. 1.1	Explosives, Division 1.1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Sol. 1	Flammable solids, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H201	Explosive; mass explosion hazard
H225	Highly flammable liquid and vapour
H228	Flammable solid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H413	May cause long lasting harmful effects to aquatic life
R11	Highly flammable
R2	Risk of explosion by shock, friction, fire or other sources of ignition
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed
R3	Extreme risk of explosion by shock, friction, fire or other sources of ignition
R36	Irritating to eyes
R36/37/38	Irritating to eyes, respiratory system and skin
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
E	Explosive
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

MUSK XYLENE UNLABELED 100 UG/ML IN ACETONITRILE ULM-9957-S

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 3 Serious Hazard
- Physical : 0 Minimal Hazard

CIL Multi-Solvent Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product