



# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 27/02/2013

Revision date: 12/01/2018

Supersedes: 19/01/2015

Version: 4.0

CDLM-9271

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Substance  
Substance name : ACETIC ANHYDRIDE (13C4, 99%; D6, 98%)  
EC Index No : 607-008-00-9 (Unlabeled)  
EC No : 203-564-8 (Unlabeled)  
CAS No : 108-24-7 (Unlabeled)  
REACH registration No : 01-2119486470-36  
Product code : CDLM-9271  
Formula : (\*CD3\*CO)2O

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-703-741-5970 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Acute Tox. 4 (Oral) H302  
Acute Tox. 3 (Inhalation:dust,mist) H331  
Skin Corr. 1A H314  
Eye Dam. 1 H318

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

T; R23  
Xn; R22  
C; R35  
Xi; R41  
R10

Full text of R-phrases: see section 16

#### GHS-US classification

Flam. Liq. 3 H226  
Acute Tox. 4 (Oral) H302  
Acute Tox. 3 (Inhalation) H331  
Skin Corr. 1A H314  
Eye Dam. 1 H318

Full text of H statements : see section 16

# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapor. Toxic if inhaled. Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage.

## 2.2. Label elements

### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H226 - Flammable liquid and vapor  
H302 - Harmful if swallowed  
H314 - Causes severe skin burns and eye damage  
H331 - Toxic if inhaled

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P260 - Do not breathe dust, fume, gas, mist, spray, vapors  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area

### GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H226 - Flammable liquid and vapor  
H302 - Harmful if swallowed  
H314 - Causes severe skin burns and eye damage  
H331 - Toxic if inhaled

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust, fume, gas, mist, spray, vapors  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective clothing, protective gloves  
P301+P312 - If swallowed: Call a doctor, a POISON CENTER if you feel unwell  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a doctor, a POISON CENTER  
P311 - Call a doctor, a POISON CENTER  
P321 - Specific treatment (see Hazardous component(s) for labeling on this label)  
P330 - Rinse mouth  
P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: Use dry sand, dry extinguishing powder, alcohol resistant foam to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool

# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P405 - Store locked up  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ACETIC ANHYDRIDE (13C4, 99%; D6, 98%)	(CAS No) 108-24-7 (Unlabeled) (EC No) 203-564-8 (Unlabeled) (EC Index No) 607-008-00-9 (Unlabeled) (REACH-no) 01-2119486470-36	100	T; R23 Xn; R22 C; R35 Xi; R41 R10

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETIC ANHYDRIDE (13C4, 99%; D6, 98%)	(CAS No) 108-24-7 (Unlabeled) (EC No) 203-564-8 (Unlabeled) (EC Index No) 607-008-00-9 (Unlabeled) (REACH-no) 01-2119486470-36	100	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318

Full text of R- and H- phrases: see section 16

Name	Product identifier	%	GHS-US classification
ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (Main constituent)	(CAS No) 108-24-7 (Unlabeled)	100	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318

Full text of H-phrases: see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after inhalation	: Toxic if inhaled.
Symptoms/injuries after skin contact	: Causes severe burns.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Dry chemical. Water spray. Dry powder. Foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Reactivity	: Flammable liquid and vapor.

# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Advice for firefighters

- Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Wear respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : Use water spray to cool exposed surfaces.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment. Avoid breathing dust, mist or spray. Avoid dust formation. Ensure there is adequate ventilation. Evacuate the danger area.
- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapors. Evacuate area. Ensure adequate air ventilation. Special attention should be given to low areas/pits where flammable vapors can accumulate.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Vacuum with an equipment that avoids ignition risk.
- Methods for cleaning up : Mechanically recover the product. Collect spillage. Vacuum with an equipment that avoids ignition risk. This material and its container must be disposed of in a safe way, and as per local legislation. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid dust formation. Provide good ventilation in process area to prevent formation of vapor. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapors, Aerosols.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Ground/bond container and receiving equipment.
- Storage conditions : Store at room temperature away from light and moisture.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	1.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	3 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract Irritation, Eye Irritation, Not classifiable as a human carcinogen.
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> Basis: USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (ceiling) (ppm)	5 ppm Basis: USA. NIOSH Recommended Exposure Limits

# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
USA OSHA	OSHA PEL (TWA) (ppm)	5 ppm Basis: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> Basis: California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm Basis: California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA OSHA	Remark (OSHA)	The value in mg/m <sup>3</sup> is approximate.

### 8.2. Exposure controls

Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing : Wear suitable protective clothing and gloves.

Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses. Safety glasses.

Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator. Wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 112.1 g/mol (Labeled)
Color	: Colorless.
Odor	: Pungent.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -73 °C (-99 °F) - lit.
Freezing point	: Not applicable
Boiling point	: 138 - 140 °C (280 - 284 °F) - lit.
Flash point	: 49 °C (120 °F) - closed cup
Auto-ignition temperature	: 316 °C (601 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable
Vapor pressure	: 5 hPa (4 mmHg) at 20 °C (68 °F); 13 hPa (10 mmHg) at 36 °C (97 °F); 6.69 hPa (5.02 mmHg)
Relative vapor density at 20 °C	: 3.52 - (Air = 1.0)
Relative density	: Not applicable
Specific gravity / density	: 1.08 g/ml at 20 °C (68 °F)
Solubility	: Water: slightly soluble
Log Pow	: -0.27
Log Kow	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 2.7 - 10.3 vol % (V)

# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor.

### 10.2. Chemical stability

Stable if stored under recommended conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Do not allow water (or moist air) contact with this material. Risk of violent reaction. Do not allow water to enter the vessels, a violent reaction may occur.

### 10.5. Incompatible materials

Acids. alcohols. Bases. Oxidizing agent. Reducing agents. Powdered metals.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation:dust,mist: Toxic if inhaled.

ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))	
LD50 oral rat	630 mg/kg
LD50 dermal rabbit	4320 mg/kg
LC50 inhalation rat (ppm)	400 ppm - 6 h
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dust, mist)	0.500 mg/l/4h

Skin corrosion/irritation	: Skin. In vitro assay. Result: Causes burns
Serious eye damage/irritation	: Eyes. rabbit. Result: Severe eye irritation
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Burning sensation. Coughing. Wheezing. Laryngitis. Shortness of breath. Spasms. Inflammation and edema of the larynx. Inflammation and edema of the bronchi. Pneumonitis. Pulmonary edema. Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/injuries after inhalation	: Toxic if inhaled.
Symptoms/injuries after skin contact	: Causes severe burns.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Harmful if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Ecology - water	: Before neutralisation, the product may represent a danger to aquatic organisms.

ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))	
LC50 fish 1	265 mg/l Leuciscus idus melanotus - 48 h
EC50 Daphnia 1	55 mg/l Daphnia (water flea) - 96 h

# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))</b>	
EC50 other aquatic organisms 1	3400 mg/l <i>Desmodesmus subspicatus</i> (green algae) - 192 h

### 12.2. Persistence and degradability

<b>ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))</b>	
Persistence and degradability	Zahn-Wellens Test - Exposure time 5 d; Result: - Readily biodegradable; (OECD Test Guideline 302B).

### 12.3. Bioaccumulative potential

<b>ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))</b>	
Log Pow	-0.27
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
- Product/Packaging disposal recommendations: : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
- Ecology - waste materials : Dispose of as unused product.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

- UN-No.(DOT) : 1715
- DOT NA no. UN1715

### 14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Acetic anhydride
- Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
- Hazard labels (DOT) : 8 - Corrosive  
3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging.  
A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging.  
A7 - Steel packaging must be corrosion-resistant or have protection against corrosion.  
A10 - When aluminum or aluminum alloy construction materials are used, they must be resistant to corrosion.  
B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Exceptions (49 CFR 173.xxx) : 154  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 243

### 14.3. Additional information

Emergency Response Guide (ERG) Number : 137  
Other information : No supplementary information available.  
Special transport precautions : Not classified as dangerous in the meaning of transport regulations.

### Overland transport

Packing group (ADR) : II  
Class (ADR) : 8 - Corrosive substances  
Hazard identification number (Kemler No.) : 83  
Classification code (ADR) : CF1  
Hazard labels (ADR) : 8 - Corrosive substances  
3 - Flammable liquids



Orange plates :

Tunnel restriction code (ADR) : D/E  
Limited quantities (ADR) : 11  
Excepted quantities (ADR) : E2

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"  
MFAG-No : 137

### Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L  
Civil Aeronautics Law : Corrosive substances

### 14.4. Environmental hazards

Other information : No supplementary information available.

### 14.5. Special precautions for user

Special transport precautions : Not classified as dangerous in the meaning of transport regulations.

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.



# ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) CDLM-9271

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

No additional information available

#### 15.2.1. National regulations

##### ACETIC ANHYDRIDE (13C4, 99%; D6, 98%) (108-24-7 (Unlabeled))

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

### 15.3. US State regulations

#### ACETIC ANHYDRIDE (13C4, 99%; D6, 98%)(108-24-7 (Unlabeled))

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
R10	Flammable
R22	Harmful if swallowed
R23	Toxic by inhalation
R35	Causes severe burns
R41	Risk of serious damage to eyes
C	Corrosive
T	Toxic
Xi	Irritant
Xn	Harmful

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



### HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 2 Moderate Hazard

Physical : 0 Minimal Hazard

CIL Multi-Solvent Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*