

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 16/12/2015

Revision date:

Version: 1.0

:

CDLM-9731-S

		substance/mixture and of the company/undertaking
1.1.	Product identifier	
Produc	et form	: Mixtures
Produc	ct name.	: BENZ[E]ACEANTHRYLENE / BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) 100 UG/M IN NONANE
Produc	ct code	: CDLM-9731-S
1.2.	Relevant identified uses of the s	substance or mixture and uses advised against
1.2.1.	Relevant identified uses	
Main u	se category	: Professional use
1.2.2.	Uses advised against	
No ado	ditional information available	
1.3.	Details of the supplier of the sa	fety data sheet
50 Fro Andove USA USA:	idge Isotope Laboratories, Inc. ntage Road er, MA 01810 1-800-322-1174 Int: 1-978-749-800 s@isotope.com www.isotope.com	0
	Emergency telephone number	
Energy and		
⊨merg	ency numbers:	
Chemt	ency numbers: rec: 1-800-424-9300 (24 hours) tional: 1-703-741-5970 (24 hours)	
Chemt Interna	rec: 1-800-424-9300 (24 hours)	on
Chemt Interna	rec: 1-800-424-9300 (24 hours) titional: 1-703-741-5970 (24 hours)	
Chemt Interna SEC1 2.1.	rec: 1-800-424-9300 (24 hours) ational: 1-703-741-5970 (24 hours) FION 2: Hazards identificatio	or mixture
Chemt Interna SEC1 2.1. Classi	rec: 1-800-424-9300 (24 hours) tional: 1-703-741-5970 (24 hours) FION 2: Hazards identificatio Classification of the substance fication according to Regulation (E	or mixture
Chemt Interna SECI 2.1. Classi Flam. I	rec: 1-800-424-9300 (24 hours) tional: 1-703-741-5970 (24 hours) FION 2: Hazards identificatio Classification of the substance fication according to Regulation (E	or mixture
Chemt Interna SECT 2.1. Classi Flam. I Acute	rec: 1-800-424-9300 (24 hours) ational: 1-703-741-5970 (24 hours) TION 2: Hazards identificatio Classification of the substance fication according to Regulation (E Liq. 3 H226 Tox. 4 (Inhalation:dust,mist) H332	or mixture
Chemt Interna SECT 2.1. Classi Flam. I Acute Skin In	rec: 1-800-424-9300 (24 hours) ational: 1-703-741-5970 (24 hours) TION 2: Hazards identificatio Classification of the substance fication according to Regulation (E Liq. 3 H226 Tox. 4 (Inhalation:dust,mist) H332 rit. 2 H315	or mixture
Chemt Interna SECT 2.1. Classi Flam. I Acute Skin In Eye Irr	rec: 1-800-424-9300 (24 hours) ational: 1-703-741-5970 (24 hours) FION 2: Hazards identification Classification of the substance fication according to Regulation (E Liq. 3 H226 Tox. 4 (Inhalation:dust,mist) H332 rit. 2 H315 it. 2 H319	or mixture
Chemt Interna SECI 2.1. Classi Flam. I Acute Skin Irr Eye Irr STOT	rec: 1-800-424-9300 (24 hours) titional: 1-703-741-5970 (24 hours) FION 2: Hazards identification Classification of the substance fication according to Regulation (E Liq. 3 H226 Tox. 4 (Inhalation:dust,mist) H332 rit. 2 H315 it. 2 H319 SE 3 H336	or mixture
Chemt Interna SEC 2.1. Classi Flam. I Acute Skin In Eye Irr STOT Asp. To	rec: 1-800-424-9300 (24 hours) titional: 1-703-741-5970 (24 hours) FION 2: Hazards identification Classification of the substance fication according to Regulation (E Liq. 3 H226 Tox. 4 (Inhalation:dust,mist) H332 rit. 2 H315 it. 2 H319 SE 3 H336	or mixture
Chemt Interna SECT 2.1. Classi Flam. I Acute Skin In Eye Irr STOT Asp. To Full tex	rec: 1-800-424-9300 (24 hours) ational: 1-703-741-5970 (24 hours) TION 2: Hazards identificatio Classification of the substance fication according to Regulation (E Liq. 3 H226 Tox. 4 (Inhalation:dust,mist) H332 rit. 2 H315 it. 2 H319 SE 3 H336 ox. 1 H304 kt of H-phrases: see section 16	or mixture :C) No. 1272/2008 [CLP]
Chemt Interna SECT 2.1. Classi Flam. I Acute Skin In Eye Irr STOT Asp. To Full tex	rec: 1-800-424-9300 (24 hours) ational: 1-703-741-5970 (24 hours) TION 2: Hazards identificatio Classification of the substance fication according to Regulation (E Liq. 3 H226 Tox. 4 (Inhalation:dust,mist) H332 rit. 2 H315 it. 2 H319 SE 3 H336 ox. 1 H304 kt of H-phrases: see section 16 fication according to Directive 67/5 20	or mixture :C) No. 1272/2008 [CLP]

Classification (GHS-US)

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Adverse physicochemical, human health and environmental effects

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements



Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to Dispose in a safe manner in accordance with local/national regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

- 3.1. Substances
- Not applicable
- 3.2. **Mixtures** Product identifier % **Classification according to** Name Directive 67/548/EEC N-NONANE UNI ABELED (CAS No) 111-84-2 99.986 R10 (EC no) 203-913-4 Xn; R20 Xn; R65 R67 Xi; R38 BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) (CAS No) 202-33-5 (Unlabeled) 0.0098 Repr.Cat.1; R60 Carc.Cat.3; R40 BENZ[E]ACEANTHRYLENE (13C2, 94%; D2, 94%) Repr.Cat.1; R60 (CAS No) 199-54-2 (Unlabeled) 0.0042 Carc.Cat.3: R40 Product identifier Classification according to Name % Regulation (EC) No. 1272/2008 [CLP] N-NONANE UNLABELED (CAS No) 111-84-2 99.986 Flam. Liq. 3, H226 (EC no) 203-913-4 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304 BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) (CAS No) 202-33-5 (Unlabeled) 0.0098 Carc. 2, H351 Repr. 1A, H360F BENZ[E]ACEANTHRYLENE (13C2, 94%; D2, 94%) 0.0042 Carc. 2, H351 (CAS No) 199-54-2 (Unlabeled) Repr. 1A, H360F Name Product identifier % **Classification (GHS-US)** N-NONANE UNLABELED (CAS No) 111-84-2 99.986 Flam. Lig. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3. H336 Asp. Tox. 1, H304

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures		
4.1.	Description of first aid measures	
First-aid measures after inhalation :		Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact :		Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Get medical advice/attention. Specific treatment (see First aid measures on this label).
4.2.	Most important symptoms and effects,	both acute and delayed
Symptoms/injuries after inhalation :		Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.
Sympto	ms/injuries after skin contact :	Causes skin irritation.
4.3.	Indication of any immediate medical at	tention and special treatment needed
No additional information available		

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	ng to Pederal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations	
SECTION 5: Firefighting measures		
5.1. Extinguishing media		
suitable extinguishing media : Dry chemical. Water spray. Foam.		
5.2. Special hazards arising from the su		
Fire hazard	: Flammable liquid and vapor.	
Explosion hazard : May form flammable/explosive vapor-air mixture.		
5.3. Advice for firefighters		
Firefighting instructions : Wear a self contained breathing apparatus.		
SECTION 6: Accidental release mea	sures	
6.1. Personal precautions, protective e	quipment and emergency procedures	
General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapour accumulating to form explosive concentrations. Vapours can accumulate in low areas.	
6.1.2. For emergency responders		
Protective equipment	: Avoid breathing dust, mist or spray.	
6.2. Environmental precautions		
Prevent entry to sewers and public waters.		
6.3. Methods and material for containm	ent and cleaning up	
For containment	: Contain spillage, then collect with non-combustible absorbent material. Disposal should be in accordance with applicable Federal, State and local regulations.	
6.4. Reference to other sections		
No additional information available		
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.	
Precautions for safe handling	: No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.	
Hygiene measures	: Wash thoroughly after handling.	
7.2. Conditions for safe storage, includ	ing any incompatibilities	
Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.	
Storage conditions	: Store at room temperature away from light and moisture.	
Incompatible materials	: Heat sources.	
7.3. Specific end use(s)		
No additional information available		
SECTION 8: Exposure controls/pers	sonal protection	
8.1. Control parameters		
BENZIE1ACEANTHRYLENE / BENZIJ1ACEA	ANTHRYLENE (13C2, 94%; D2, 94%) 100 UG/ML IN NONANE	

Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.0000000000 ppm Central Nervous System impairment.
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.0000000000 ppm Central Nervous System impairment.

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Personal protective equipment



Skin and body protection Respiratory protection

- : Wear suitable protective clothing.
- : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties		
The properties listed below are for the solvent, the main component of this mixture.			
Physical state	: Liquid		
Appearance	: Liquid.		
Molecular mass	: 128.3 g/mol		
Color	: Colorless.		
Odor	: No data available		
Odor threshold	: No data available		
рН	: No data available		
Relative evaporation rate (butyl acetate=1)	: No data available		
Melting point	: No data available		
Freezing point	: -53 °C (- 63 °F) - lit		
Boiling point	: 151 °C (304 °F) - lit		
Flash point	: 31.0 °C (87.8 °F) - closed cup		
Self ignition temperature	: 205 °C (401 °F)		
Decomposition temperature	: No data available		
Flammability (solid, gas)	: Flammable liquid and vapor		
Vapor pressure	: 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)		
Relative vapor density at 20 °C	: No data available		
Relative density	: No data available		
Density	: 0.718 g/ml		
Solubility	: Water: 0 %		
Log Pow	: 5.65		
Log Kow	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Explosive limits	: 0.87 - 2.9 % (V)		

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity		
10.1. Reactivity		
No additional information available		
10.2. Chemical stability		
See storage and expiration date on CoA.		
10.3. Possibility of hazardous reactions		
No additional information available		
10.4. Conditions to avoid		
Open flame. Overheating. Direct sunlight. Heat. Sparks.		
10.5. Incompatible materials		
No additional information available		

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products			
May release flammable gases.			
SECTION 11: Toxicological information	SECTION 11: Toxicological information		
11.1. Information on toxicological effects			
Acute toxicity : Harmful if inhaled.			
BENZ[E]ACEANTHRYLENE / BENZ[J]ACEAN	THRYLENE (13C2, 94%; D2, 94%) 100 UG/ML IN NONANE		
ATE (dust, mist) 1.500 mg/l/4h			
N-NONANE UNLABELED (111-84-2)			
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h		
LC50 inhalation rat (ppm)	3200 ppm/4h		
ATE (gases)	3200.000 ppmV/4h		
ATE (vapors)	11.000 mg/l/4h		
ATE (dust, mist)	23.760 mg/l/4h		
Skin corrosion/irritation	: Causes skin irritation.		
Serious eye damage/irritation	: Causes serious eye irritation.		
Respiratory or skin sensitization	: Not classified		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Not classified		
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.		
Specific target organ toxicity (repeated exposure)	: Not classified		
Aspiration hazard	: May be fatal if swallowed and enters airways.		
Potential Adverse human health effects and : Harmful if inhaled. symptoms			
Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.			
Symptoms/injuries after skin contact	: Causes skin irritation.		

SECT	SECTION 12: Ecological information		
12.1.	Toxicity		
No addit	ional information available		
12.2.	Persistence and degradability		

BENZ[E]ACEANTHRYLENE (13C2, 94%; D2, 94%) (199-54-2 (Unlabeled))		
Persistence and degradability	Not available.	
BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) (202-33-5 (Unlabeled))		
Persistence and degradability Not available.		
12.3. Bioaccumulative potential		
BENZ[E]ACEANTHRYLENE / BENZ[J]ACEAN	THRYLENE (13C2, 94%; D2, 94%) 100 UG/ML IN NONANE	
Log Pow 5.65		
N-NONANE UNLABELED (111-84-2)		
Log Pow	5.65	
Bioaccumulative potential	Indication of bioaccumulation.	
BENZ[E]ACEANTHRYLENE (13C2, 94%; D2, 9	4%) (199-54-2 (Unlabeled))	
Bioaccumulative potential Not available.		
BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) (202-33-5 (Unlabeled))		
Bioaccumulative potential Not available.		
12.4. Mobility in soil		
BENZ[E]ACEANTHRYLENE (13C2, 94%; D2, 94%) (199-54-2 (Unlabeled))		
Ecology - soil	Not available.	

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, Ecology - soil	Not available.
12.5. Results of PBT and vPvB assessme	ant
No additional information available	אונ
12.6. Other adverse effects	
No additional information available	
SECTION 13: Disposal consideration	ns
13.1. Waste treatment methods	
Waste disposal recommendations	: Dispose of contents/container to Comply with applicable regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
SECTION 14: Transport information	
In accordance with ADR / RID / ADNR / IMDG /	ICAO / IATA
14.1. UN number	
UN-No.(DOT)	: 1920
DOT NA no.	UN1920
14.2. UN proper shipping name	
14.2. UN proper shipping name DOT Proper Shipping Name	: Nonanes
DOT Proper Snipping Name Department of Transportation (DOT) Hazard	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Classes	
Hazard labels (DOT)	: 3 - Flammable liquid
Packing group (DOT) DOT Special Provisions (49 CFR 172.102)	 III - Minor Danger III - Minor Danger B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquid with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 5 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Tab 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
Marine pollutant	: No
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport	
Packing group (ADR)	: III
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 30
Classification code (ADR)	: F1
Danger labels (ADR)	: 3 - Flammable liquids

EN (English US)

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Orange plates	30 1920		
Tunnel restriction code	: D/E		
Limited quantities (ADR)	5L		
EAC	: 3Y		
Excepted quantities (ADR)	: E1		
Transport by sea			
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.		
MFAG-No	: 128		
Air transport			
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L		
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L		
Civil Aeronautics Law	: Flammable liquids		
14.4. Environmental hazards			
Other information	: No supplementary information available.		
14.5. Special precautions for user			
14.6. Transport in bulk according to Anne	x II of MARPOL 73/78 and the IBC Code		
Not applicable			
SECTION 15: Regulatory information	SECTION 15: Regulatory information		
15.1. US Federal regulations			
BENZ[E]ACEANTHRYLENE / BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) 100 UG/ML IN NONANE			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard		
N-NONANE UNLABELED (111-84-2)			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard		

15.2. International regulations

CANADA

BENZ[E]ACEANTHRYLENE / BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) 100 UG/ML IN NONANE Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2.1. National regulations

No additional information available

15.3. US State regulations

BENZ[E]ACEANTHRYLENE / BENZ[J]ACEANTHRYLENE (13C2, 94%; D2, 94%) 100 UG/ML IN NONANE()		
State or local regulations	U.S Massachusetts - Right To Know List	
	U.S Pennsylvania - RTK (Right to Know) List	
	U.S New Jersey - Right to Know Hazardous Substance List	
	This product does not contain any chemicals known to State of California to cause cancer,	
	birth defects, or any other reproductive harm.	

N-NONANE UNLABELED (111-84-2)		
U.S Massachusetts - Right To Know List		

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-NONANE UNLABELED (111-84-2)

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - New Jersey - Right to Know Hazardous Substance List

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 1A	Reproductive toxicity Category 1A
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H360F	May damage fertility
R10	Flammable
R20	Harmful by inhalation
R38	Irritating to skin
R40	Limited evidence of a carcinogenic effect
R60	May impair fertility
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
Xi	Irritant
Xn	Harmful

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur

Health	: 2 Moderate Hazard - Temporary or minor injury
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product