



# ETHANOL (2-13C, 99%) (<6% H2O)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/12/2010

Revision date: 31/03/2017

Supersedes: 01/09/2016

Version: 4.0

CLM-130

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	: Substance
Substance name	: ETHANOL (2-13C, 99%) (<6% H2O)
EC Index No	: 603-002-00-5 (Unlabeled)
EC No	: 200-578-6 (Unlabeled)
CAS No	: 14770-41-3
Product code	: CLM-130
Formula	: *CH3CH2OH
Synonyms	: Absolute alcohol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category	: Professional use
Industrial/Professional use spec	: For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-703-741-5970 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
STOT SE 3 H335

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11  
Xi; R36/37/38

Full text of R-phrases: see section 16

#### GHS-US classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
STOT SE 3 H335

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical equipment  
P261 - Avoid breathing gas, mist, spray, vapours  
P264 - Wash hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective clothing, protective gloves

#### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P210 - Keep away from sparks, open flames, hot surfaces, heat. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing vapours, spray, mist, gas  
P264 - Wash hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves, protective clothing  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a doctor if you feel unwell  
P321 - Specific treatment (see Hazardous component(s) for labelling on this label)  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), D-powder, alcohol resistant foam to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ETHANOL (2-13C, 99%) (<6% H2O)	(CAS No) 14770-41-3 (EC No) 200-578-6 (Unlabeled) (EC Index No) 603-002-00-5 (Unlabeled)	100	F; R11 Xi; R36/37/38
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ETHANOL (2-13C, 99%) (<6% H2O)	(CAS No) 14770-41-3 (EC No) 200-578-6 (Unlabeled) (EC Index No) 603-002-00-5 (Unlabeled)	100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of R- and H-statements: see section 16

Name	Product identifier	%	GHS-US classification
ETHANOL (2-13C, 99%) (<6% H2O) (Main constituent)	(CAS No) 14770-41-3	100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of H-statements: see section 16

#### 3.2. Mixtures

Not applicable

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Evacuate danger area.
First-aid measures after inhalation	: When symptoms occur: go into open air and ventilate suspected area. If not breathing, give artificial respiration. Get medical advice/attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get immediate medical advice/attention. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Wash skin with plenty of water. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).
First-aid measures after eye contact	: Rinse cautiously with water for several minutes.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May be harmful if inhaled. May cause respiratory irritation. May cause respiratory irritation.
Symptoms/injuries after skin contact	: May be harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.  
Explosion hazard : May form flammable/explosive vapour-air mixture.

#### 5.3. Advice for firefighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Wear a self contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear recommended personal protective equipment.  
Other information : Use water spray to cool unopened containers.

# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Avoid breathing vapours, mist, gas. Avoid dust formation.

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Comply with local regulations for disposal. Stop leak without risks if possible. Contain large spillage with sand or earth.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.  
Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. No open flames. No smoking. Use only non-sparking tools. Avoid breathing fume, gas, mist, spray, vapours. Use only outdoors or in a well-ventilated area.  
Hygiene measures : Wash hands, forearms and face thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof ventilating equipment.  
Storage conditions : Store at room temperature away from light and moisture.  
Incompatible materials : Heat sources.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

ETHANOL (2-13C, 99%) (<6% H2O) (14770-41-3)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	1000.0000000 ppm Remarks: Upper Respiratory Tract irritation Confirmed animal carcinogen with unknown relevance to humans; USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	1000 ppm Remarks: Upper Respiratory Tract irritation, Confirmed animal carcinogen with unknown relevance to humans ; USA. ACGIH Threshold Limit Values (TLV)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900 USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm USA. NIOSH Recommended Exposure Limits
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup> The value in mg/m3 is approximate ;USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

#### 8.2. Exposure controls

Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing : Wear suitable protective clothing and gloves.  
Hand protection : Wear suitable protective clothing and gloves.  
Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses.  
Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection. Wear suitable protective clothing.  
Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.  
Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Molecular mass : 47.06 g/mol (Labeled)  
Colour : Colourless.  
Odour : No data available.  
Odour threshold : No data available  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point : -143.99 °C (-227.18 °F)  
Freezing point : No data available  
Boiling point : 78 - 80 °C (172.4 - 176.0 °F)  
Flash point : 14 °C (57.2 °F) - closed cup  
Auto-ignition temperature : 363 °C (685.4 °F)  
Decomposition temperature : No data available  
Flammability (solid, gas) : Highly flammable liquid and vapour  
Vapour pressure : 59.5 hPa (44.6 mmHg) at 20.0 °C (68.0 °F)  
Relative vapour density at 20 °C : No data available  
Relative density : No data available  
Density : 0.7974 g/ml  
Solubility : Water: completely soluble  
Log Pow : -0.349 at 24 °C (75 °F)  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidising properties : No data available  
Explosive limits : 3.3 - 19 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable if stored under recommended conditions.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

Open flame. Direct sunlight. Heat. Sparks.

### 10.5. Incompatible materials

Strong oxidizing agents. Alkali metals. Peroxides.

# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

ETHANOL (2-13C, 99%) (<6% H2O) (14770-41-3)	
LD50 oral rat	10470 mg/kg
LD50 dermal rabbit	15800 mg/kg
LC50 inhalation rat (mg/l)	30000 mg/l/4h

Skin corrosion/irritation	: Skin. rabbit. No skin irritation. 24 Hours. (OECD 404 method)
Serious eye damage/irritation	: Eyes. rabbit. moderate eye irritation. (OECD 405 method)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Carcinogenicity. mouse. oral. Tumorigenic: Carcinogenic by RTECS criteria. Liver: Tumors. blood
Reproductive toxicity	: Reproductive toxicity. Reproductive toxicity - Human - female - Oral Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on Newborn: Drug dependence.
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: CNS depression. Narcosis. Damage to heart. Stomach - Irregularities - Based on Human Evidence. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/injuries after inhalation	: May be harmful if inhaled. May cause respiratory irritation. May cause respiratory irritation.
Symptoms/injuries after skin contact	: May be harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

ETHANOL (2-13C, 99%) (<6% H2O) (14770-41-3)	
LC50 fish 1	14200 mg/l - Pimephales promelas (fathead minnow) - 96 h
LC50 other aquatic organisms 1	5012 mg/l - Ceriodaphnia dubia (water flea) - 48 h
ErC50 (algae)	275 mg/l - Chlorella vulgaris (Fresh water algae) - 72 h (OECD Test Guideline 201)
NOEC (chronic)	9.6 mg/l - Daphnia magna (Water flea) - 9 d

### 12.2. Persistence and degradability

ETHANOL (2-13C, 99%) (<6% H2O) (14770-41-3)	
Biodegradation	95 % Result: - Readily biodegradable

### 12.3. Bioaccumulative potential

ETHANOL (2-13C, 99%) (<6% H2O) (14770-41-3)	
Log Pow	-0.349 at 24 °C (75 °F)
Bioaccumulative potential	Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : Toxic to aquatic life with long lasting effects. Avoid release to the environment.

# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
- Product/Packaging disposal recommendations: : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
- Ecology - waste materials : Dispose of as unused product.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

- UN-No.(DOT) : 1170
- DOT NA no. UN1170

#### 14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Ethyl alcohol solutions
- Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : 24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
- DOT Packaging Bulk (49 CFR 173.xxx) : 242

#### 14.3. Additional information

- Emergency Response Guide (ERG) Number : 127
- Other information : No supplementary information available.
- Special transport precautions : Not classified as dangerous in the meaning of transport regulations.

#### Overland transport

- Packing group (ADR) : II
- Class (ADR) : 3 - Flammable liquid
- Hazard identification number (Kemler No.) : 33
- Classification code (ADR) : F1
- Danger labels (ADR) : 3 - Flammable liquids



- Orange plates : An orange rectangular label with a black border. It is divided into two horizontal sections. The top section contains the number "33" and the bottom section contains the number "1170".

- Tunnel restriction code (ADR) : D/E

# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Limited quantities (ADR) : 11  
Excepted quantities (ADR) : E2

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
MFAG-No : 127

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L  
(49 CFR 173.27)  
DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)  
Civil Aeronautics Law : Flammable liquids

### 14.4. Environmental hazards

Other information : No supplementary information available.

### 14.5. Special precautions for user

Special transport precautions : Not classified as dangerous in the meaning of transport regulations.

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

ETHANOL (2-13C, 99%) (<6% H2O) (14770-41-3)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

### 15.2. International regulations

#### CANADA

ETHANOL (2-13C, 99%) (<6% H2O) (14770-41-3)
Listed on the Canadian DSL (Domestic Substances List)

#### 15.2.1. National regulations

No additional information available

### 15.3. US State regulations

ETHANOL (2-13C, 99%) (<6% H2O)(14770-41-3)	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information



# ETHANOL (2-13C, 99%) (<6% H2O) CLM-130

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
R11	Highly flammable
R36/37/38	Irritating to eyes, respiratory system and skin
F	Highly flammable
Xi	Irritant

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

CIL Multi-Solvent Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*