

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 04/10/2017 Revision date: Version: 1.0 CLM-8989-S

SECTION 1:	Identification of the subs	stance/mixture and of the company/undertaking		
	uct identifier			
Product form		: Mixtures		
Product name		: 7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE		
Product code		: CLM-8989-S		
1.2. Relev	1.2. Relevant identified uses of the substance or mixture and uses advised against			
1.2.1. Relev	ant identified uses			
Main use categ	ory	: Professional use		
Industrial/Profes	ssional use spec	: For professional use only		
1.2.2	adviced enginet			
	advised against formation available			
	Is of the supplier of the safety d	lata sheet		
50 Frontage Ro	ope Laboratories, Inc. ad			
Andover, MA 0				
USA				
cilsales@isotop	2-1174 Int: 1-978-749-8000 e.com www.isotope.com			
	'			
Emergency nur	gency telephone number			
• •	00-424-9300 (24 hours)			
	-703-741-5970 (24 hours)			
SECTION 2	Hazards identification			
	sification of the substance or mi	ixture		
	according to Regulation (EC) No	0 1272/2008 ICL P1		
Flam. Liq. 2 H2				
Skin Irrit. 2 H				
	361			
STOT SE 3 H				
STOT RE 2 H				
Asp. Tox. 1 H				
•	ard classes and H-statements : see	a saction 16		
I un text of flaza				
Classification	according to Directive 67/548/El	EC [DSD] or 1999/45/EC [DPD]		
F; R11				
Xi; R38				
Xn; R65 Repr.Cat.3; R62	2			
Repr.Cat.3; R6				
R67				
N; R51/53 Xn; R48/20				
	arases: see section 16			
	firstion			
GHS-US classi				
Flam. Liq. 2 Skin Irrit. 2	H225 H315			
Repr. 2	H361			
STOT SE 3	H336 H373			

H304 Aquatic Acute 2 H401 Full text of H statements : see section 16

H373

STOT RE 2

Asp. Tox. 1

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

brain. kidneys. liver. urinary bladder. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs (brain, kidneys, liver, urinary bladder) (if inhaled, if swallowed, in contact with skin). May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation.

2.2. Label elements				
Labeling according to Regulation (EC) No. 1272/2008 [CLP]				
Hazard pictograms (CLP)				
	GHS02 GHS08 GHS07			
Signal word (CLP)	: Danger			
Hazard statements (CLP)	 H225 - Highly flammable liquid and vapor H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging the unborn child (if inhaled, if swallowed, in contact with skin) H373 - May cause damage to organs (liver, kidneys, brain, urinary bladder) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed) 			
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P260 - Do not breathe dust, fume, gas, mist, spray, vapors P264 - Wash hands, forearms and face thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P280 - Wear face shield, protective clothing, protective gloves, eye protection 			
GHS-US labeling				
Hazard pictograms (GHS-US)	HS02 GHS02 GHS08 GHS07			
Signal word (GHS-US)	: Danger			
	 Highly flammable liquid and vapor H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation H336 - May cause drowsiness or dizziness H361 - Suspected of damaging fertility, Suspected of damaging the unborn child (Dermal, Inhalation, oral) H373 - May cause damage to organs (kidneys, liver, urinary bladder, brain) through prolonged or repeated exposure (Dermal, Inhalation, oral) H401 - Toxic to aquatic life 			
Precautionary statements (GHS-US)	 P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, hot surfaces, open flames, sparks No smoking P233 - Keep container tightly closed P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical, lighting, ventilating equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P260 - Do not breathe fume, mist, spray, vapors P261 - Avoid breathing dust, fume, gas, mist, spray, vapors P264 - Wash hands, forearms and face thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P273 - Avoid release to the environment P280 - Wear eye protection, face protection, protective clothing, protective gloves P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER P302+P352 - If on skin: Wash with plenty of water 			

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

- P304+P340 If initialed. Remove person to nesh all and keep combination of breathin P308+P313 - If exposed or concerned: Get medical advice/attention
- P312 Call a doctor, a POISON CENTER if you feel unwell
- P314 Get medical advice/attention if you feel unwell
- P321 Specific treatment (see Hazardous component(s) for labeling on this label)
- P331 Do NOT induce vomiting
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P362+P364 Take off contaminated clothing and wash it before reuse
- P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing powder to extinguish
- P403+P233 Store in a well-ventilated place. Keep container tightly closed
- P403+P235 Store in a well-ventilated place. Keep cool
- P405 Store locked up

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

PBT: not relevant - no registration required

SECTION 3: Composition/Information on ingredients

3.1. Substances

- Not applicable
- 3.2. Mixtures

3.2. Mixtures			
Name	Product identifier	%	Classification according to Directive 67/548/EEC
TOLUENE UNLABELED	(CAS No) 108-88-3 (EC No) 203-625-9 (EC Index No) 601-021-00-3 (REACH-no) 01-2119471310-51	99.9942	F; R11 Xi; R38 Xn; R65 Repr.Cat.3; R62 Repr.Cat.3; R63 R67 N; R51/53 Xn; R48/20
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%)	(CAS No) 20268-52-4 (Unlabeled) (EC Index No)	0.0058	Carc.Cat.1; R45 N; R50/53
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
TOLUENE UNLABELED	(CAS No) 108-88-3 (EC No) 203-625-9 (EC Index No) 601-021-00-3 (REACH-no) 01-2119471310-51	99.9942	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%)	(CAS No) 20268-52-4 (Unlabeled) (EC Index No)	0.0058	Carc. 1B, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Name	Product identifier	%	GHS-US classification
TOLUENE UNLABELED	(CAS No) 108-88-3	99.9942	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%)	(CAS No) 20268-52-4 (Unlabeled)	0.0058	Carc. 1B, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures		
4.1.	Description of first aid measures	
First-aid measures general		: IF exposed or concerned: Get medical advice/attention.

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

26, 2012 / Rules and Regulations	
First-aid measures after inhalation	Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Gently wash with plenty of soap and water, Get immediate medical advice/attention. Get medical advice/attention. Specific treatment (see Hazard pictograms (CLP) on this label).
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, i present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Immediately call a poison center or doctor/physician.
4.2. Most important symptoms and e	effects, both acute and delayed
Symptoms/injuries	: Suspected of damaging fertility. Suspected of damaging the unborn child (in contact with skin, inhaled, if swallowed). Causes damage to organs (kidneys, liver, urinary bladder, brain) (in contact with skin, if inhaled, if swallowed).
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Symptoms/injuries after eye contact	: May cause eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.
4.3. Indication of any immediate me	dical attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measure	es
5.1. Extinguishing media	
Suitable extinguishing media	: Dry powder. Dry sand. Dry chemical. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from the	e substance or mixture
Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: vapors may form flammable mixture with air. Highly flammable liquid and vapor.
5.3. Advice for firefighters	
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Wear recommended personal protective equipment.
Other information	: Use water spray to cool exposed surfaces.
SECTION 6: Accidental release m	neasures
	e equipment and emergency procedures
General measures	: Flammable liquids. No open flames. No smoking. Eliminate every possible source of ignition. Use special care to avoid static electric charges.
6.1.1. For non-emergency personnel	
Emergency procedures	: Use personal protective equipment as required. Ensure adequate air ventilation. Avoid breathing vapors, mist, gas. Eliminate all ignition sources if safe to do so. Evacuate unnecessary personnel. Special attention should be given to low areas/pits where flammable vapors can accumulate.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Prevent liquid from entering sewers, waterco product into the environment.	burses, underground or low areas. Do not allow to enter drains or water courses. Do not discharge the
6.3. Methods and material for contai	inment and cleaning up
For containment	: Dike and contain spill.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4.Reference to other sectionsFor further information refer to section 13.		
SECTION 7: Handling and storage	e	
7.1. Precautions for safe handling		
Additional hazards when processed	: Avoid all contact with skin, eyes, or clothing. Handle empty containers with care because residual vapors are flammable. Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). Keep away from sources of ignition - No smoking.	
Precautions for safe handling	No open flames. No smoking. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, fume, gas, mist, spray, vapors. Use only outdoors or in a well-ventilated area.	
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Wash hands, forearms and face thoroughly after handling.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures	: Ground/bond container and receiving equipment. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof Lighting equipment, ventilating equipment.	
Storage conditions	: Store at room temperature away from light and moisture.	
Incompatible materials	: Heat sources.	
Storage area	: Under inert gas.	

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.0000000 ppm
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Visual impairment. Female reproductive. Pregnancy loss. 2015 Adoption. Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen.; Component: Toluene CAS-No.: 108-88-3 Parameters Toluene Value: 0.0300 mg/l Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS- No.: 108-88-3 Parameters: Toluene Value: 0.0200 mg/l Biological specimen: In blood Remarks: Prior t last shift of workweek Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS- No.: 108-88-3 Parameters: o-Cresol Value: 0.3000 mg/g Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	375 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm USA. NIOSH Recommended Exposure Limits
USA OSHA	OSHA PEL (TWA) (mg/m³)	375 mg/m ³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (mg/m³)	560 mg/m ³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-2

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE				
USA OSHA	Remark (OSHA)	OSHA PEL (TWA) - 200 ppm - USA. Occupational Exposure Limits (OSHA) - Table Z-2. Remarks: Z37.12-1967		
TOLUENE UNLABELED (108	3-88-3)			
Italy - Portugal - USA ACGIH		20.0000000 ppm		
Italy - Portugal - USA ACGIH		Visual impairment. Female reproductive. Pregnancy loss. 2015 Adoption. Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen.; Component: Toluene CAS-No.: 108-88-3 Parameters: Toluene Value: 0.0300 mg/l Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS- No.: 108-88-3 Parameters: Toluene Value: 0.0200 mg/l Biological specimen: In blood Remarks: Prior to last shift of workweek Basis: ACGIH - Biological Exposure Indices (BEI); Component: Toluene CAS- No.: 108-88-3 Parameters: o-Cresol Value: 0.3000 mg/g Biological specimen: Urine Remarks: End of shift (As soon as possible after exposure ceases) Basis: ACGIH - Biological Exposure Indices (BEI)		
USA NIOSH	NIOSH REL (TWA) (mg/m³)	375 mg/m ³ USA. NIOSH Recommended Exposure Limits		
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm USA. NIOSH Recommended Exposure Limits		
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³ USA. NIOSH Recommended Exposure Limits		
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm USA. NIOSH Recommended Exposure Limits		
USA OSHA	OSHA PEL (TWA) (mg/m³)	375 mg/m ³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000		
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000		
USA OSHA	OSHA PEL (STEL) (mg/m ³)	560 mg/m ³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000		
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants 1910.1000		
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-2		
USA OSHA	Remark (OSHA)	OSHA PEL (TWA) - 200 ppm - USA. Occupational Exposure Limits (OSHA) - Table Z-2. Remarks: Z37.12-1967		

8.2. Exposure controls

Appropriate engineering controls

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Personal protective equipment

Materials for protective clothing

Environmental exposure controls

Skin and body protection

Respiratory protection

smoking and when leaving work. : Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



- : Wear suitable protective clothing and gloves.
- : Wear suitable protective clothing and gloves.
- : Wear eye protection. Chemical goggles or face shield with safety glasses.
- : Wear suitable protective clothing, gloves and eye/face protection. Wear suitable protective clothing.
- : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

: Avoid release to the environment.

Hand protection

Eye protection

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

26, 2012 / Rules and Regulations				
SECTION 9: Physical and chemical properties				
9.1. Information on basic physical and chemical properties				
The properties listed below are for the solvent, the main component of this mixture.				
Physical state	: Liquid			
Appearance	: Liquid.			
Molecular mass	: 92.14 g/mol			
Color	: Colorless.			
Odor	: No data available.			
Odor threshold	: No data available			
рН	: No data available			
Relative evaporation rate (butyl acetate=1)	: No data available			
Melting point	: -93 °C (-135 °F)			
Freezing point	: No data available			
Boiling point	: 110 - 111 °C (230 - 232 °F)			
Flash point	: 4 °C (39.2 °F) - closed cup			
Auto-ignition temperature	: 535 °C (995 °F)			
Decomposition temperature	: No data available			
Flammability (solid, gas)	: Highly flammable liquid and vapor			
Vapor pressure	: 29.1 hPa (21.8 mmHg) at 20.0 °C (68.0 °F)			
Relative vapor density at 20 °C	: No data available			
Relative density	: No data available			
Specific gravity / density	: 0.865 g/ml at 25 °C (77 °F)			
Solubility	: Water: 0.5 g/l at 15 °C (59 °F)			
Log Pow	No data available			
Log Kow	No data available			
Viscosity, kinematic	No data available			
Viscosity, dynamic	: No data available			
Explosive properties	: No data available			
Oxidizing properties	: No data available			
Explosion limits	: 1.2 - 7 % (V)			
9.2. Other information				
No additional information available				
SECTION 10: Stability and reactivity				
10.1. Reactivity				
vapors may form flammable mixture with air. Highly flammable liquid and vapor.				
10.2. Chemical stability				
See storage and expiration date on CoA.				
10.3. Possibility of hazardous reactions				
No dangerous reactions known under normal conditions of use.				
10.4. Conditions to avoid				
Heat. Open flame. Sparks. Direct sunlight. Extremely high or low temperatures.				
10.5. Incompatible materials				
Strong oxidizing agents.				

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2).

SECTION 11: Toxicological information				
11.1. Information on toxicological effects	1.1. Information on toxicological effects			
Acute toxicity :	cute toxicity : Not classified			
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE				
LD50 oral rat	> 5580 mg/kg			
LD50 dermal rabbit	12196 mg/kg			
LC50 inhalation rat (mg/l)	12500 - 28800 mg/m³ 4 h			

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7-CHLOROBENZ[A]ANTHRACENE (13C6, 9	%) 50 UG/ML IN TOLUENE			
ATE CLP (dermal)	12196.000 mg/kg body weight			
ATE CLP (vapors)	12.500 mg/l/4h			
ATE CLP (dust, mist)	12.500 mg/l/4h			
TOLUENE UNLABELED (108-88-3)				
LD50 oral rat	> 5580 mg/kg			
LD50 dermal rabbit	12196 mg/kg			
LC50 inhalation rat (mg/l)	12500 - 28800 mg/m ³ 4 h			
ATE CLP (dermal)	12196.000 mg/kg body weight			
ATE CLP (vapors)	12.500 mg/l/4h			
ATE CLP (dust, mist)	12.500 mg/l/4h			
7-CHLOROBENZ[A]ANTHRACENE (13C6, 9	%) (20268-52-4 (Unlabeled))			
Additional information	LD50 Intravenous - Rat - > 200 mg/kg			
Skin corrosion/irritation	: Causes skin irritation.			
	Skin			
	rabbit			
	Causes skin irritation 24 Hours			
Corious que demore/irritation				
Serious eye damage/irritation	: Not classified			
	Eyes rabbit			
	No eye irritation			
	(OECD 405 method)			
Respiratory or skin sensitization	: Not available			
	No data available			
Germ cell mutagenicity	: rat. liver. DNA Damage			
Carcinogenicity	: Not classified			
Reproductive toxicity	: Damage to fetus possible. Suspected human reproductive toxicant Reproductive toxicity - Rat - Inhalation. Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count) Experiments have shown reproductive toxicity effects in male and female laboratory animals Developmental Toxicity - Rat - Oral. Effects on Embryor or Fetus: Fetotoxicity (except death, e.g, stunted fetus).			
Specific target organ toxicity - single exposure	: May cause drowsiness or dizziness.			
	No data available			
Specific target organ toxicity – repeated exposure	: May cause damage to organs (liver, kidneys, brain, urinary bladder) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed).			
	No data available			
Aspiration hazard	: May be fatal if swallowed and enters airways.			
Potential Adverse human health effects and symptoms	: Symptoms/injuries. IF INHALED: lungs. Pulmonary irritation. Pulmonary edema. Chest pain. central nervous system. This information is based on our current knowledge and is intended t describe the product for the purposes of health, safety and environmental requirements only. should not therefore be construed as guaranteeing any specific property of the product. Stomach - Irregularities - Based on Human Evidence. Lung irritation, chest pain, pulmonay edema, Inhalation sudies have shown the development of inflammatory and ulcerous lesions the penis, prepuce, and scrotom in animals.			
IARC group	: 3			
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness or dizziness.			
Symptoms/injuries after skin contact	: Harmful in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.			
Symptoms/injuries after eye contact	: May cause eye irritation.			
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.			

SECTION 12: Ecological	information	
12.1. Toxicity		
Ecology - general	: Toxic to bees.	
Ecology - water	: Toxic to aquatic life.	
7-CHLOROBENZ[A]ANTHRA	CENE (13C6, 99%) 50 UG/ML IN TOLUENE	
EC50 Daphnia 1	8 mg/l Daphnia magna (Water flea) - 24h	
06/10/2017	EN (English LIS)	8/13

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE				
LC50 fish 2	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h			
EC50 Daphnia 2	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h			
ErC50 (algae)	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h			
ErC50 (other aquatic plants)	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h			
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d			
TOLUENE UNLABELED (108-88-3)				
EC50 Daphnia 1	8 mg/l Daphnia magna (Water flea) - 24h			
LC50 fish 2	7.63 mg/l Oncorhynchus mykiss (Rainbow trout) - 96 h			
EC50 Daphnia 2	6 mg/l Daphnia magna (Water flea) - Immobilization - 48 h			
ErC50 (algae)	245 mg/l Chlorella vulgaris (Fresh water algae) - 24 h			
ErC50 (other aquatic plants)	10 mg/l Pseudokirchneriella subcapitata (Green algae) - 24 h			
NOEC (chronic)	5.44 mg/l Pimephales promelas (fathead minnow) - 7 d			

7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE				
Persistence and degradability Readily biodegradable.				
TOLUENE UNLABELED (108-88-3)				
Persistence and degradability	Readily biodegradable.			
12.3. Bioaccumulative potential				
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE				
BCF fish 1 0.05 mg/l Leuciscus idus (Golden orfe) - 3 d				
Bioconcentration factor (BCF REACH) 90				
TOLUENE UNLABELED (108-88-3)				
BCF fish 1 0.05 mg/l Leuciscus idus (Golden orfe) - 3 d				
Bioconcentration factor (BCF REACH) 90				
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) (20268-52-4 (Unlabeled))				
Log Pow	5.7996			
12.4. Mobility in soil				

No additional information available

12.5 Results of PBT and vPvB assessm

12.3. Results of FDT allu VFVD assessmen	it.			
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE				
PBT: not relevant – no registration required				
TOLUENE UNLABELED (108-88-3)				
PBT: not relevant – no registration required				
12.6. Other adverse effects				
Other adverse effects	: Toxic to aquatic life with long lasting effects. Disposal must be done according to official regulations. Avoid release to the environment.			

13.1. Waste treatment methods Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Loca environmental control regulations. Product/Packaging disposal recommendations: : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Additional information : Handle empty containers with care because residual vapors are flammable.
environmental control regulations. Product/Packaging disposal recommendations: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
professional waste disposal service to dispose of this material.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Dispose of as unused product.
SECTION 14: Transport information

00/40/0047		0/40
Proper Shipping Name (DOT)	: Toluene	
14.2. UN proper shipping name		
	011234	
DOT NA no.	UN1294	
UN-No.(DOT)	: 1294	
14.1. UN number		
In accordance with ADR / RID / IMDG / IAT	A / ADN	
ocorron 14. Transport informa		

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
	FLAMMABLE LIQUID
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal
	during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT RQ	: 1000 lbs
Marine pollutant	: No
14.3. Additional information	
Other information	: No supplementary information available.
Overland transport	
Overland transport	
Packing group (ADR)	: II
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 33 : F1
Classification code (ADR) Hazard labels (ADR)	: 3 - Flammable liquids
Orange plates	
	<u>33</u> 1294
Tunnel restriction code (ADR)	: D/E
Limited quantities (ADR)	11
EAC	: 3YE
Excepted quantities (ADR)	: E2
Transport by sea	
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" or passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
MFAG-No	: 130
Air transport	
DOT Quantity Limitations Passenger aircraft/rail	: 5L
(49 CFR 173.27)	· 60 l
	: 60 L
(49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49	: 60 L : Flammable liquids
(49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50 UG/ML IN TOLUENE				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
CERCLA RQ	1000 lb			
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
TOLUENE UNLABELED (108-88-3)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
CERCLA RQ	1000 lb			
SARA Section 302 Threshold Planning Quantity (TPQ)	SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) (20268-52-4 (Unlabeled))				
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.			
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313			
15.2. International regulations				

CANADA

7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) 50) UG/ML IN TOLUENE
Listed on the Canadian DSL (Domestic Substances L	ist)
TOLUENE UNLABELED (108-88-3)	

15.2.1. National regulations

No additional information available

15.3. US State regulations

7-CHLOROBENZ[A]ANTHRA	CENE (13C6, 99%) 50	UG/ML IN TOLUENE				
U.S California - Proposition 6	65 - Carcinogens List	No				
U.S California - Proposition 6 Toxicity	65 - Developmental	Yes				
U.S California - Proposition 6 Toxicity - Female	65 - Reproductive	No				
U.S California - Proposition 6 Toxicity - Male	65 - Reproductive	No				
No significant risk level (NSRL))	7000				
State or local regulations		U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S Pennsylvania - RTK (Right to Know) List U.S Massachusetts - Right To Know List				
TOLUENE UNLABELED (108	-88-3)	·				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk level		

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	7000

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) (20268-52-4 (Unlabeled))					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
Yes	No	No	No	7000	
TOLUENE UNLABELED (108-88-3) State or local regulations					
U.S Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S New Jersey - Right to Know Hazardous Substance List U.S New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S Pennsylvania - RTK (Right to Know) List U.S Massachusetts - Right To Know List					
7-CHLOROBENZ[A]ANTHRACENE (13C6, 99%) (20268-52-4 (Unlabeled))					
State or local regulations					
U.S Massachusetts - Right U.S New Jersey - Right to U.S Pennsylvania - RTK (F	Know Hazardous Substance	List			

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-phrases:

Hazardous to the aquatic environment - Acute Hazard Category 1
Hazardous to the aquatic environment - Chronic Hazard Category 1
Aspiration hazard Category 1
Carcinogenicity Category 1B
Flammable liquids Category 2
Reproductive toxicity Category 2
Skin corrosion/irritation Category 2
Specific target organ toxicity (repeated exposure) Category 2
Specific target organ toxicity (single exposure) Category 3
Highly flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
May cause drowsiness or dizziness
May cause cancer
Suspected of damaging fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure
Very toxic to aquatic life
Very toxic to aquatic life with long lasting effects
Highly flammable
Irritating to skin
May cause cancer
Harmful: danger of serious damage to health by prolonged exposure through inhalation
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Possible risk of impaired fertility
Possible risk of harm to the unborn child
Harmful: may cause lung damage if swallowed
Vapors may cause drowsiness and dizziness
Highly flammable
Dangerous for the environment
Irritant
Harmful

TOLUENE CLM-8989-S

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product