



ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 12/17/2010 Revision date: 5/17/2023 Supersedes: 9/1/2015 Version: 4.1

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : ISOPROPANOL-D8 (D, 99%)
Chemical name : ISOPROPANOL-D8 (D, 99%)
CAS-No. : 67-63-0
Product code : DLM-44
Formula : C3H8O
Synonyms : sec-Propyl alcohol / Isopropyl alcohol / 2-Propanol

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Cambridge Isotope Laboratories, Inc.
50 Frontage Rd
01810
ANDOVER, MA, 01810
USA
T 1-800-322-1174
cilsales@isotope.com - www.isotope.com

1.4. Emergency telephone number

Emergency number : 1-703-741-5970
Chemtrec 1-800-424-9300 24 hours

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. sparks, open flames, hot surfaces, heat
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P241 - Use explosion-proof electrical equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing vapors, spray, mist, dust.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P370+P378 - In case of fire: Use D-powder, carbon dioxide (CO₂), alcohol resistant foam to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%	GHS US classification
ISOPROPANOL-D8 (D, 99%) (Main constituent)	CAS-No.: 67-63-0	100	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). Evacuate danger area.
First-aid measures after inhalation : When symptoms occur: go into open air and ventilate suspected area. If not breathing, give artificial respiration. Get medical advice/attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention. Specific measures (see Hazard pictograms (CLP) on this label). Wash contaminated clothing before reuse.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Fatal in contact with skin. central nervous system. Prolonged or repeated exposure can cause: Nausea, Dizziness, Headache, Vomiting, Diarrhoea, Convulsions. Aspiration of this material may cause chemical pneumonia. Kidney - irregularities - Based on Human Evidence.

Symptoms/effects : May cause damage to organs (kidneys, Eyes, Skin) (in contact with skin, if inhaled, if swallowed).

Symptoms/effects after inhalation : May be harmful if inhaled. May cause respiratory irritation.

Symptoms/effects after skin contact : May be harmful in contact with skin. May cause skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂).

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : May form flammable/explosive vapor-air mixture.

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance. Wear a self contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Avoid breathing vapors, mist, gas. Avoid dust formation. Use personal protective equipment as required. Ensure adequate air ventilation. Evacuate danger area.

6.1.2. For emergency responders

Protective equipment : Avoid breathing Dust, vapors.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

For containment : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapor concentrations. No open flames. No smoking. Use only non-sparking tools. Do not get in eyes, on skin, or on clothing. Avoid breathing dust, mist, spray, vapors.
Hygiene measures : Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions : Store at room temperature away from light and moisture.
Incompatible materials : Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ISOPROPANOL-D8 (D, 99%) (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA [ppm]	200 ppm Remarks: Central Nervous System impairment, Upper Respiratory Tract irritation ,Eye irritation, Substances for which there is a Biological Exposure Index or Indices see BEI® (section), Not classifiable as a human carcinogen; USA. ACGIH Threshold Limit Values (TLV)
ACGIH OEL STEL [ppm]	400 ppm Remarks: Central Nervous System impairment, Upper Respiratory Tract irritation ,Eye irritation, Substances for which there is a Biological Exposure Index or Indices see BEI® (section), Not classifiable as a human carcinogen; USA. ACGIH Threshold Limit Values (TLV)
Remark (ACGIH)	Component: 2-Propanol; CAS-No- 67-63-0; Parameters- Acetone; Value- 40.0000 mg/l; Biological specimen- Urine; Basis- ACGIH-Biological; Remarks: End of shift at end of workweek; Exposure Indices (BEI)
Regulatory reference	ACGIH 2022
USA - ACGIH - Biological Exposure Indices	
Local name	2-PROPANOL
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2022

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ISOPROPANOL-D8 (D, 99%) (67-63-0)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	980 mg/m ³ The value in mg/m ³ is approximate. USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA PEL TWA [2]	400 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA PEL STEL [1]	1225 mg/m ³ California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA PEL STEL [2]	500 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA PEL C	980 mg/m ³ California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA PEL C [ppm]	400 ppm California permissible exposure limits for chemical contaminants (Title 8, Article 107)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	980 USA. NIOSH Recommended Exposure Limits
NIOSH REL TWA [ppm]	400 ppm USA. NIOSH Recommended Exposure Limits
NIOSH REL STEL	1225 mg/m ³ USA. NIOSH Recommended Exposure Limits
NIOSH REL STEL [ppm]	500 ppm USA. NIOSH Recommended Exposure Limits

8.2. Appropriate engineering controls

- Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.

Materials for protective clothing:

Wear suitable protective clothing and gloves

Hand protection:

Wear suitable protective clothing and gloves

Eye protection:

Wear eye protection. Chemical goggles or face shield with safety glasses

Skin and body protection:

Wear suitable protective clothing, gloves and eye/face protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

Personal protective equipment symbol(s):



ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colorless
Odor	: Alcohol-like
Odor threshold	: No data available
pH	: No data available
Melting point	: -89.5 °C (-129.1 °F)
Freezing point	: No data available
Boiling point	: 82 °C (180 °F)
Flash point	: 12 °C (53.6 °F) - closed cup
Relative evaporation rate (butyl acetate=1)	: 3
Flammability (solid, gas)	: Highly flammable liquid and vapor.
Vapor pressure	: 43.2 hPa (32.4 mmHg) at 20.0 °C (68.0 °F); 58.7 hPa (44.0 mmHg) at 25.0 °C (77.0 °F)
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.785 g/ml at 25 °C (77 °F)
Molecular mass	: 68.14 g/mol (Labeled)
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: 0.05
Auto-ignition temperature	: 425 (797.0 °F)
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: 2 – 12.7 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4. Conditions to avoid

Open flame. Direct sunlight. Avoid Heat, Flames and Sparks.

10.5. Incompatible materials

Strong oxidizing agents. Acid anhydrides. Aluminum. Halogenated compounds. Acids.

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ISOPROPANOL-D8 (D, 99%) (67-63-0)	
LD50 oral rat	5045 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Somnolence (general)
LD50 dermal rat	12800 mg/kg - Rabbit
LC50 Inhalation - Rat [ppm]	16000 - 8 h
ATE US (oral)	5045 mg/kg body weight
ATE US (dermal)	12800 mg/kg body weight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

ISOPROPANOL-D8 (D, 99%) (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Potential Adverse human health effects and symptoms : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Fatal in contact with skin. central nervous system. Prolonged or repeated exposure can cause: Nausea, Dizziness, Headache, Vomiting, Diarrhoea, Convulsions. Aspiration of this material may cause chemical pneumonia. Kidney - irregularities - Based on Human Evidence.
Symptoms/effects : May cause damage to organs (kidneys, Eyes, Skin) (in contact with skin, if inhaled, if swallowed).
Symptoms/effects after inhalation : May be harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact : May be harmful in contact with skin. May cause skin irritation.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

ISOPROPANOL-D8 (D, 99%) (67-63-0)	
LC50 - Fish [1]	9640 mg/l - Pimephales promelas (fathead minnow) - 96 h

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ISOPROPANOL-D8 (D, 99%) (67-63-0)	
EC50 - Crustacea [1]	5102 mg/l - Daphnia magna (Water flea) - 24 h
ErC50 algae	> 1000 mg/l - 24 h
ErC50 other aquatic plants	EC50 - > 2,000.00 mg/l - Desmodesmus subspicatus (green algae) - 72 h
Additional information	EC50 (Daphnia Magna) -invertebrates. :

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

ISOPROPANOL-D8 (D, 99%) (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
Product/Packaging disposal recommendations	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No	: UN1219
UN-No. (TDG)	: Not applicable
UN-No. (IMDG)	: 1219
UN-No. (IATA)	: 1219

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Isopropyl alcohol
Proper Shipping Name (TDG)	: Not applicable
Proper Shipping Name (IMDG)	: ISOPROPANOL (ISOPROPYL ALCOHOL)
Proper Shipping Name (IATA)	: Isopropanol

14.3. Transport hazard class(es)

DOT	
Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : Not applicable
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Not classified as dangerous in the meaning of transport regulations

DOT

UN-No.(DOT) : UN1219
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx) : 4b;150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

Emergency Response Guide (ERG) Number : 129

IMDG

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B
Flash point (IMDG) : 12°C c.c.
Properties and observations (IMDG) : Colourless, mobile liquid. Flashpoint: 12°C c.c. Explosive limits: 2% to 12% Miscible with water.
MFAG-No : 129

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provision (IATA) : A180
ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

ISOPROPANOL-D8 (D, 99%) (67-63-0)

Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
ISOPROPANOL-D8 (D, 99%)	67-63-0	Present	Active	

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

ISOPROPANOL-D8 (D, 99%) (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

ISOPROPANOL-D8 (D, 99%) (67-63-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on TECI (Thailand Existing Chemicals Inventory)

15.3. US State regulations

ISOPROPANOL-D8 (D, 99%) (67-63-0)

State or local regulations

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/17/2023

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of H-phrases

H225 Highly flammable liquid and vapor

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

ISOPROPANOL-D8 (D, 99%)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.