



MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 2/28/2017 Revision date: 7/31/2023 Supersedes: 2/28/2017 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE
Product code : DLM-8278-S

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Cambridge Isotope Laboratories, Inc.
50 Frontage Rd
01810
ANDOVER, MA, 01810
USA
T 1-800-322-1174
cilsales@isotope.com - www.isotope.com

1.4. Emergency telephone number

Emergency number : 1-703-741-5970
Chemtrec 1-800-424-9300 24 hours

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture



GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Acute toxicity (dermal) Category 4	H312	Harmful in contact with skin
Acute toxicity (inhalation) Category 4	H332	Harmful if inhaled
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :  

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. sparks, open flames, heat, hot surfaces
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P241 - Use explosion-proof electrical equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing vapors, mist, gas.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing.
P301+P312 - If swallowed: Call a doctor if you feel unwell.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a doctor if you feel unwell.
P322 - Specific treatment (see Hazard pictograms (CLP) on this label)
P330 - Rinse mouth.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use alcohol resistant foam, foam, D-powder, carbon dioxide (CO₂) to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name : MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Name	Product identifier	%	GHS US classification
ACETONITRILE UNLABELED	CAS-No.: 75-05-8	99.987	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319
MUSK XYLENE (TERT-BUTYL-D9, 98%)	CAS-No.: 81-15-2 (Unlabeled)	0.013	Expl. 1.1, H201 Flam. Sol. 1, H228 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 4, H413

Full text of hazard classes and H-statements : see section 16

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Evacuate area.
First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. If not breathing, give artificial respiration. Call a physician immediately. Get immediate medical advice/attention.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Specific measures (see Hazard pictograms (CLP) on this label). Wash with plenty of soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open. Get immediate medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Treat as cyanide poisoning. Always have on hand a cyanide first-aid kit, together with proper instructions. The onset of symptoms is generally delayed pending conversion to cyanide. Nausea, Vomiting, Diarrhea, Headache, Dizziness, Rash, Cyanosis, Excitement, Depression, Drowsiness, Impaired judgment, Lack of coordination, Stupor, Death. Lungs - Lung edema - Based on human evidence. Harmful if swallowed. Harmful in contact with skin. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
------------------------------	--

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Wear a self contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus, rubber boots and thick rubber gloves.

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Use personal protective equipment as required. Avoid breathing vapors, mist, gas. Ensure adequate air ventilation. Evacuate unnecessary personnel. Eliminate all ignition sources if safe to do so. Provide adequate ventilation to minimize dust and/or vapor concentrations. Special attention should be given to low areas/pits where flammable vapors can accumulate.

6.1.2. For emergency responders

Protective equipment : For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Dike and contain spill. Disposal should be in accordance with applicable Federal, State and local regulations.

Methods for cleaning up : Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Lighting equipment equipment.

Storage conditions : Store at room temperature away from light and moisture.

Incompatible materials : Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	70 mg/m ³ The value in mg/m ³ is approximate.
OSHA PEL TWA [2]	40 ppm The value in mg/m ³ is approximate.
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	34 mg/m ³ Forms Cyanide in the body.
NIOSH REL TWA [ppm]	20 ppm Forms Cyanide in the body.
MUSK XYLENE (TERT-BUTYL-D9, 98%) (81-15-2 (Unlabeled))	
No additional information available	
ACETONITRILE UNLABELED (75-05-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	70 mg/m ³ The value in mg/m ³ is approximate.
OSHA PEL TWA [2]	40 ppm The value in mg/m ³ is approximate.
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	34 mg/m ³ Forms Cyanide in the body.
NIOSH REL TWA [ppm]	20 ppm Forms Cyanide in the body.
8.2. Appropriate engineering controls	
Environmental exposure controls	: Avoid release to the environment.
8.3. Individual protection measures/Personal protective equipment	
Personal protective equipment: Gloves. Safety glasses. Protective clothing. Self-contained breathing apparatus.	
Materials for protective clothing:	
Wear suitable protective clothing and gloves	
Hand protection:	
Wear suitable protective clothing and gloves	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid, clear.
Color	: Colorless
Odor	: ether-like
Odor threshold	: No data available
pH	: No data available
Melting point	: -48 °C (-54°F)
Freezing point	: No data available
Boiling point	: 81 – 82 °C (178 - 180 °F)
Flash point	: 2 °C (35.6 °F) - closed cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor.
Vapor pressure	: 73.18 hPa (54.89 mmHg) at 15°C (59 °F), 119.81 hPa (89.86 mmHg) at 25°C(77 °F)
Relative vapor density at 20°C	: 1.42 - (Air = 1.0)
Relative density	: No data available
Density	: 0.786 g/ml
Molecular mass	: 41.05 g/mol
Solubility	: Water: 100 %
Partition coefficient n-octanol/water (Log Pow)	: -0.34
Auto-ignition temperature	: 523 °C (973 °F)
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: 4.4 – 16 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

See storage and expiration date on CoA.

10.3. Possibility of hazardous reactions

Highly flammable liquid and vapor.

10.4. Conditions to avoid

Heat. Open flame. Direct sunlight. Sparks. Extremely high or low temperatures.

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Acids, Bases, Oxidizing agents, Reducing agents, Alkali metals.

10.6. Hazardous decomposition products

May release flammable gases. Carbon oxides (CO, CO₂). Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Harmful if inhaled.

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	≥ 26.8 mg/l
LC50 Inhalation - Rat [ppm]	7551 ppm - 8h
ATE US (oral)	500.065 mg/kg body weight
ATE US (dermal)	2000 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

MUSK XYLENE (TERT-BUTYL-D9, 98%) (81-15-2 (Unlabeled))

LD50 oral rat	> 10000 mg/kg
LD50 dermal rabbit	> 15000 mg/kg
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

ACETONITRILE UNLABELED (75-05-8)

LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	≥ 26.8 mg/l
LC50 Inhalation - Rat [ppm]	7551 ppm - 8h
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	2000 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACETONITRILE UNLABELED (75-05-8)

ATE US (dust, mist)	1.5 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

MUSK XYLENE (TERT-BUTYL-D9, 98%) (81-15-2 (Unlabeled))

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

MUSK XYLENE (TERT-BUTYL-D9, 98%) (81-15-2 (Unlabeled))

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Treat as cyanide poisoning. Always have on hand a cyanide first-aid kit, together with proper instructions. The onset of symptoms is generally delayed pending conversion to cyanide. Nausea, Vomiting, Diarrhea, Headache, Dizziness, Rash, Cyanosis, Excitement, Depression, Drowsiness, Impaired judgment, Lack of coordination, Stupor, Death. Lungs - Lung edema - Based on human evidence. Harmful if swallowed. Harmful in contact with skin. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

LC50 - Fish [1]	1640 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 - Crustacea [1]	3600 mg/l Daphnia magna (Water flea) - 48h
NOEC (chronic)	640 mg/l Daphnia magna (Water flea) - 14d

ACETONITRILE UNLABELED (75-05-8)

LC50 - Fish [1]	1640 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 - Crustacea [1]	3600 mg/l Daphnia magna (Water flea) - 48h
NOEC (chronic)	640 mg/l Daphnia magna (Water flea) - 14d

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Persistence and degradability	Biodegradability	Result: - Readily biodegradable.
-------------------------------	------------------	----------------------------------

ACETONITRILE UNLABELED (75-05-8)

Persistence and degradability	Biodegradability	Result: - Readily biodegradable.
-------------------------------	------------------	----------------------------------

12.3. Bioaccumulative potential

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Partition coefficient n-octanol/water (Log Pow)	-0.34
---	-------

Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).
---------------------------	--

ACETONITRILE UNLABELED (75-05-8)

Partition coefficient n-octanol/water (Log Pow)	-0.34
---	-------

Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).
---------------------------	--

12.4. Mobility in soil

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Ecology - soil	Not expected to absorb on soil.
----------------	---------------------------------

ACETONITRILE UNLABELED (75-05-8)

Ecology - soil	Not expected to absorb on soil.
----------------	---------------------------------

12.5. Other adverse effects

Other adverse effects : Avoid release to the environment. Disposal must be done according to official regulations. May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.

Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No	: UN1648
UN-No. (TDG)	: UN1648
UN-No. (IMDG)	: 1648
UN-No. (IATA)	: 1648

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Acetonitrile
Proper Shipping Name (TDG) : ACETONITRILE
Proper Shipping Name (IMDG) : ACETONITRILE
Proper Shipping Name (IATA) : Acetonitrile

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3
Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : 3
Hazard labels (TDG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1648

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
TDG	
UN-No. (TDG)	: UN1648
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L
Emergency Response Guide (ERG) Number	: 127
IMDG	
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP2
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Flash point (IMDG)	: 2°C c.c.
Properties and observations (IMDG)	: Colourless, volatile liquid. Flashpoint: 2°C c.c. Explosive limits: 3% to 16% Miscible with water. When involved in a fire, evolves toxic cyanide fumes. Harmful if swallowed, by skin contact or by inhalation.
MFAG-No	: 127
IATA	
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ERG code (IATA)

: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

CERCLA RQ	5000 lb
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
MUSK XYLENE (TERT-BUTYL-D9, 98%)	81-15-2 (Unlabeled)	Not present	-	
ACETONITRILE UNLABELED	75-05-8	Present	Active	

MUSK XYLENE (TERT-BUTYL-D9, 98%) (81-15-2 (Unlabeled))

SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard

ACETONITRILE UNLABELED (75-05-8)

Subject to reporting requirements of United States SARA Section 313
Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	5000 lb
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

ACETONITRILE UNLABELED (75-05-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

ACETONITRILE UNLABELED (75-05-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

MUSK XYLENE (TERT-BUTYL-D9, 98%) 100 UG/ML IN ACETONITRILE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

Component	State or local regulations
ACETONITRILE UNLABELED(75-05-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 07/31/2023

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of H-phrases	
H201	Explosive; mass explosion hazard
H225	Highly flammable liquid and vapor
H228	Flammable solid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.