



EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/¹³C₁₂, 99%) IN ISOCTANE:NONANE

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 26/01/2016

Revision date:

:

Version: 1.0

EC-5385-CS5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name. : EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/¹³C₁₂, 99%) IN ISOCTANE:NONANE
Product code : EC-5385-CS5

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11
Xn; R20
Xn; R65
Xi; R38
N; R51/53

Full text of R-phrases: see section 16

Classification (GHS-US)

Flam. Liq. 2	H225
Acute Tox. 4 (Inhalation)	H332
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Acute 2	H401

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Chronic 2

H411

Adverse physicochemical, human health and environmental effects

Kidney, Liver, Central nervous system.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: N-NONANE UNLABELED

Hazard statements (CLP)

: H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P261 - Avoid breathing fume, mist, spray, vapors
P264 - Wash both hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing fume, mist, spray, vapors
P264 - Wash Both hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)
P331 - If swallowed, do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use Alcohol resistant foam., Carbon dioxide., Dry chemical., Water spray for extinction
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to Comply with applicable regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	95.1734477	R10 Xn; R20 Xn; R65 R67 Xi; R38
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC no) 208-759-1 (EC index no) 601-009-00-8	4.8260416	Xi; R38 N; R50/53 R67 F; R11
2,2',5,5'-TETRACB UNLABELED	(CAS No) 35693-99-3 (EC index no) 602-039-00-4	0.0000698	Xn; R22 N; R50/53
2,4,4'-TRICB UNLABELED	(CAS No) 7012-37-5 (EC no) 230-293-2	0.0000698	Xi; R36/37/38 N; R50/53
2,2',4,5,5'-PENTACB UNLABELED	(CAS No) 37680-73-2	0.0000698	R33
2,2',3,4,4',5'-HEXACB UNLABELED	(CAS No) 35065-28-2	0.0000698	N; R50/53 R33
2,2',3,4,4',5,5'-HEPTACB UNLABELED	(CAS No) 35065-29-3	0.0000698	R33
2,2',4,4',5,5'-HEXACB UNLABELED	(CAS No) 35065-27-1 (EC no) 215-648-1	0.0000698	R33
2,2',5,5'-TETRACB (PCB-52) (13C12, 99%)	(CAS No) 208263-80-3 (EC index no) 602-039-00-4	0.0000139	Carc.Cat.1; R45 N; R51/53 Xn; R48/20/21/22
2,4,4'-TRICB (PCB-28) (13C12, 99%)	(CAS No) 208263-76-7 (EC no) 230-293-2 (EC index no) 602-039-00-4	0.0000139	Xn; R20/21/22 N; R50/53 R48
2,2',3,4,4',5,5'-HEPTACB (PCB-180) (13C12, 99%)	(CAS No) 35065-29-3 (Unlabeled)	0.0000139	N; R50/53
2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%)	(CAS No) 208263-66-5 (EC index no) 602-039-00-4	0.0000139	Xn; R48/20/21/22 N; R50/53 R33
2,2',4,4',5,5'-HEXACB (PCB-153) (13C12, 99%)	(CAS No) 185376-58-3 (EC index no) 602-039-00-4	0.0000139	N; R50/53 R33 R48
2,2',4,5,5'-PENTACB (PCB-101) (13C12, 99%)	(CAS No) 104130-39-4 (EC index no) 602-039-00-4	0.0000139	Xn; R48/20/21/22 N; R50/53 R33

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Directive 67/548/EEC
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%)	(CAS No) 33025-41-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%)	(CAS No) 39635-33-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
2,3',4',5-TETRACB (PCB-70) (13C12, 99%)	(CAS No) 208263-81-4 (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
2,3,3',5,5'-PENTACB (PCB-111) (13C12, 99%)	(CAS No) 235416-29-2 (EC index no) 602-039-00-4	0.0000014	Xn; R48/20/21/22 N; R50/53 R33
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%)	(CAS No) 39635-35-3 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33 R48
2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%)	(CAS No) 35065-30-6 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	N; R50/53 R33

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS No) 111-84-2 (EC no) 203-913-4	95.1734477	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC no) 208-759-1 (EC index no) 601-009-00-8	4.8260416	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',5,5'-TETRACB UNLABELED	(CAS No) 35693-99-3 (EC index no) 602-039-00-4	0.0000698	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,4,4'-TRICB UNLABELED	(CAS No) 7012-37-5 (EC no) 230-293-2	0.0000698	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,5,5'-PENTACB UNLABELED	(CAS No) 37680-73-2	0.0000698	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5'-HEXACB UNLABELED	(CAS No) 35065-28-2	0.0000698	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5,5'-HEPTACB UNLABELED	(CAS No) 35065-29-3	0.0000698	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,4',5,5'-HEXACB UNLABELED	(CAS No) 35065-27-1 (EC no) 215-648-1	0.0000698	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',5,5'-TETRACB (PCB-52) (13C12, 99%)	(CAS No) 208263-80-3 (EC index no) 602-039-00-4	0.0000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,4,4'-TRICB (PCB-28) (13C12, 99%)	(CAS No) 208263-76-7 (EC no) 230-293-2 (EC index no) 602-039-00-4	0.0000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5,5'-HEPTACB (PCB-180) (13C12, 99%)	(CAS No) 35065-29-3 (Unlabeled)	0.0000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%)	(CAS No) 208263-66-5 (EC index no) 602-039-00-4	0.0000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,4',5,5'-HEXACB (PCB-153) (13C12, 99%)	(CAS No) 185376-58-3 (EC index no) 602-039-00-4	0.0000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',4,5,5'-PENTACB (PCB-101) (13C12, 99%)	(CAS No) 104130-39-4 (EC index no) 602-039-00-4	0.0000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,3,4,4'-TETRACB (PCB-60) (13C12, 99%)	(CAS No) 33025-41-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3,3',4,5,5'-PENTACB (PCB-127) (13C12, 99%)	(CAS No) 39635-33-1 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3',4',5-TETRACB (PCB-70) (13C12, 99%)	(CAS No) 208263-81-4 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',5,5'-PENTACB (PCB-111) (13C12, 99%)	(CAS No) 235416-29-2 (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,3',4,5,5'-HEXACB (PCB-159) (13C12, 99%)	(CAS No) 39635-35-3 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%)	(CAS No) 35065-30-6 (Unlabeled) (EC index no) 602-039-00-4	0.0000014	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	Classification (GHS-US)
N-NONANE UNLABELED	(CAS No) 111-84-2	95.1734477	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304
ISOOCTANE UNLABELED	(CAS No) 540-84-1	4.8260416	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible). Consult a doctor/medical service.
First-aid measures after inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of soap and water. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness or dizziness. Harmful if swallowed or if inhaled.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

suitable extinguishing media : Alcohol resistant foam. Dry chemical. Carbon dioxide. Water spray. Sand.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Vapor is explosive with air above.

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Ensure adequate ventilation. Evacuate unnecessary personnel. Evacuate danger area. Special attention should be given to low areas/pits where flammable vapors can accumulate. Use personal protective equipment as required.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
Hygiene measures : Always wash your hands immediately after handling this product, and once again before leaving the workplace. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions : Store at room temperature away from light and moisture.
Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2,2',5,5'-TETRACB (PCB-52) (13C12, 99%) (208263-80-3)		
USA OSHA	OSHA PEL (TWA) (mg/m3)	0.5000000000 mg/m ³
2,2',5,5'-TETRACB UNLABELED (35693-99-3)		
USA OSHA	OSHA PEL (TWA) (mg/m3)	0.5000000000 mg/m ³
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.0000000000 ppm Central Nervous System impairment.

8.2. Exposure controls

- Personal protective equipment : Gloves. Safety glasses. Respiratory protection of the dependent type. Protective clothing.



EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection	: Wear suitable protective clothing and gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 128.3 g/mol
Color	: Colorless.
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31.0 °C (87.8 °F) - closed cup
Self ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.718 g/ml
Solubility	: Water: 0 %
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 0.87 - 2.9 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapor is explosive with air above.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Direct sunlight.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

May release flammable gases.

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE	
ATE (vapors)	11.000 mg/l/4h

N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h
LC50 inhalation rat (ppm)	3200 ppm/4h
ATE (gases)	3200.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
ATE (dust, mist)	23.760 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
No data available

Serious eye damage/irritation : Causes serious eye irritation.
No data available

Respiratory or skin sensitization : Not available
No data available

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not available

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified
No data available

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential Adverse human health effects and symptoms : Harmful if inhaled.

Symptoms/injuries after inhalation : Harmful if inhaled. May cause drowsiness or dizziness. Harmful if swallowed or if inhaled.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life with long lasting effects.

2,2',5,5'-TETRACB (PCB-52) (13C12, 99%) (208263-80-3)	
LC50 fish 1	>= 0.002 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	>= 0.002 mg/l Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

2,2',5,5'-TETRACB UNLABELED (35693-99-3)	
LC50 fish 1	Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

2,4,4'-TRICB (PCB-28) (13C12, 99%) (208263-76-7)	
LC50 fish 1	> 0.16 mg/l Pimephale promelas (fathead minnow) -96h
EC50 Daphnia 1	> 0.16 mg/l Daphnia magna (Water flea) -48h

2,4,4'-TRICB UNLABELED (7012-37-5)	
LC50 fish 1	> 0.16 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 Daphnia 1	> 0.16 mg/l Daphnia magna (Water flea) - 48h

2,2',4,4',5,5'-HEXACB UNLABELED (35065-27-1)	
LC50 fish 1	Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	Daphnia magna (Water flea) - 48 h

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,2',4,4',5,5'-HEXACB (PCB-153) (13C12, 99%) (185376-58-3)	
LC50 fish 1	Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	Daphnia magna (Water flea) - 48 h

2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%) (35065-30-6 (Unlabeled))	
LC50 fish 1	0.034 mg/l Pimephales promelas (fathead minnow) - 96 h

12.2. Persistence and degradability

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE	
Log Pow	5.65

2,2',3,4,4',5,5'-HEPTACB (PCB-180) (13C12, 99%) (35065-29-3 (Unlabeled))	
Log Pow	8.27

2,2',4,4',5,5'-HEXACB (PCB-153) (13C12, 99%) (185376-58-3)	
Log Pow	7.75

N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

2,2',3,3',4,4',5-HEPTACB (PCB-170) (13C12, 99%) (35065-30-6 (Unlabeled))	
Log Pow	8.27

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.

SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

UN-No.(DOT) : 1920
DOT NA no. UN1920

14.2. UN proper shipping name

DOT Proper Shipping Name : Nonanes
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
Marine pollutant	: No



14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR)	: III
Class (ADR)	: 3 - Flammable liquid
Hazard identification number (Kemler No.)	: 30
Classification code (ADR)	: F1
Danger labels (ADR)	: 3 - Flammable liquids



Orange plates :

Tunnel restriction code	: D/E
Limited quantities (ADR)	: 5L
EAC	: 3Y
Excepted quantities (ADR)	: E1

Transport by sea

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No	: 128

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.4. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
-------------------------------------	--

N-NONANE UNLABELED (111-84-2)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
-------------------------------------	--

ISOOCTANE UNLABELED (540-84-1)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

15.2. International regulations

CANADA

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.2.1. National regulations

No additional information available

15.3. US State regulations

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE()

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.
----------------------------	---

N-NONANE UNLABELED (111-84-2)

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

ISOOCTANE UNLABELED (540-84-1)

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
R10	Flammable
R11	Highly flammable
R20	Harmful by inhalation
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed
R22	Harmful if swallowed
R33	Danger of cumulative effects
R36/37/38	Irritating to eyes, respiratory system and skin
R38	Irritating to skin
R45	May cause cancer
R48	Danger of serious damage to health by prolonged exposure
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

EN-1948-4 MARKER PCB CALIBRATION SERIES CS5 (UNLABELED/13C12, 99%) IN ISOCTANE:NONANE EC-5385-CS5

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product