

SAFETY DATA SHEET

Version 5.4 Revision Date 10/14/2015 Print Date 10/14/2015

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : 1.2.3.7.8.9-HXBDD-13C12

Product Number : ED-5238-A-1.2 Brand : Cerilliant

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich

3050 Spruce Street

SAINT LOUIS MO 63103

USA

Telephone : +1 800-325-5832 Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226

Skin irritation (Category 2), H315 Reproductive toxicity (Category 2), H361

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Specific target organ toxicity - repeated exposure (Category 2), H373

Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Cerilliant - ED-5238-A-1.2 Page 1 of 9

Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and
	understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/
	physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Book Boko Boko	Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for
	breathing. Call a POISON CENTER or doctor/ physician if you feel
B000 B040	unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.
	-, and

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Component		Classification	Concentration
Nonane			
CAS-No. EC-No.	111-84-2 203-913-4	Flam. Liq. 3; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Acute 1; Aquatic Chronic 1; H226, H304, H315, H336, H410	>= 70 - < 90 %
Toluene			
CAS-No.	108-88-3	Flam. Liq. 2; Skin Irrit. 2; Repr.	>= 30 - < 50 %
EC-No.	203-625-9	2; STOT SE 3; STOT RE 2;	
Index-No.	601-021-00-3	Asp. Tox. 1; Aquatic Acute 2;	
	01-2119471310-51-XXXX	H225, H304, H315, H336, H361, H373, H401	

For the full text of the H-Statements mentioned in this Section, see Section 16.

Cerilliant - ED-5238-A-1.2 Page 2 of 9

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

Cerilliant - ED-5238-A-1.2 Page 3 of 9

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis		
			parameters			
Nonane	111-84-2	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	Remarks	Central Nervous System impairment				
		TWA	200.000000	USA. NIOSH Recommended		
			ppm 1,050.000000 mg/m3	Exposure Limits		
		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Central Ne	Central Nervous System impairment			
		TWA	200 ppm	USA. NIOSH Recommended		
			1,050 mg/m3	Exposure Limits		
		TWA	200 ppm	USA. OSHA - TABLE Z-1 Limits for		
			1,050 mg/m3	Air Contaminants - 1910.1000		
Toluene	108-88-3	TWA	100 ppm	USA. OSHA - TABLE Z-1 Limits for		
			375 mg/m3	Air Contaminants - 1910.1000		
		STEL	150 ppm	USA. OSHA - TABLE Z-1 Limits for		
			560 mg/m3	Air Contaminants - 1910.1000		
		TWA	200 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
		Z37.12-196	67			
		CEIL	300 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
		Z37.12-1967				
		Peak	500 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
		Z37.12-1967				
		TWA	20 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Visual impa	airment	,		
		Female reproductive Pregnancy loss				
		2015 Adoption				
		Substances for which there is a Biological Exposure Index or Indices (see BEI® section)				
			able as a human c	arcinogen		
		TWA	100 ppm 375 mg/m3	USA. NIOSH Recommended Exposure Limits		
		ST	150 ppm 560 mg/m3	USA. NIOSH Recommended Exposure Limits		

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Toluene	108-88-3	Toluene	0.0200	In blood	ACGIH - Biological

		mg/l		Exposure Indices (BEI)	
Remarks	Prior to last	Prior to last shift of workweek			
	Toluene	0.0300 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)	
	End of shift (As soon as possible after exposure ceases)				
	o-Cresol	0.3000 mg/g	Urine	ACGIH - Biological Exposure Indices (BEI)	
	End of shift (As soon as possible after exposure ceases)				

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

b) Odour
c) Odour Threshold
d) pH
e) Melting point/freezing
No data available
No data available
No data available

point

NO data available

f) Initial boiling point and

150.0 - 151.0 °C (302.0 - 303.8 °F) at 1,013.3 hPa (760.0 mmHg)

boiling range

g) Flash point 31.0 °C (87.8 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, gas) No data availablej) Upper/lower No data available

flammability or

Cerilliant - ED-5238-A-1.2 Page 5 of 9

explosive limits

k) Vapour pressure No data available Vapour density No data available m) Relative density No data available No data available n) Water solubility Partition coefficient: n-No data available

octanol/water

p) Auto-ignition temperature

No data available

Decomposition temperature

No data available

Viscosity No data available r) Explosive properties No data available Oxidizing properties No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions 10.3

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Cerilliant - ED-5238-A-1.2 Page 6 of 9

Carcinogenicity

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence (Toluene)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1993 Class: 3 Packing group: III

Proper shipping name: Flammable liquids, n.o.s. (Nonane)

Cerilliant - ED-5238-A-1.2 Page 7 of 9

Reportable Quantity (RQ): 3333 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 1993 Class: 3 Packing group: III EMS-No: F-E, S-E

Proper shipping name: FLAMMABLE LIQUID, N.O.S. (Nonane)

Marine pollutant:yes

IATA

Toluene

UN number: 1993 Class: 3 Packing group: III

Proper shipping name: Flammable liquid, n.o.s. (Nonane)

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date 108-88-3 2007-07-01

~ . ~ . .

~ ~ ~ ~ . .

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
Nonane	111-84-2	1994-04-01
Toluene	108-88-3	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Nonane	111-84-2	1994-04-01
Toluene	108-88-3	2007-07-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Nonane	111-84-2	1994-04-01
Toluene	108-88-3	2007-07-01

California Prop. 65 Components

WARNING: This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause birth defects or other reproductive	108-88-3	2009-02-01

harm. Toluene

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity
Asp. Tox.
Flam. Liq.

Acute aquatic toxicity
Chronic aquatic toxicity
Aspiration hazard
Flammable liquids

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Cerilliant - ED-5238-A-1.2 Page 8 of 9

H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Repr. Reproductive toxicity

Skin Irrit. Skin irritation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

Further information

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.4 Revision Date: 10/14/2015 Print Date: 10/14/2015

Cerilliant - ED-5238-A-1.2 Page 9 of 9