

2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE UNLABELED CERTIFIED STANDARD

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 30/04/2018 Revision date: : Version: 1.0 PCB-64-CS

	ion of the substance/mixture and of the company/undertaking
1.1. Product identifier	. Misturee
Product form	: Mixtures
Product name	: 2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE UNLABELED CERTIFIED STANDARD : PCB-64-CS
Product code	
1.2. Relevant identified	uses of the substance or mixture and uses advised against
1.2.1. Relevant identified	uses
Main use category	: Professional use
Industrial/Professional use spe	ec : For professional use only
1.2.2. Uses advised agair	nst
No additional information avail	
	lier of the safety data sheet
Cambridge Isotope Laboratorie 50 Frontage Road Andover, MA 01810 USA	es, inc.
USA: 1-800-322-1174 Int: 1 cilsales@isotope.com www.	-978-749-8000 .isotope.com
Emergency telepho	one number
Emergency numbers:	
Chemtrec: 1-800-424-9300 (2 International: 1-703-741-5970	
SECTION 2: Hazards id	dentification
2.1. Classification of th	e substance or mixture
Classification according to F	Regulation (EC) No. 1272/2008 [CLP]
Flam. Liq. 2 H225	
Skin Irrit. 2 H315	
STOT SE 3 H336	
Asp. Tox. 1 H304	
Aquatic Acute 1 H400	
Aquatic Chronic 1 H410	
	H-statements : see section 16
Classification according to I	Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]
Xi; R38 N; R50/53 R67 F; R11	
Xn; R65	
Full text of R-phrases: see sec	xtion 16
GHS-US classification	
Flam. Liq. 2 H225 Skin Irrit. 2 H315 STOT SE 3 H336 Asp. Tox. 1 H304	

Aquatic Acute 1 H400

Aquatic Chronic 1 H410

Full text of H statements : see section 16

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Liver, Kidney. Highly flammable liquid and vapor. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.



CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P391 - Collect spillage P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container to hazardous or special waste collection p

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

- Not applicable
- 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC No) 208-759-1 (EC Index No) 601-009-00-8 (REACH-no) 01-2119457965-22	99.98	Xi; R38 N; R50/53 R67 F; R11 Xn; R65
2,3,4',6-TETRACB UNLABELED		0.02	Not classified
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC No) 208-759-1 (EC Index No) 601-009-00-8 (REACH-no) 01-2119457965-22	99.98	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4',6-TETRACB UNLABELED		0.02	Not classified
Name	Product identifier	%	GHS-US classification
ISOOCTANE UNLABELED	(CAS No) 540-84-1	99.98	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,3,4',6-TETRACB UNLABELED		0.02	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: If medical advice is needed, have product container or label at hand. Call a physician immediately. Evacuate danger area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Call a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Take immediately victim to hospital. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, i present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention
First-aid measures after ingestion	: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth Call a physician immediately.
4.2. Most important symptoms and effe	ects, both acute and delayed
Symptoms/injuries	: May cause drowsiness or dizziness.
Symptoms/injuries after inhalation	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May be harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: May cause eye irritation.

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion

May be fatal if swallowed and enters ainwaye. May result in aspiration into the lunge, causing

Symptoms/injuries after ingestion	:	May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing
		chemical pneumonia. Risk of lung edema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Flood fire area with water from a distance. Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Special hazards arising from the s	
Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: Flash back possible over important distance.
Reactivity	: vapors may form flammable mixture with air. Highly flammable liquid and vapor.
5.3. Advice for firefighters	
Firefighting instructions	: Wear a self contained breathing apparatus.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Use water spray to cool exposed surfaces.
SECTION 6: Accidental release mea	asures
6.1. Personal precautions, protective e	equipment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Use personal protective equipment as required. Remove all sources of ignition. Ensure adequate air ventilation. Provide adequate ventilation to minimize dust and/or vapor concentrations. No open flames, no sparks, and no smoking. Avoid breathing gas, mist, vapors. Avoid contact with skin and eyes. Evacuate danger area. Special attention should be given to low areas/pits where flammable vapors can accumulate.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Stop leak, if possible without risk. Prevent entry	y to sewers and public waters. Avoid release to the environment.
6.3. Methods and material for containn	nent and cleaning up
For containment	: Vacuum with an equipment that avoids ignition risk. This material and its container must be disposed of in a safe way, and as per local legislation. Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	
For further information refer to section 13.	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Avoid all contact with skin, eyes, or clothing.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, mist. Avoid contact with skin and eyes.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, include	ling any incompatibilities
Technical measures	: Keep dry. Store in tightly closed, leak-proof containers. Containers which are opened should be properly resealed and kept upright to prevent leakage. Ground/bond container and receiving equipment.
Storage conditions	: Store at room temperature away from light and moisture.
20/04/2018	EN (Essilab LIC) 4/40

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

No additional information available

SECTION 8: Exposure controls/personal protection		
8.1. Control parameters		
2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE UNLABELED CERTIFIED STANDARD		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	300.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract irritation
ISOOCTANE UNLABELED (540-84-1)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	300.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract irritation

8.2. Exposure controls

Appropriate engineering controls

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Ensure good ventilation of the work station.

Personal protective equipment

: Gloves. Protective clothing. Protective goggles. Self-contained breathing apparatus.



Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: Wear suitable protective clothing and gloves.
Eye protection	: Wear eye protection. Chemical goggles or face shield with safety glasses. Safety glasses.
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
The properties listed below are for the solvent, the main compo	nent of this mixture.
Physical state	: Liquid
Appearance	: Liquid.
Color	: Colourless.
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -107 °C (-161 °F)
Freezing point	: No data available
Boiling point	: 98 - 99 °C (208 - 210 °F) at 1,013 hPa (760 mmHg)
Flash point	: -12 °C (10 °F) - closed cup
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 55 hPa (41 mmHg) at 21 °C (70 °F); 117 hPa (88 mmHg) at 37.8 °C (100.04 °F)
Relative vapor density at 20 °C	: 3.94 - (Air = 1.0)
Relative density	: No data available
Specific gravity / density	: 0.69 g/ml at 20 °C (68 °F)
Solubility	: Water: insoluble
Log Pow	: 4.6
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

26, 2012 / Rules and Regulations	
Oxidizing properties	: No data available
Explosion limits	: 1 - 6 % (V)
9.2. Other information	
No additional information available	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Vapors may form flammable mixture with air. High	nly flammable liquid and vapor.
10.2. Chemical stability	
See storage and expiration date on CoA.	
10.3. Possibility of hazardous reactions	
Vapors may form explosive mixture with air.	
10.4. Conditions to avoid	
Avoid contact with hot surfaces. Heat. No flames,	no sparks. Eliminate all sources of ignition
10.5. Incompatible materials	
Strong oxidizing agents.	
10.6. Hazardous decomposition products	
Carbon oxides (CO, CO2).	
SECTION 11: Toxicological informati	on
11.1. Information on toxicological effects	
Acute toxicity	: Not classified
2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE	UNLABELED CERTIFIED STANDARD
LD50 oral rat	> 5000 mg/kg (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	> 33.52 mg/l/4h (OECD Test Guideline 403)
ISOOCTANE UNLABELED (540-84-1)	
LD50 oral rat	> 5000 mg/kg (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	> 33.52 mg/l/4h (OECD Test Guideline 403)
Skin corrosion/irritation	: Skin. rabbit. Result: Irritating to skin. (OECD 404 method)
Serious eye damage/irritation	: Eyes. rabbit. Result: No eye irritation. (OECD 405 method)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: rat - Unscheduled DNA synthesis
Carcinogenicity	: Not classified
Reproductive toxicity	: Not available
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness
Specific target organ toxicity – repeated exposure	: Health hazard - Aspiration hazard
	No data available
Aspiration hazard	: Aspiration hazard
Potential Adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Affects the liver.
Symptoms/injuries after inhalation	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May be harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: May cause eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing
	chemical pneumonia. Risk of lung edema.

SECTI	SECTION 12: Ecological information		
12.1.	Toxicity		
No additional information available			

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE	UNLABELED CERTIFIED STANDARD
Log Pow	4.6
ISOOCTANE UNLABELED (540-84-1)	
Log Pow	4.6
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessmen	t
No additional information available	
12.6. Other adverse effects	
Other adverse effects	: Very toxic to aquatic life with long lasting effects. Avoid release to the environment. Disposal must be done according to official regulations.
SECTION 13: Disposal considerations	S
13.1. Waste treatment methods	
	: Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
	: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials	: Dispose of as unused product.
SECTION 14: Transport information	
In accordance with ADR / RID / IMDG / IATA / AD	Ν
14.1. UN number	
UN-No.(DOT)	: 1262
DOT NA no.	UN1262
14.2. UN proper shipping name	
Proper Shipping Name (DOT)	: Octanes
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal
	: 150
	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT RQ	: 1000 lbs : No
Marine pollutant	

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency Response Guide (ERG) Number : 128 Other information : No supplementary information available. Overland transport Packing group (ADR) : 1 Gloss (ADR) : 3 Gloss (ADR) : 3 Gloss (ADR) : 3 Glossification code (ADR) : 3 Glossification			
Other information : No supplementary information available. Overland transport :: I Packing group (ADR) :: I Class (ADR) :: I Hazard identification number (Kemier No.) ::: 33 Classification code (ADR) ::: FI Hazard identification number (Kemier No.) ::: 33 Orange plates ::: 33 Orange plates ::: 33 Tunnel restriction code (ADR) ::: DE Tunnel restriction code (ADR) ::: DE Tunnel restriction code (ADR) ::: DE DOT vessel Stowage Location ::: E2 Tansport by see DD DOT Vessel Stowage Location ::: E3 MFAG-No ::: 128 Mart transport ::: 00 L Ord Approximations Passengers or and 3 m of overlaw vessel length; and (in) 0.:: 0.: 0.:: 0.: 0.: 0.: 0.: 0.: 0.: 0	14.3. Additional information	• 100	
Overland transport Packing group (ADR) I Class (ADR) 3 - Flammable liquid Hazard identification number (Kemler No.) 3 3 Classification code (ADR) Fl Hazard identification code (ADR) 9 - Flammable liquids Orange plates 33 Innel restriction code (ADR) 10 EAC 33 Innel restriction code (ADR) 10 EAC 34 Excepted quantities (ADR) 11 EAC 34 Excepted quantities (ADR) 12 DOT Vessel Stowage Location B - (i) The material may be stowed 'on deck' or "under deck' on a cargo vessel and on a sassenger vessel carrying a number of passenger similate to not more fram the larger of 25 passengers, or one passenger seesil material may be stowed 'on deck' or "under deck' on a cargo vessel and on a second is exceeded. MFAG-No 1 28 Air transport 5 L DOT Quantity Limitations Passenger aircraft/rail 5 L Qi GV T172:70 6 0 L Crit 175:73 Flammable liquids 14.1 Environment Elemmable liquids 14.2 Environment F on L Crit 175:73 <td< td=""><td></td><td></td></td<>			
Packing group (ADR) : 1 Class (ADR) : 3 - Flammable liquid Hazard (definitionion number (Kemler No.) : 3 Classification code (ADR) : FI Hazard dabels (ADR) : 3 - Flammable liquids Orange plates : 33 12622 Tunnel restriction code (ADR) : DE Limited quantities (ADR) : DE Limited quantities (ADR) : DE Transport by sea DOT Vessel Stowage Location : B - (I) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel arrying a number of passengers limited to nor more than the larger of 25 passenger vessel in which the number of passengers limited to nor a cargo vessel and on a passenger vessel in which the number of passengers limited to nor a cargo vessel and on a passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passengers limited to nor dock only" or passenger vessel in which the number of passenger specified in paragraph (k)(2)() of this to Cluarity Limitations Passenger aircraft/rial is 5 L 40 Crantry Limitations Cargo aircraft only (4) is 60 L Crant r5.72.72 DOT Quanty Limitations Cargo aircraft only (4) is 60 L Crant r5.73.72 DOT Quanty Limitations for user 14.5 Special precautions for user 14.5 Special precautions for user 14.5 Special precautions for user 14.5 Special precautions for user 14.5 Transport in bulk according to Annex II of MARPOL T3/78 and the IBC Code Not applicable ESECTION 15: Regulatory information 15.1.US Federal regulations	Other information	: No supplementary information available.	
Class (ADR) : : : : : : : : : : : : : : : : : : :	Overland transport		
Hazard identification number (Kemler No.) i S Classification code (ADR) i F I Hazard labels (ADR) i S I I I I I I I I I I I I I I I I I I I			
Classification code (ADR) : F1 Hazard labels (ADR) : S 7 Fianmable liquids Orange plates : 3 7 Fianmable liquids Orange plates : 3 7 Fianmable liquids DTUnel restriction code (ADR) : DTE Limited quantities (ADR) : DTE Limited quantities (ADR) : DTE Limited quantities (ADR) : E Excepted quantities (ADR) : E Excepted quantities (ADR) : E DT vessel glowage Location : E DT Vessel Stowage Location : E DT Vessel Stowage Location : E B - (1) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel is number of passengers initiated not more than the larger of 25 passengers on one passenger per each 3 m of vorefail vessel length, and (ii) Cin deck confy" on passenger vessels in which the number of passengers initiated not more than the larger of 25 passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. MFAG-No : 128 Air transport DD CT Quantity Limitations Passenger aircraftvrail : S L DD CT Quantity Limitations Cargo aircraft only (#) : 60 L CFR 175.75) Civil Aeronautics Law : Flammable liquids 14.4. Environmental hazards Dangerous for the environment : Vosupplementary information available. 14.5. Special procautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information			
Hazard labels (ADR) : 3 - Flammable liquids with a second provide the provide			
Orange plates : 33 1262 Tunnel restriction code (ADR) : DE Limited quantities (ADR) : 1 EAC : 3YE Excepted quantities (ADR) : E2 Transport by sea : B - 0) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to on thora than the larger of 25 passenger vessel carrying a number of passengers limited to on thora than the larger of 25 passenger vessel is in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. MFAG-No : 128 DOT Quantity Limitations Passenger aircraft/rail : 5 L OT Quantity Limitations Cargo aircraft only (9) : 60 L CFR 175.70 : Flarmable liquids 14.1 Environmental hazards Dangerous for the environment : Ko supplementary information available. 14.5 Special precautions for user 14.5 Special precautions for user 14.5 Transport In bulk according to Annex II of MARPOL 7378 and the IBC Code Not applicable Section 15: Regulatory information			
33 1262 Tunnel restriction code (ADR) : Limited quantities (ADR) : EAC : EAC : Excepted quantities (ADR) : EXcepted quantities (ADR) : DT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger yeasel carrying a number of passenger isinited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel lendty; and (i) "On deck conly" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this is secton is exection is exected. MFAG-No : DOT Quantity Limitations Passenger aircraft/rail is 5 L DOT Quantity Limitations Cargo aircraft only (49 : 60 L CFR 175.75 Civil Aeronautics Law : Flammable liquids 14. Environmental hazards Dangerous for the environment : Vis applicable : Secial precautions for user : 14.5 Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable Secial precautions for user	Hazard labels (ADR)	: 3 - Flammable liquids	
33 1262 Tunnel restriction code (ADR) : Limited quantities (ADR) : EAC : EAC : Excepted quantities (ADR) : EXcepted quantities (ADR) : DT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger yeasel carrying a number of passenger isinited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel lendty; and (i) "On deck conly" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this is secton is exection is exected. MFAG-No : DOT Quantity Limitations Passenger aircraft/rail is 5 L DOT Quantity Limitations Cargo aircraft only (49 : 60 L CFR 175.75 Civil Aeronautics Law : Flammable liquids 14. Environmental hazards Dangerous for the environment : Vis applicable : Secial precautions for user : 14.5 Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable Secial precautions for user			
Tunnel restriction code (ADR) I Limited quantities (ADR) 11 EAC : 3YE Excepted quantities (ADR) : E2 Transport by sea Image: Comparison of the search of the material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length: and (ii) "On deck only" on passenger vessel in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. MFAG-No : 128 Air transport : 5 L DOT Quantity Limitations Passenger aircraft/rail : 5 L OT Quantity Limitations Cargo aircraft only (49) : 60 L CFR 175.75 : Flammable liquids It.4. Environmental hazards Dangerous for the environment : Vosupplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 7378 and the IBC Code Not applicable Section 15: Regulatory information Section 15: Regulatory information : No supplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 7378 and the IBC Code	Orange plates		
Limited quantities (ADR) 1 EAC : 3YE Excepted quantities (ADR) : E2 Transport by sea		1262	
Limited quantities (ADR) 1 EAC : 3YE Excepted quantities (ADR) : E2 Transport by sea	Tunnel restriction code (ADR)	: D/E	
Excepted quantities (ADR) : E2 Transport by sea B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessel carrying a number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. MFAG-No : 128 Air transport : 5 L QOT Quantity Limitations Passenger aircraft/rail : 5 L QOT Quantity Limitations Cargo aircraft only (49) : 60 L CFR 175.75 : Flammable liquids 14. Environmental hazards Dangerous for the environment : Vaspplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information	Limited quantities (ADR)	11	
Transport by sea DOT Vessel Stowage Location : B - (i) The material may be stowed 'on deck'' or 'under deck'' on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length; and (ii) 'On deck only' on passenger vessels in which the number of passengers is pecified in paragraph (k)(2)(i) of this section is exceeded. MFAG-No : 128 Air transport DOT Quantity Limitations Passenger aircraft/rail : 5 L DOT Quantity Limitations Passenger aircraft/rail : 60 L : 60 L CFR 175.75) : Flammable liquids : 60 L 14.4 Environmental hazards : Flammable liquids Dangerous for the environment : work of the onvironment : work of the information 14.5 Special precautions for user : No supplementary information available. 14.5. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable : SECTION 15: Regulatory information	EAC	: 3YE	
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger, vessel carrying a number of passengers limited to not more than the larger of 25 passenger, or one passenger per each 3 m of overall vessel length, and (ii) "On deck only" on passenger, or one passenger per each 3 m of overall vessel length, and (ii) "On deck only" on passenger, or one passenger, or one passenger, specified in paragraph (k)(2)(i) of this section is exceeded. MFAG-No : 128 Air transport : 5 L DOT Quantity Limitations Passenger aircraft/rail : 5 L : 60 L CFR 173.27) : 60 L DOT Quantity Limitations Cargo aircraft only (49) : Flammable liquids : 60 L CFR 175.75) : Flammable liquids 14.4. Environmental hazards : Dangerous for the environment : vos supplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information	Excepted quantities (ADR)	: E2	
passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. Air transport DOT Quantity Limitations Passenger aircraft/rail if 5 L Q9 CTR 175.27) DOT Quantity Limitations Cargo aircraft only (49 if 60 L CFR 175.75 Civil A eronautics Law I Hammable liquids 14.4. Environmental hazards Dangerous for the environment i Vos uspplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations	Transport by sea		
MFAG-No : 128 Air transport DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49) : 60 L CFR 175.75) Civil Aeronautics Law : Flammable liquids 14.4. Environmental hazards Dangerous for the environment : Flammable liquids 14.4. Environmental hazards Dangerous for the environment : Volume value liquids Cher information : No supplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex I of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations	DOT Vessel Stowage Location	passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this	
DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 60 L CFR 175.75) Civil Aeronautics Law : Flammable liquids 14.4. Environmental hazards Dangerous for the environment : Civil Aeronautics Law : Dangerous for the environment : Civil Aeronautics Law :	MFAG-No		
(49 CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 : 60 L CFR 175.75) Civil Aeronautics Law i Flammable liquids 14.4. Environmental hazards Dangerous for the environment :	Air transport		
CFR 175.75) Flammable liquids 14.4. Environmental hazards Dangerous for the environment :		: 5L	
14.4. Environmental hazards Dangerous for the environment Image: Special precautions for user 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations		: 60 L	
Dangerous for the environment : with a construction of the environment Other information : No supplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations	Civil Aeronautics Law	: Flammable liquids	
Other information : No supplementary information available. 14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations	14.4. Environmental hazards		
14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations	Dangerous for the environment		
14.5. Special precautions for user 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations			
14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations	Other information	 No supplementary information available. 	
Not applicable SECTION 15: Regulatory information 15.1. US Federal regulations	14.5. Special precautions for user		
SECTION 15: Regulatory information 15.1. US Federal regulations		x II of MARPOL 73/78 and the IBC Code	
15.1. US Federal regulations			
2.3.4'.6-TETRACB 100 UG/ML IN ISOOCTANE UNLABELED CERTIFIED STANDARD	15.1. US Federal regulations		
	2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE	UNLABELED CERTIFIED STANDARD	

3,4,0-TETRACB TO UG/ME IN ISOUCTANE UNLABELED CERTIFIED STANDARD		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporing requirements of the United States SARA Section 313.	
30/04/2018	EN (English US)	8/10

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ISOOCTANE UNLABELED (540-84-1)		
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporing requirements of the United States SARA Section 302.	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	Not subject to reporing requirements of the United States SARA Section 313.	

15.2. International regulations

CANADA

2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE UNLABELED CERTIFIED STANDARD

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

2,3,4',6-TETRACB 100 UG/ML IN ISOOCTANE UNLABELED CERTIFIED STANDARD	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List

ISOOCTANE UNLABELI	ED (540-84-1)			
U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	No significant risk level (NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male	
No	No	No	No	
2,3,4',6-TETRACB UNLA	BELED			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
ISOOCTANE UNLABELED (540-84-1)				
State or local regulation	IS			
U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List				
2,3,4',6-TETRACB UNLABELED				
State or local regulations				
U.S Pennsylvania - RTK (Right to Know) List U.S New Jersey - Right to Know Hazardous Substance List				

SECTION 16: Other information

Other information

: This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

CERTIFIED STANDARD PCB-64-CS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

I text of R-, H- and EU	H-phrases:	
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1	
Asp. Tox. 1	Aspiration hazard Category 1	
Flam. Liq. 2	Flammable liquids Category 2	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H225	Highly flammable liquid and vapor	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	
H336	May cause drowsiness or dizziness	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
R11	Highly flammable	
R38	Irritating to skin	
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment	
R65	Harmful: may cause lung damage if swallowed	
R67	Vapors may cause drowsiness and dizziness	
F	Highly flammable	
Ν	Dangerous for the environment	
Xi	Irritant	
Xn	Harmful	

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

0