



100% ETHYLENE GLYCOL UNLABELED

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/01/2011

Revision date: 30/08/2016

Supersedes: 02/04/2012

Version: 3.0

ULM-71

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Substance name : 100% ETHYLENE GLYCOL UNLABELED
EC index no : 603-027-00-1
EC no : 203-473-3
CAS No : 107-21-1
Product code : ULM-71
Formula : C₂H₆O₂
Synonyms : 1,2-Ethanediol
Other means of identification : Also applicable to:
ULM-71C

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Oral) H302
STOT RE 2 H373

Full text of H-statements: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R22
Carc.Cat.1; R45

Full text of R-phrases: see section 16

GHS-US classification

Acute Tox. 4 (Oral) H302
STOT RE 2 H373

Adverse physicochemical, human health and environmental effects

Liver, Cardiovascular system, Eyes, Kidney, Central nervous system.

100% ETHYLENE GLYCOL UNLABELED ULM-71

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Warning

Hazard statements (CLP) :


H302 - Harmful if swallowed
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed)

Precautionary statements (CLP) :

P260 - Do not breathe dust, fume, gas, mist, spray, vapours
P264 - Wash Both hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P301+P312 - IF SWALLOWED: Call a doctor if you feel unwell
P314 - Get medical advice/attention if you feel unwell
P330 - Rinse mouth
P501 - Dispose of contents/container to Dispose in a safe manner in accordance with local/national regulations

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H302 - Harmful if swallowed
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)

Precautionary statements (GHS-US) :

P260 - Do not breathe dust, fume, gas, mist, spray, vapours
P264 - Wash Both hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P301+P312 - IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell
P314 - Get medical advice and attention if you feel unwell
P330 - If swallowed, rinse mouth
P501 - Dispose of contents/container to Comply with applicable regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%	Classification according to Directive 67/548/EEC
100% ETHYLENE GLYCOL UNLABELED (Main constituent)	(CAS No) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1	100	Xn; R22 Carc.Cat.1; R45
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
100% ETHYLENE GLYCOL UNLABELED (Main constituent)	(CAS No) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1	100	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

Full text of R- and H-statements: see section 16

Name	Product identifier	%	GHS-US classification
100% ETHYLENE GLYCOL UNLABELED (Main constituent)	(CAS No) 107-21-1	100	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

Full text of H-statements: see section 16

3.2. Mixture

Not applicable

100% ETHYLENE GLYCOL UNLABELED ULM-71

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
- First-aid measures after inhalation : If breathed in, move person to fresh air. If not breathing, give artificial respiration. Consult a physician.
- First-aid measures after skin contact : Wash off with soap and plenty of water. Consult a physician.
- First-aid measures after eye contact : Flush eye with water for 15 minutes. Get medical attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May be harmful if inhaled. Causes respiratory tract irritation.
- Symptoms/injuries after skin contact : May be harmful if absorbed through skin. Causes skin irritation.
- Symptoms/injuries after eye contact : Causes eye irritation.
- Symptoms/injuries after ingestion : Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Firefighting instructions : Wear self contained breathing apparatus for fire fighting if necessary.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protective equipment. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation. Evacuate personnel to safe area.

6.1.1. For non-emergency personnel

- Emergency procedures : Use personal protective equipment. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

- For containment : Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.
- Methods for cleaning up : Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Normal measures for preventive fire protection.
- Precautions for safe handling : Avoid breathing Avoid breathing dust, mist or spray.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed in a cool, dry and well-ventilated place.
- Storage conditions : Store at room temperature away from light and moisture.

7.3. Specific end use(s)

No additional information available

100% ETHYLENE GLYCOL UNLABELED ULM-71

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

100% ETHYLENE GLYCOL UNLABELED (107-21-1)

USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	125.0000000000 mg/m ³
----------	---	----------------------------------

8.2. Exposure controls

Personal protective equipment : Safety glasses. Gloves. Protective clothing. Respiratory protection of the dependent type.



Hand protection : Wear suitable protective clothing and gloves.

Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : When appropriate, use NIOSH/CEN approved respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 62.07 g/mol
Colour	: Colourless.
Odour	: No data available.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: 1
Melting point	: -13 °C (9 °F)
Freezing point	: No data available
Boiling point	: 196 - 198 °C (385 - 388 °F)
Flash point	: 111 °C (232 °F) - closed cup
Auto-ignition temperature	: 400 °C (752 °F)Auto-flammability
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.11 hPa (0.08 mmHg) at 20 °C (68 °F). 0.13 hPa (0.10 mmHg) at 20 °C (68 °F)
Relative vapour density at 20 °C	: 2.14 - (Air = 1.0)
Relative density	: No data available
Density	: 1.113 g/ml at 25 °C (77 °F)
Solubility	: Water: Completely miscible
Log Pow	: -1.36
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 3.2 - 15.3 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

100% ETHYLENE GLYCOL UNLABELED ULM-71

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Not available.

10.5. Incompatible materials

Strong acids, Strong oxidizing agents, Strong bases, Aldehydes, Aluminum.

10.6. Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

100% ETHYLENE GLYCOL UNLABELED (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rabbit	10626 mg/kg
ATE CLP (oral)	500.000 mg/kg bodyweight
ATE CLP (dermal)	10626.000 mg/kg bodyweight

Skin corrosion/irritation	: Not classified No data available
Serious eye damage/irritation	: Not classified Eyes - rabbit - Mild eye irritation - 24 h
Respiratory or skin sensitisation	: Not available No data available
Germ cell mutagenicity	: Not available
Carcinogenicity	: This product is or contains a component that is not classifiable as to its carcinogenicity on its IARC, ACGIH, NTP, or EPA classification.
Reproductive toxicity	: Laboratory experiments have shown teratogenic effects. Overexposure may cause reproductive disorders with laboratory animals.
Specific target organ toxicity (single exposure)	: Not classified No data available
Specific target organ toxicity (repeated exposure)	: May cause damage to organs (kidneys) through prolonged or repeated exposure (in contact with skin, if inhaled, if swallowed). No data available
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Nausea. Vomiting. Abdominal pain. Weakness. Muscle tenderness. Respiratory failure. Convulsions. Cardiovascular collapse. Pulmonary edema. Hypocalcemic tetany. Severe metabolic acidosis. Liver injury may occur. Without treatment, death may occur in 8 to 24 hours. Renal failure. Brain and liver damage.
Symptoms/injuries after inhalation	: May be harmful if inhaled. Causes respiratory tract irritation.
Symptoms/injuries after skin contact	: May be harmful if absorbed through skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

100% ETHYLENE GLYCOL UNLABELED (107-21-1)	
LC50 fish 1	18500 mg/l Oncorhynchus mykiss (rainbow trout) - 96h
LC50 other aquatic organisms 1	> 10000 mg/l Leuciscus idus (Golden orfe) - 48 h
EC50 Daphnia 1	74000 mg/l Daphnia magna (Water flea) - 24 h
LC50 other aquatic organisms 2	41000 mg/l Daphnia magna (Water flea) - 48 h
NOEC (acute)	32000 - 39140 mg/l Pimephales promelas (fathead minnow) - Min: 7 d Max: 96 h
NOEC chronic algae	24000 mg/l Daphnia (Water flea) - 48 h

12.2. Persistence and degradability

100% ETHYLENE GLYCOL UNLABELED (107-21-1)	
BOD (% of ThOD)	Ratio BOD/ThBOD 0.78%

12.3. Bioaccumulative potential

100% ETHYLENE GLYCOL UNLABELED (107-21-1)	
Bioconcentration factor (BCF REACH)	0.6 50 mg/l- other fish - 61 d

100% ETHYLENE GLYCOL UNLABELED ULM-71

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

100% ETHYLENE GLYCOL UNLABELED (107-21-1)	
Log Pow	-1.36

12.4. Mobility in soil

100% ETHYLENE GLYCOL UNLABELED (107-21-1)	
Ecology - soil	Not available.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.
- Waste treatment methods : Offer surplus and non-recyclable solutions to a licensed disposal company.
- Ecology - waste materials : Dispose as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

- UN-No.(DOT) : 3082
- DOT NA no. UN3082

14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.
- Transport hazard class(es) (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
- Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



- DOT Symbols : G - Identifies PSN requiring a technical name
- Packing group (DOT) : III - Minor Danger
- DOT Special Provisions (49 CFR 172.102) : 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.
146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.
173 - An appropriate generic entry may be used for this material.
335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leakproof when used as bulk packaging.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 155
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
- DOT Packaging Bulk (49 CFR 173.xxx) : 241
- DOT RQ : 5000 lbs

100% ETHYLENE GLYCOL UNLABELED ULM-71

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Marine pollutant : No

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : IMDG/IATA: Not dangerous goods.

Overland transport

Packing group (ADR) : III
Class (ADR) : 9 - Miscellaneous dangerous substances and articles
Hazard identification number (Kemler No.) : 90
Classification code (ADR) : M6
Danger labels (ADR) : 9 - Miscellaneous dangerous substances and articles



Orange plates :

Tunnel restriction code : E
Limited quantities (ADR) : 5l
EAC code : •3Z
Excepted quantities (ADR) : E1

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No : 171

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : No limit
Civil Aeronautics Law : Miscellaneous dangerous substances & articles (Hazardous materials notice Appended Table 1 Article 194 of the Enforcement Regulations)

14.4. Environmental hazards

Other information : No supplementary information available.

14.5. Special precautions for user

Special transport precautions : IMDG/IATA: Not dangerous goods.

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

100% ETHYLENE GLYCOL UNLABELED (107-21-1)

Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

100% ETHYLENE GLYCOL UNLABELED ULM-71

Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

100% ETHYLENE GLYCOL UNLABELED (107-21-1)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

100% ETHYLENE GLYCOL UNLABELED(107-21-1)

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List WARNING! This product contains a chemical known by the state of California to cause birth defects or other reproductive harm.
----------------------------	--


SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H302	Harmful if swallowed
H373	May cause damage to organs through prolonged or repeated exposure
R22	Harmful if swallowed
R45	May cause cancer
Xn	Harmful

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard

CIL Multi-Solvent Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product