



# FLUORANTHENE UNLABELED 200 UG/ML IN ISOCTANE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/12/2017

Revision date:

Version: 1.0

ULM-7421-S

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixtures  
Product name : FLUORANTHENE UNLABELED 200 UG/ML IN ISOCTANE  
Product code : ULM-7421-S

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : For professional use only

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

#### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-703-741-5970 (24 hours)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
STOT SE 3 H336  
Asp. Tox. 1 H304  
Aquatic Acute 1 H400  
Aquatic Chronic 1 H410

Full text of hazard classes and H-statements : see section 16

##### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R38  
N; R50/53  
R67  
F; R11  
Xn; R65

Full text of R-phrases: see section 16

##### GHS-US classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
STOT SE 3 H336  
Asp. Tox. 1 H304  
Aquatic Acute 1 H400  
Aquatic Chronic 1 H410

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Liver, Kidney.

# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S


## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazard statements (CLP) :


H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof ventilating, lighting, electrical equipment  
P261 - Avoid breathing vapours, spray, mist, gas, fume, dust  
P264 - Wash hands, forearms and face thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment

#### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P210 - Keep away from sparks, open flames, hot surfaces, heat. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing mist, spray, vapours, gas, fume, dust  
P264 - Wash hands, forearms and face thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P301+P310 - If swallowed: Immediately call a doctor  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P312 - Call a doctor if you feel unwell  
P321 - Specific treatment (see Hazard pictograms (CLP) on this label)  
P331 - Do NOT induce vomiting  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing powder to extinguish  
P391 - Collect spillage  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC No) 208-759-1 (EC Index No) 601-009-00-8 (REACH-no) 01-2119457965-22	99.971	Xi; R38 N; R50/53 R67 F; R11 Xn; R65
FLUORANTHENE UNLABELED	(CAS No) 206-44-0 (EC No) 205-912-4 (Unlabeled)	0.029	Xn; R22 N; R50/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ISOOCTANE UNLABELED	(CAS No) 540-84-1 (EC No) 208-759-1 (EC Index No) 601-009-00-8 (REACH-no) 01-2119457965-22	99.971	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
FLUORANTHENE UNLABELED	(CAS No) 206-44-0 (EC No) 205-912-4 (Unlabeled)	0.029	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
ISOOCTANE UNLABELED	(CAS No) 540-84-1	99.971	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
FLUORANTHENE UNLABELED	(CAS No) 206-44-0	0.029	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May cause drowsiness or dizziness.
Symptoms/injuries after inhalation	: May be fatal if swallowed and enters airways.
Symptoms/injuries after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/injuries after eye contact	: May cause severe irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Flood fire area with water from a distance.

# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapour.  
Explosion hazard : May form flammable/explosive vapour-air mixture.  
Reactivity : Vapours may form flammable mixture with air. Highly flammable liquid and vapour.

### 5.3. Advice for firefighters

- Firefighting instructions : Wear a self contained breathing apparatus.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, mist, gas. Avoid contact with skin and eyes. Use personal protective equipment as required. Remove all sources of ignition. Ensure adequate air ventilation. Provide adequate ventilation to minimize dust and/or vapour concentrations.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

- Stop leak without risks if possible. Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Vacuum with an equipment that avoids ignition risk. This material and its container must be disposed of in a safe way, and as per local legislation.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

### 6.4. Reference to other sections

- No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Avoid all contact with skin, eyes, or clothing.  
Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist, spray, vapours. Avoid contact with skin and eyes.  
Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment. Keep dry. Store in tightly closed, leak-proof containers. Containers which are opened should be properly resealed and kept upright to prevent leakage.  
Storage conditions : Store at room temperature away from light and moisture.  
Incompatible materials : Heat sources.

### 7.3. Specific end use(s)

- No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	300.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract irritation
ISOOCTANE UNLABELED (540-84-1)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	300.00000000 ppm Basis: USA. ACGIH Threshold Limit Values (TLV)

# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ISOOCTANE UNLABELED (540-84-1)		
Italy - Portugal - USA ACGIH	Remark (ACGIH)	Upper Respiratory Tract irritation
FLUORANTHENE UNLABELED (206-44-0)		
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> Basis: California permissible exposure limits for chemical contaminants (Title 8, Article 107)

### 8.2. Exposure controls

- Appropriate engineering controls : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Protective goggles. Protective clothing. Self-contained breathing apparatus.



- Materials for protective clothing : Wear suitable protective clothing and gloves.
- Hand protection : Wear suitable protective clothing and gloves.
- Eye protection : Wear eye protection. Chemical goggles or face shield with safety glasses. Safety glasses.
- Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator.
- Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

*The properties listed below are for the solvent, the main component of this mixture.*

- Physical state : Liquid
- Appearance : Liquid.
- Molecular mass : 114.23 g/mol
- Colour : Colourless.
- Odour : No data available
- Odour threshold : No data available
- pH : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Melting point : -107 °C (-161 °F)
- Freezing point : No data available
- Boiling point : 98 - 99 °C (208 - 210 °F) at 1,013 hPa (760 mmHg)
- Flash point : -12 °C (10 °F) - closed cup
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : Not applicable
- Vapour pressure : 55 hPa (41 mmHg) at 21 °C (70 °F); 117 hPa (88 mmHg) at 37.8 °C (100.04 °F)
- Relative vapour density at 20 °C : 3.94 - (Air = 1.0)
- Relative density : No data available
- Density : 0.69 g/ml at 20 °C (68 °F)
- Solubility : Water: insoluble
- Log Pow : 4.6
- Log Kow : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : No data available
- Explosive properties : No data available
- Oxidising properties : No data available
- Explosive limits : 1 - 6 % (V)

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapours may form flammable mixture with air. Highly flammable liquid and vapour.

# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.2. Chemical stability

See storage and expiration date on CoA.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

Sparks. Heat. Direct sunlight. Overheating. Open flame.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE	
LD50 oral rat	> 5000 mg/kg (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	> 33.52 mg/l/4h (OECD Test Guideline 403)

ISOOCTANE UNLABELED (540-84-1)	
LD50 oral rat	> 5000 mg/kg (OECD Test Guideline 401)
LD50 dermal rabbit	> 2000 mg/kg (OECD Test Guideline 402)
LC50 inhalation rat (mg/l)	> 33.52 mg/l/4h (OECD Test Guideline 403)

FLUORANTHENE UNLABELED (206-44-0)	
LD50 oral rat	2000 mg/kg
LD50 dermal rabbit	3180 mg/kg

Skin corrosion/irritation	: Skin. rabbit. Result: Irritating to skin. (OECD 404 method)
Serious eye damage/irritation	: Eyes. rabbit. Result: No eye irritation. (OECD 405 method)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: rat - Unscheduled DNA synthesis
Carcinogenicity	: Not classified
Reproductive toxicity	: Not available
STOT-single exposure	: May cause drowsiness or dizziness
STOT-repeated exposure	: Health hazard - Aspiration hazard No data available
Aspiration hazard	: Aspiration hazard
Potential adverse human health effects and symptoms	: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Affects the liver.
Symptoms/injuries after inhalation	: May be fatal if swallowed and enters airways.
Symptoms/injuries after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/injuries after eye contact	: May cause severe irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. Risk of lung oedema.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water : Very toxic to aquatic life with long lasting effects.

FLUORANTHENE UNLABELED (206-44-0)	
LC50 fish 1	0.0077 mg/l Oncorhynchus mykiss (rainbow trout) - 96 h
EC50 Daphnia 1	> 0.005 - 0.01 mg/l Immobilization EC50 - Daphnia magna (Water flea) - 3 d
EC50 Daphnia 2	0.78 mg/l Immobilization EC50 - Daphnia magna (Water flea) - 20 h
NOEC (acute)	560 mg/l Cyprinodon variegatus (sheepshead minnow) - 96 h
NOEC chronic crustacea	0.085 mg/l Daphnia magna (Water flea) - 48 h

# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.2. Persistence and degradability

#### FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

Log Pow	4.6
---------	-----

#### ISOOCTANE UNLABELED (540-84-1)

Log Pow	4.6
---------	-----

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : Very toxic to aquatic life with long lasting effects. Avoid release to the environment. Disposal must be done according to official regulations.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.

Product/Packaging disposal recommendations: : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Ecology - waste materials : Dispose of as unused product.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No.(DOT) : 1262  
DOT NA no. UN1262

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Octanes  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 242

### 14.3. Additional information

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

### Overland transport

Packing group (ADR) : II



# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code (ADR) : F1  
Danger labels (ADR) : 3 - Flammable liquids



Orange plates :

Tunnel restriction code (ADR) : D/E  
Limited quantities (ADR) : 11  
EAC code : 3YE  
Excepted quantities (ADR) : E2

### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.  
MFAG-No : 128

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L  
(49 CFR 173.27)  
DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)  
Civil Aeronautics Law : Flammable liquids

### 14.4. Environmental hazards

Dangerous for the environment :



Other information : No supplementary information available.

### 14.5. Special precautions for user

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
ISOOCTANE UNLABELED (540-84-1)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
FLUORANTHENE UNLABELED (206-44-0)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.



# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

FLUORANTHENE UNLABELED (206-44-0)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

### 15.2. International regulations

#### CANADA

FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE
Listed on the Canadian DSL (Domestic Substances List)

#### 15.2.1. National regulations

No additional information available

### 15.3. US State regulations

#### FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

#### ISOOCTANE UNLABELED (540-84-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

#### FLUORANTHENE UNLABELED (206-44-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

#### ISOOCTANE UNLABELED (540-84-1)

##### State or local regulations

U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List

#### FLUORANTHENE UNLABELED (206-44-0)

##### State or local regulations

U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1

# FLUORANTHENE UNLABELED 200 UG/ML IN ISOOCTANE

ULM-7421-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R11	Highly flammable
R22	Harmful if swallowed
R38	Irritating to skin
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapours may cause drowsiness and dizziness
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



### HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 3 Serious Hazard

Physical

: 0 Minimal Hazard

CIL Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*