



# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 20/01/2015

Revision date:

:

Version: 1.0

### ULM-8531-S

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixtures  
Product name. : OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE  
Product code : ULM-8531-S

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only.

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-202-483-7616 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225  
Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Dermal) H312  
Acute Tox. 4 (Inhalation) H332  
Eye Irrit. 2 H319

Full text of H-phrases: see section 16

#### Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11

Full text of R-phrases: see section 16

#### Classification (GHS-US)

Flam. Liq. 2 H225  
Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Dermal) H312  
Acute Tox. 4 (Inhalation) H332  
Acute Tox. 4 (Inhalation:vapour) H332  
Eye Irrit. 2A H319

#### Adverse physicochemical, human health and environmental effects

Lungs, Blood, Kidney, Liver, Central nervous system.

# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. Label elements

#### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

ACETONITRILE UNLABELED

Hazard statements (CLP) :


H225 - Highly flammable liquid and vapor  
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled  
H319 - Causes serious eye irritation

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P261 - Avoid breathing fume, mist, spray, vapors  
P264 - Wash both hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area

#### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing fume, mist, spray, vapors  
P264 - Wash Both hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear eye protection, face protection, protective clothing, protective gloves  
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER/doctor/physician if you feel unwell  
P330 - If swallowed, rinse mouth  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use Alcohol resistant foam., Carbon dioxide., Dry chemical., Water spray for extinction  
P403+P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/container to Comply with applicable regulations.

### 2.3. Other hazards

No additional information available

# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ACETONITRILE UNLABELED	(CAS No) 75-05-8 (EC no) 200-835-2 (EC index no) 608-001-00-3	99.9873	F; R11
OXYBENZONE UNLABELED	(CAS No) 131-57-7 (unlabeled) (EC no) 205-031-5	0.0127	Xi; R36/37/38

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETONITRILE UNLABELED	(CAS No) 75-05-8 (EC no) 200-835-2 (EC index no) 608-001-00-3	99.9873	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
OXYBENZONE UNLABELED	(CAS No) 131-57-7 (unlabeled) (EC no) 205-031-5	0.0127	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Name	Product identifier	%	Classification (GHS-US)
ACETONITRILE UNLABELED	(CAS No) 75-05-8	99.9873	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319

Full text of R-, H- and EUH-phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
First-aid measures after inhalation	: If breathed in, move person to fresh air. If not breathing, give artificial respiration. Consult a physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
First-aid measures after ingestion	: Rinse mouth. Call a POISON CENTER/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May be harmful if inhaled. Causes respiratory tract irritation.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Vapors may form explosive mixture with air.

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray to cool unopened containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : No naked lights. No smoking. Use only non-sparking tools.  
Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.  
Storage conditions : Store at room temperature away from light and moisture.  
Incompatible materials : Heat sources.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.0000000000 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.
ACETONITRILE UNLABELED (75-05-8)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.0000000000 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.
USA OSHA	OSHA PEL (TWA) (ppm)	40.0000000000 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	60.0000000000 ppm

#### 8.2. Exposure controls

Personal protective equipment : Gas mask with filter type NO at conc. in air >. Protective clothing. Protective goggles. Self-contained breathing apparatus. Gloves.



Hand protection : Wear suitable protective clothing and gloves.  
Eye protection : Wear safety glasses with side shields (or goggles) and a face shield.  
Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Respiratory protection : When appropriate, use NIOSH/CEN approved respirator.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Physical state	: Liquid
Appearance	: Liquid, clear.
Molecular mass	: 41.05
Color	: Colourless.
Odor	: ether-like.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: -48 °C (-54°F)
Freezing point	: No data available
Boiling point	: 81 - 82 °C (178 - 180 °F)
Flash point	: 2.0 °C (35.6 °F) - closed cup
Self ignition temperature	: 523 °C (973 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 73.18 hPa (54.89 mmHg) at 15°C (59 °F), 119.81 hPa (89.86 mmHg) at 25°C(77 °F)
Relative vapor density at 20 °C	: 1.42 - (Air = 1.0)
Relative density	: No data available
Solubility	: Water: 100 %
Log Pow	: -0.34
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 4.4 - 16 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Vapors may form explosive mixture with air.

### 10.2. Chemical stability

See storage and expiration date on CoA.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Open flame. Direct sunlight.

### 10.5. Incompatible materials

Acids, Bases, Oxidizing agents, Reducing agents, Alkali metals.

### 10.6. Hazardous decomposition products

May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE	
LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	≥ 26.8 mg/l
LC50 inhalation rat (ppm)	7551 ppm - 8h
ATE (oral)	500.000 mg/kg body weight
ATE (dermal)	1100.000 mg/kg body weight
ATE (gases)	4500.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
ATE (dust, mist)	1.500 mg/l/4h

# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACETONITRILE UNLABELED (75-05-8)	
LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	≥ 26.8 mg/l
LC50 inhalation rat (ppm)	7551 ppm - 8h
ATE (oral)	500.000 mg/kg body weight
ATE (dermal)	2000.000 mg/kg body weight
ATE (gases)	4500.000 ppmV/4h
ATE (vapors)	11.000 mg/l/4h
ATE (dust, mist)	1.500 mg/l/4h

OXYBENZONE UNLABELED (131-57-7 (unlabeled))	
LD50 oral rat	7400 mg/kg
ATE (oral)	7400.000 mg/kg body weight

Skin corrosion/irritation	: Not classified Skin - rabbit - No skin irritation
Serious eye damage/irritation	: Causes serious eye irritation. Eyes - Rabbit - Irritating to eyes
Respiratory or skin sensitization	: Did not cause sensitization on laboratory animals. Buehler Test - guinea pig - Did not cause sensitisation on laboratory animals.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: No evidence of carcinogenicity in animal studies (when indicated).
Reproductive toxicity	: Animal testing did not show any effects on fertility.
Specific target organ toxicity (single exposure)	: Not classified The substance or mixture is not classified as specific target organ toxicant.
Specific target organ toxicity (repeated exposure)	: Not classified The substance or mixture is not classified as specific target organ toxicant.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Harmful if swallowed. Harmful in contact with skin.
Symptoms/injuries after inhalation	: May be harmful if inhaled. Causes respiratory tract irritation.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE	
LC50 fish 1	1640.00 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 Daphnia 1	3600 mg/l Daphnia magna (Water flea) - 48h
NOEC (chronic)	640 mg/l Daphnia magna (Water flea) - 14d

ACETONITRILE UNLABELED (75-05-8)	
LC50 fish 1	1640.00 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 Daphnia 1	3600 mg/l Daphnia magna (Water flea) - 48h
NOEC (chronic)	640 mg/l Daphnia magna (Water flea) - 14d

### 12.2. Persistence and degradability

OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE		
Persistence and degradability	Biodegradability	Result: - Readily biodegradable.

ACETONITRILE UNLABELED (75-05-8)		
Persistence and degradability	Biodegradability	Result: - Readily biodegradable.

OXYBENZONE UNLABELED (131-57-7 (unlabeled))		
Persistence and degradability	Not available.	

# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.3. Bioaccumulative potential

OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE	
Log Pow	-0.34
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).
ACETONITRILE UNLABELED (75-05-8)	
Log Pow	-0.34
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).
OXYBENZONE UNLABELED (131-57-7 (unlabeled))	
Bioaccumulative potential	Not available.

### 12.4. Mobility in soil

OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE	
Ecology - soil	Not expected to absorb on soil.
ACETONITRILE UNLABELED (75-05-8)	
Ecology - soil	Not expected to absorb on soil.
OXYBENZONE UNLABELED (131-57-7 (unlabeled))	
Ecology - soil	Not available.

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and Local environmental control regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

## SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

### 14.1. UN number

UN-No.(DOT) : 1648  
DOT NA no. UN1648

### 14.2. UN proper shipping name

DOT Proper Shipping Name : Acetonitrile  
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger  
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 242

# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

Packing group (ADR) : II  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code (ADR) : F1  
Danger labels (ADR) : 3 - Flammable liquids



Orange plates :

Tunnel restriction code : D/E  
Limited quantities (ADR) : 1L  
EAC : •2YE  
Excepted quantities (ADR) : E2

#### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.  
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"  
MFAG-No : 127

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5L  
(49 CFR 173.27)  
DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)  
Civil Aeronautics Law : Flammable liquids

### 14.4. Environmental hazards

Other information : No supplementary information available.

### 14.5. Special precautions for user

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

#### ACETONITRILE UNLABELED (75-05-8)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---



# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

##### OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### ACETONITRILE UNLABELED (75-05-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

#### 15.2.1. National regulations

No additional information available

### 15.3. US State regulations

#### OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE()

State or local regulations

U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### ACETONITRILE UNLABELED (75-05-8)

U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
R11	Highly flammable
R36/37/38	Irritating to eyes, respiratory system and skin
F	Highly flammable
Xi	Irritant

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



# OXYBENZONE UNLABELED 100 UG/ML IN ACETONITRILE ULM-8531-S

## Safety Data Sheet

according to Regulation (EC) No. 453/2010 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### HMIS III Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard
Physical	: 0 Minimal Hazard

CIL Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*