



# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 19/01/2016

Revision date: 02/06/2020

Supersedes: 19/01/2016

Version: 1.1

ULM-9852-S

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixtures  
Product name : BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE  
Product code : ULM-9852-S

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : For professional use only

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.  
50 Frontage Road  
Andover, MA 01810  
USA

USA: 1-800-322-1174 Int: 1-978-749-8000  
[cilsales@isotope.com](mailto:cilsales@isotope.com) [www.isotope.com](http://www.isotope.com)

### Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)  
International: 1-703-741-5970 (24 hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225  
Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Dermal) H312  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Eye Irrit. 2 H319

Full text of hazard classes and H-statements : see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11  
Xn; R20/21/22  
Xi; R36

Full text of R-phrases: see section 16

#### GHS-US classification

Flam. Liq. 2 H225  
Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Dermal) H312  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Eye Irrit. 2A H319

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Lungs, Blood, Kidney, Liver, Central nervous system.

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.2. Label elements

#### Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

ACETONITRILE UNLABELED

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapor  
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled  
H319 - Causes serious eye irritation

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P261 - Avoid breathing vapors, mist, gas.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.

#### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, face protection, protective clothing, protective gloves.  
P301+P312 - If swallowed: Call a doctor if you feel unwell  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a doctor if you feel unwell  
P321 - Specific treatment (see Hazardous component(s) for labeling on this label)  
P330 - Rinse mouth.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), dry extinguishing powder to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
ACETONITRILE UNLABELED	(CAS-No.) 75-05-8 (EC-No.) 200-835-2 (EC Index-No.) 608-001-00-3 (REACH-no) 01-2119471307-38	99.987	F; R11 Xi; R36 Xn; R20/21/22
BISPHENOL B UNLABELED	(CAS-No.) 77-40-7 (EC-No.) 201-025-1	0.013	Xn; R22 Xi; R36 R53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ACETONITRILE UNLABELED	(CAS-No.) 75-05-8 (EC-No.) 200-835-2 (EC Index-No.) 608-001-00-3 (REACH-no) 01-2119471307-38	99.987	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
BISPHENOL B UNLABELED	(CAS-No.) 77-40-7 (EC-No.) 201-025-1	0.013	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Chronic 4, H413

Name	Product identifier	%	GHS-US classification
ACETONITRILE UNLABELED	(CAS-No.) 75-05-8	99.987	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319

Full text of R- and H- phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. If not breathing, give artificial respiration. Call a physician immediately. Get immediate medical advice/attention.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Specific measures (see First aid measures on this label). Wash with plenty of soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Explosion hazard : May form flammable/explosive vapor-air mixture.  
Reactivity : Vapors may form explosive mixture with air.

### 5.3. Advice for firefighters

- Firefighting instructions : Wear a self contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus, rubber boots and thick rubber gloves.  
Other information : Use water spray to cool unopened containers.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Use personal protective equipment as required. Avoid breathing vapors, mist, gas. Ensure adequate air ventilation. Evacuate unnecessary personnel. Eliminate all ignition sources if safe to do so. Provide adequate ventilation to minimize dust and/or vapor concentrations. Special attention should be given to low areas/pits where flammable vapors can accumulate.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Dike and contain spill. Disposal should be in accordance with applicable Federal, State and local regulations.  
Methods for cleaning up : Collect spillage. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Avoid all eye and skin contact and do not breathe vapor and mist. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : No open flames. No smoking. Use only non-sparking tools.  
Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands, forearms and face thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Lighting equipment, ventilating equipment.  
Storage conditions : Store at room temperature away from light and moisture.  
Incompatible materials : Heat sources.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.00000000 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	34 mg/m <sup>3</sup> Forms Cyanide in the body.
USA NIOSH	NIOSH REL (TWA) (ppm)	20 ppm Forms Cyanide in the body.
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup> The value in mg/m <sup>3</sup> is approximate.
USA OSHA	OSHA PEL (TWA) (ppm)	40 ppm The value in mg/m <sup>3</sup> is approximate.

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACETONITRILE UNLABELED (75-05-8)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	20.00000000 ppm Lower Respiratory Tract irritation. Not classifiable as a human carcinogen.
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	34 mg/m <sup>3</sup> Forms Cyanide in the body.
USA NIOSH	NIOSH REL (TWA) (ppm)	20 ppm Forms Cyanide in the body.
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup> The value in mg/m <sup>3</sup> is approximate.
USA OSHA	OSHA PEL (TWA) (ppm)	40 ppm The value in mg/m <sup>3</sup> is approximate.

### 8.2. Exposure controls

- Appropriate engineering controls : Handle in accordance with good industrial hygiene and safety procedures.  
Personal protective equipment : Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.



- Materials for protective clothing : Wear suitable protective clothing and gloves.  
Hand protection : Wear suitable protective clothing and gloves.  
Eye protection : Chemical goggles or face shield with safety glasses.  
Skin and body protection : Wear suitable protective clothing, gloves and eye/face protection.  
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.  
Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

- Physical state : Liquid  
Appearance : Liquid, clear  
Molecular mass : 41.05 g/mol  
Color : Colorless  
Odor : Ether-like  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : -48 °C (-54°F)  
Freezing point : No data available  
Boiling point : 81 - 82 °C (178 - 180 °F)  
Flash point : 2 °C (35.6 °F) - closed cup  
Auto-ignition temperature : 523 °C (973 °F)  
Decomposition temperature : No data available  
Flammability (solid, gas) : Highly flammable liquid and vapor  
Vapor pressure : 73.18 hPa (54.89 mmHg) at 15°C (59 °F),  
119.81 hPa (89.86 mmHg) at 25°C(77 °F)  
Relative vapor density at 20 °C : 1.42 - (Air = 1.0)  
Relative density : No data available  
Specific gravity / density : 0.786 g/ml  
Solubility : Water: 100 %  
Log Pow : -0.34  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : 4.4 - 16 vol %

### 9.2. Other information

No additional information available

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Vapors may form explosive mixture with air.

#### 10.2. Chemical stability

See storage and expiration date on CoA.

#### 10.3. Possibility of hazardous reactions

Highly flammable liquid and vapor.

#### 10.4. Conditions to avoid

Heat. Open flame. Direct sunlight. Sparks. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Acids, Bases, Oxidizing agents, Reducing agents, Alkali metals.

#### 10.6. Hazardous decomposition products

May release flammable gases. Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation:dust,mist: Harmful if inhaled.

BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE	
LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	≥ 26.8 mg/l
LC50 inhalation rat (ppm)	7551 ppm - 8h
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	2000.000 mg/kg body weight
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h

ACETONITRILE UNLABELED (75-05-8)	
LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	≥ 26.8 mg/l
LC50 inhalation rat (ppm)	7551 ppm - 8h
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	2000.000 mg/kg body weight
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h

BISPHENOL B UNLABELED (77-40-7)	
LD50 oral rat	4556 mg/kg
LD50 dermal rabbit	> 10250 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight

Skin corrosion/irritation : Not classified  
Skin - Rabbit - No skin irritation

Serious eye damage/irritation : Causes serious eye irritation.  
Rabbit - Eyes - Irritating to eyes

Respiratory or skin sensitization : Did not cause sensitization on laboratory animals. Buehler Test - Guinea pig - Did not cause sensitization on laboratory animals. (OECD 406 method)

Germ cell mutagenicity : Not classified

Carcinogenicity : No evidence of carcinogenicity in animal studies (when indicated).

Reproductive toxicity : Animal testing did not show any effects on fertility.

Specific target organ toxicity – single exposure : Not classified  
The substance or mixture is not classified as specific target organ toxicant.

Specific target organ toxicity – repeated exposure : Not classified  
The substance or mixture is not classified as specific target organ toxicant.

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Treat as cyanide poisoning. Always have on hand a cyanide first-aid kit, together with proper instructions. The onset of symptoms is generally delayed pending conversion to cyanide. Nausea, Vomiting, Diarrhea, Headache, Dizziness, Rash, Cyanosis, Excitement, Depression, Drowsiness, Impaired judgment, Lack of coordination, Stupor, Death. Lungs - Lung edema - Based on human evidence. Harmful if swallowed. Harmful in contact with skin. This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

LC50 fish 1	1640 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 Daphnia 1	3600 mg/l Daphnia magna (Water flea) - 48h
NOEC (chronic)	640 mg/l Daphnia magna (Water flea) - 14d

#### ACETONITRILE UNLABELED (75-05-8)

LC50 fish 1	1640 mg/l Pimephales promelas (fathead minnow) - 96h
EC50 Daphnia 1	3600 mg/l Daphnia magna (Water flea) - 48h
NOEC (chronic)	640 mg/l Daphnia magna (Water flea) - 14d

### 12.2. Persistence and degradability

#### BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

Persistence and degradability	Biodegradability	Result: - Readily biodegradable.
-------------------------------	------------------	----------------------------------

#### ACETONITRILE UNLABELED (75-05-8)

Persistence and degradability	Biodegradability	Result: - Readily biodegradable.
-------------------------------	------------------	----------------------------------

### 12.3. Bioaccumulative potential

#### BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

Log Pow	-0.34
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).

#### ACETONITRILE UNLABELED (75-05-8)

Log Pow	-0.34
Bioaccumulative potential	No bioaccumulation is to be expected (log Pow <= 4).

#### BISPHENOL B UNLABELED (77-40-7)

Log Pow	4.467
---------	-------

### 12.4. Mobility in soil

#### BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

Ecology - soil	Not expected to absorb on soil.
----------------	---------------------------------

#### ACETONITRILE UNLABELED (75-05-8)

Ecology - soil	Not expected to absorb on soil.
----------------	---------------------------------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Other adverse effects	: Avoid release to the environment. Disposal must be done according to official regulations. May cause long lasting harmful effects to aquatic life.
-----------------------	--

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.
------------------------------	--

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Product/Packaging disposal recommendations : Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
- Ecology - waste materials : Dispose of as unused product.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

- UN-No.(DOT) : 1648  
DOT NA no. UN1648

#### 14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Acetonitrile  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger  
DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
Marine pollutant : No

#### 14.3. Additional information

- Other information : No supplementary information available.

#### Overland transport

- Packing group (ADR) : II  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code (ADR) : F1  
Hazard labels (ADR) : 3 - Flammable liquids



- Orange plates : An orange rectangular label with a black border. The number "33" is printed in black in the upper half, and the number "1648" is printed in black in the lower half.

- Tunnel restriction code (ADR) : D/E  
Limited quantities (ADR) : 11  
EAC : •2YE  
Excepted quantities (ADR) : E2



# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

MFAG-No : 127

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)

Civil Aeronautics Law : Flammable liquids

### 14.4. Environmental hazards

Other information : No supplementary information available.

### 14.5. Special precautions for user

### 14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of United States SARA Section 302
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313
ACETONITRILE UNLABELED (75-05-8)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of United States SARA Section 302
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Subject to reporting requirements of United States SARA Section 313

### 15.2. International regulations

#### CANADA

BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE
Listed on the Canadian DSL (Domestic Substances List)

#### 15.2.1. National regulations

No additional information available

### 15.3. US State regulations

BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE()	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

# BISPHENOL B UNLABELED 100 UG/ML IN ACETONITRILE

ULM-9852-S

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ACETONITRILE UNLABELED (75-05-8)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

ACETONITRILE UNLABELED (75-05-8)
<b>State or local regulations</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H319	Causes serious eye irritation
H332	Harmful if inhaled
H413	May cause long lasting harmful effects to aquatic life
R11	Highly flammable
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed
R22	Harmful if swallowed
R36	Irritating to eyes
R53	May cause long-term adverse effects in the aquatic environment
F	Highly flammable
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



### Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

CIL Mixture SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*