



METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 23/01/2015
EO-5275

Revision date: 08/06/2020

Supersedes: 23/01/2015

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixtures
Product name : METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)
Product code : EO-5275

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Cambridge Isotope Laboratories, Inc.
50 Frontage Road
Andover, MA 01810
USA

USA: 1-800-322-1174 Int: 1-978-749-8000
cilsales@isotope.com www.isotope.com

Emergency telephone number

Emergency numbers:

Chemtrec: 1-800-424-9300 (24 hours)
International: 1-703-741-5970 (24 hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of hazard classes and H-statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R10
Xn; R20
Xn; R65
Xi; R36/38
R67

Full text of R-phrases: see section 16

GHS-US classification

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of H statements : see section 16

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Adverse physicochemical, human health and environmental effects

Central Nervous System. Flammable liquid and vapor. May cause drowsiness or dizziness. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: N-NONANE UNLABELED

Hazard statements (CLP)

: H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective clothing, protective gloves.

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US)

: P210 - Keep away from heat, open flames, sparks. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing dust, fume, gas, mist, spray, vapors.
P264 - Wash Both hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective clothing, protective gloves.
P301+P310 - If swallowed: Immediately call a poison center or doctor
P302+P352 - If on skin: Wash with plenty of water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a poison center or doctor if you feel unwell
P321 - Specific treatment (see See the emergency and first aid section of this material safety data sheet. on this label)

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362 - Take off contaminated clothing and wash before reuse.
P370+P378 - In case of fire: Use Alcohol resistant foam, Carbon dioxide, Dry chemical, Water spray to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to Dispose in a safe manner in accordance with local/national regulations

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.999722	R10 Xn; R20 Xn; R65 Xi; R36/38 R67
2,2',5,5'-TETRACB (PCB-52) (13C12, 99%)	(CAS-No.) 208263-80-3 (EC Index-No.) 602-039-00-4	0.000139	Carc.Cat.1; R45 N; R51/53 Xn; R48/20/21/22
2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%)	(CAS-No.) 208263-66-5 (EC Index-No.) 602-039-00-4	0.000139	Xn; R48/20/21/22 N; R50/53 R33

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N-NONANE UNLABELED	(CAS-No.) 111-84-2 (EC-No.) 203-913-4	99.999722	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
2,2',5,5'-TETRACB (PCB-52) (13C12, 99%)	(CAS-No.) 208263-80-3 (EC Index-No.) 602-039-00-4	0.000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%)	(CAS-No.) 208263-66-5 (EC Index-No.) 602-039-00-4	0.000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Name	Product identifier	%	GHS-US classification
N-NONANE UNLABELED	(CAS-No.) 111-84-2	99.999722	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H336 Asp. Tox. 1, H304
2,2',5,5'-TETRACB (PCB-52) (13C12, 99%)	(CAS-No.) 208263-80-3	0.000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%)	(CAS-No.) 208263-66-5	0.000139	STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Risk of lung edema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: For small fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: Vapors may form explosive mixture with air.

5.3. Advice for firefighters

Firefighting instructions	: Wear self contained breathing apparatus for fire fighting if necessary.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
----------------------	--

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For containment	: Contain spillage, then collect with non-combustible absorbent material. Disposal should be in accordance with applicable Federal, State and local regulations. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal.
-----------------	---

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions	: Store at room temperature away from light and moisture.
Incompatible materials	: Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1050 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1050 mg/m ³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.
N-NONANE UNLABELED (111-84-2)		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200.00000000 ppm USA. ACGIH Threshold Limit Values (TLV)
Italy - Portugal - USA ACGIH	Remark (ACGIH)	CNS impair
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1050 mg/m ³ USA. NIOSH Recommended Exposure Limits
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm USA. NIOSH Recommended Exposure Limits
USA NIOSH	Remark (NIOSH)	Central Nervous System impairment
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1050 mg/m ³ USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm USA. OSHA - Table Z-1 Limits for Air Contaminants - 1910.1000
USA OSHA	OSHA PEL (Ceiling) (mg/m ³)	1050 California permissible exposure limits for chemical contaminants.
USA OSHA	OSHA PEL (Ceiling) (ppm)	200 ppm California permissible exposure limits for chemical contaminants.
2,2',5,5'-TETRACB (PCB-52) (13C12, 99%) (208263-80-3)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	0.5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Protective clothing. Protective goggles. Gloves. Self-contained breathing apparatus.



Materials for protective clothing	: Wear suitable protective clothing and gloves.
Hand protection	: protective gloves.

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Chemical goggles or face shield. Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing, gloves and eye/face protection.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Approved respirator.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

The properties listed below are for the solvent, the main component of this mixture.

Physical state	: Liquid
Appearance	: Liquid
Molecular mass	: 128.3 g/mol
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: -53 °C (- 63 °F) - lit
Boiling point	: 151 °C (304 °F) - lit
Flash point	: 31 °C (87.8 °F) - closed cup
Auto-ignition temperature	: 205 °C (401 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapor
Vapor pressure	: 12.4 hPa (9.3 mmHg) at 37.7 °C (99.9 °F)
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.718 g/ml at 25 °C (77 °F)
Solubility	: Water: 0 %
Log Pow	: 5.65
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 0.87 - 2.9 % (V)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapors may form explosive mixture with air.

10.2. Chemical stability

Stable if stored under recommended conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:vapour: Harmful if inhaled.

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)	
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

N-NONANE UNLABELED (111-84-2)	
LC50 inhalation rat (mg/l)	23760 mg/m ³ male - 4 h
ATE CLP (vapors)	11.000 mg/l/4h
Skin corrosion/irritation, Dermal, rat	Result: Skin Irritation (Draize Test)
Additional information	: S. Typhimurium Result: negative

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.
Specific target organ toxicity – repeated exposure : Not classified
Aspiration hazard : May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.
Symptoms/effects after inhalation : Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact : Causes skin irritation. May be harmful in contact with skin.
Symptoms/effects after eye contact : Causes serious eye irritation.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Risk of lung edema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

2,2',5,5'-TETRACB (PCB-52) (13C12, 99%) (208263-80-3)	
LC50 fish 1	>= 0.002 mg/l Pimephales promelas (fathead minnow) - 96 h
EC50 Daphnia 1	>= 0.002 mg/l Daphnia magna (Water flea) - 48 h
NOEC (chronic)	0.1 mg/l Oncorhynchus mykiss (rainbow trout) - 7 d

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

N-NONANE UNLABELED (111-84-2)	
Log Pow	5.65
Bioaccumulative potential	Indication of bioaccumulation.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.6. Other adverse effects

Other adverse effects : Disposal must be done according to official regulations.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste materials should be disposed of under conditions which meet Federal, State, and local environmental control regulations.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Dispose of as unused product.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 1920

DOT NA no. UN1920

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Nonanes

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Other information : No supplementary information available.

Overland transport

Packing group (ADR) : III

Class (ADR) : 3 - Flammable liquid

Hazard identification number (Kemler No.) : 30

Classification code (ADR) : F1

Hazard labels (ADR) : 3 - Flammable liquids



METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Orange plates	:	<table border="1"><tr><td>30</td></tr><tr><td>1920</td></tr></table>	30	1920
30				
1920				
Tunnel restriction code (ADR)	:	D/E		
Limited quantities (ADR)	:	5l		
EAC	:	3Y		
Excepted quantities (ADR)	:	E1		

Transport by sea

DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
MFAG-No	:	128

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	220 L
Civil Aeronautics Law	:	Flammable liquids

14.4. Environmental hazards

Other information	:	No supplementary information available.
-------------------	---	---

14.5. Special precautions for user

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
N-NONANE UNLABELED (111-84-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
2,2',5,5'-TETRACB (PCB-52) (13C12, 99%) (208263-80-3)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.
2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%) (208263-66-5)	
SARA Section 302 Threshold Planning Quantity (TPQ)	Not subject to reporting requirements of the United States SARA Section 302.
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	Not subject to reporting requirements of the United States SARA Section 313.

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

Listed on the Canadian DSL (Domestic Substances List)

N-NONANE UNLABELED (111-84-2)

Listed on the Canadian DSL (Domestic Substances List)

15.2.1. National regulations

No additional information available

15.3. US State regulations

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

N-NONANE UNLABELED (111-84-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

2,2',5,5'-TETRACB (PCB-52) (13C12, 99%) (208263-80-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	

2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%) (208263-66-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	Yes	Yes	Yes	

N-NONANE UNLABELED (111-84-2)

State or local regulations

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

2,2',5,5'-TETRACB (PCB-52) (13C12, 99%) (208263-80-3)

State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List

2,2',3,4,4',5'-HEXACB (PCB-138) (13C12, 99%) (208263-66-5)

State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - New Jersey - Right to Know Hazardous Substance List

METHOD 1614 LABELED INJECTION INTERNAL STOCK SOLUTION (13C12, 99%)

EO-5275

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 and according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Other information : This product is not radioactive. The data given for this product are those of the corresponding unlabeled compound, unless specifically indicated otherwise. Health and safety data for labeled compounds are generally not available, but are assumed to be similar or identical to the corresponding unlabeled compound.


Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
R10	Flammable
R20	Harmful by inhalation
R33	Danger of cumulative effects
R36/38	Irritating to eyes and skin
R45	May cause cancer
R48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R67	Vapors may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

CIL Mixture SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product